



API OIL COUNTRY SEAMLESS CASING

Available lengths range 2 and/or range 3

OD (in)	Wall	ID	Wt. Per Ft.	Grade	End Finish
4	.286	3.428	11.34	J-55 Liner	PE
	.500	3.000	18.69	C-75	LT&C
4 1/2	.205	4.090	9.50	K-55	ST&C
	.224	4.052	10.50	K-55	ST&C
	.250	4.000	11.60	K-55	LT&C
	.250	4.000	11.60	K-55	ST&C
	.250	4.000	11.60	N-80	LT&C
	.250	4.000	11.60	P-110	LT&C
	.290	3.920	13.50	L-80	LT&C
	.290	3.920	13.50	N-80	ST&C
	.290	3.920	13.50	N-80	LT&C
	.290	3.920	13.50	P-110	LT&C
	.337	3.826	15.10	P-110	LT&C
	5	.220	4.560	11.50	K-55
.253		4.494	13.00	K-55	ST&C
.296		4.408	14.87	K-55	PE
.296		4.408	15.00	K-55	ST&C
.296		4.408	14.87	N-80	PE
.296		4.408	15.00	N-80	ST&C
.296		4.408	15.00	P-110	ST&C
.314		5.352	20.00	N-80	LT&C
.362		4.276	17.93	N-80	PE
.362		4.276	18.00	N-80	LT&C
.362		4.276	18.00	P-110	LT&C
.362		4.276	18.00	N-80	X LINE CONN
.478	4.044	23.08	P-110	LT&C	
5 1/2	.244	5.012	14.00	K-55	ST&C
	.275	4.950	15.50	K-55	ST&C
	.275	4.950	15.50	K-55	LT&C
	.304	4.892	17.00	K-55	ST&C
	.304	4.892	17.00	K-55	LT&C
	.304	4.892	17.00	L-80	LT&C
	.304	4.892	17.00	N-80	LT&C
	.304	4.892	17.00	N-80	X LINE CONN
	.304	4.892	16.87	N-80	PE
	.304	4.892	17.00	P-110	LT&C
	.361	4.778	20.00	N-80	LT&C
	.361	4.778	19.81	N-80	PE
	.361	4.778	20.00	P-110	LT&C
	.415	4.670	23.00	L-80	LT&C
	.415	4.670	23.00	N-80	LT&C
	.415	4.670	23.00	P-110	LT&C
.476	4.548	26.00	P-110	PE	

OD (in)	Wall	ID	Wt. Per Ft.	Grade	End Finish
6 5/8	.288	6.049	20.00	K-55	ST&C
	.352	5.921	24.00	K-55	ST&C
	.352	5.921	24.00	N-80	LT&C
	.352	5.921	24.00	N-80	ST&C
	.352	5.921	24.00	P-110	LT&C
	.417	5.791	28.00	N-80	LT&C
	.417	5.791	28.00	P-110	LT&C
	.475	5.675	32.00	N-80	LT&C
	.475	5.675	32.00	P-110	LT&C
	7	.231	6.538	17.00	H-40
.272		6.456	20.00	K-55	ST&C
.317		6.366	23.00	K-55	ST&C
.317		6.366	23.00	K-55	LT&C
.317		6.366	23.00	C-75	LT&C
.317		6.366	23.00	N-80	LT&C
.317		6.366	23.00	JL-95	LT&C
.317		6.366	23.00	C-95	LT&C
.362		6.276	26.00	K-55	ST&C
.362		6.276	26.00	K-55	LT&C
.362		6.276	26.00	C-75	LT&C
.362		6.276	26.00	N-80	LT&C
.362		6.276	26.00	P-110	LT&C
.408		6.184	29.00	C-75	LT&C
.408		6.184	29.00	L-80	LT&C
.408		6.184	29.00	N-80	LT&C
.408		6.184	29.00	C-95	LT&C
.408		6.184	28.72	C-95	PE
.408		6.184	29.00	P-110	LT&C
.453		6.094	32.00	L-80	LT&C
.453		6.094	32.00	N-80	LT&C
.453		6.094	32.00	JL-95	LT&C
.453	6.094	32.00	C-95	LT&C	
.453	6.094	32.00	P-110	LT&C	
.498	6.004	35.00	L-80	LT&C	
.498	6.004	35.00	N-80	LT&C	
.498	6.004	35.00	P-110	LT&C	
.498	6.004	35.00	C-75	LT&C	
.498	6.004	35.00	S-95	LT&C	
.540	5.920	38.00	N-80	LT&C	
.540	5.920	38.00	P-110	LT&C	
.540	5.920	38.00	V-150	LT&C	
7 5/8	.250	7.125	20.00	H-40	ST&C
	.300	7.025	24.00	H-40	ST&C
	.300	7.025	24.00	K-55	ST&C
	.328	6.969	26.40	K-55	ST&C
	.328	6.969	26.40	N-80	LT&C
	.375	6.875	29.70	N-80	LT&C
	.375	6.875	29.04	N-80	PE
	.375	6.875	29.70	N-80	X LINE CONN
	.375	6.875	29.04	P-110	LT&C
	.430	6.765	33.70	N-80	LT&C
	.430	6.765	33.70	P-110	LT&C
	.500	6.625	39.00	N-80	LT&C
.500	6.625	39.00	P-110	ST&C	
.500	6.625	39.00	JL-95	LT&C	
.500	6.625	39.00	P-110	LT&C	
.500	6.625	39.00	C-95	LT&C	
.595	6.435	45.30	N-80	PE	
8 5/8	.264	8.097	24.00	K55	ST&C
	.304	8.071	28.00	H-40	ST&C
	.304	8.071	28.00	K-55	ST&C
	.352	7.921	32.00	H-40	ST&C
	.352	7.921	32.00	K-55	ST&C
	.400	7.825	36.00	K-55	ST&C
	.400	7.825	36.00	N-80	LT&C
	.400	7.825	36.00	N-80	X LINE CONN
	.450	7.725	39.29	N-80	PE
	.450	7.725	40.00	N-80	LT&C
.500	7.625	44.00	N-80	LT&C	
.557	7.511	49.00	N-80	LT&C	

OD (in)	Wall	ID	Wt. Per Ft.	Grade	End Finish
9 5/8	.281	9.063	29.30	H-40	ST&C
	.312	9.001	32.30	H-40	ST&C
	.352	8.921	36.00	K-55	ST&C
	.395	8.835	40.00	K-55	ST&C
	.395	8.835	40.00	C-75	LT&C
	.395	8.835	40.00	N-80	LT&C
	.435	8.755	42.70	N-80	PE
	.435	8.755	43.50	N-80	LT&C
	.435	8.755	43.50	L-80	LT&C
	.435	8.755	43.50	N-80	X LINE CONN
	.435	8.755	43.50	P-110	LT&C
	.472	8.681	47.00	L-80	LT&C
	.472	8.681	47.00	C-75	LT&C
	.472	8.681	47.00	C-75	BT&C
	10 3/4	.279	10.192	32.75	H-40
.350		10.050	40.50	K-55	ST&C
.400		9.950	45.50	K-55	ST&C
.450		9.850	51.00	K-55	LT&C
.450		9.850	51.00	K-55	ST&C
.450		9.850	49.50	N-80	PE
.450		9.850	51.00	N-80	ST&C
.450		9.850	51.00	P-110	ST&C
.495		9.760	55.50	N-80	ST&C
.495		9.760	55.50	N-80	ST&C
.495		9.760	55.50	P-110	ST&C
.545		9.535	60.70	P-110	ST&C
.595		9.435	65.70	P-110	ST&C
.650		9.450	71.10	N-80	ST&C
11 3/4		.333	11.084	42.00	H-40
	.375	11.000	47.00	K-55	ST&C
	.435	10.880	54.00	K-55	ST&C
	.489	10.772	60.00	K-55	ST&C
	.489	10.772	60.00	N-80	ST&C
13 3/8	.330	12.715	48.00	H-40	ST&C
	.380	12.615	54.50	K-55	ST&C
	.430	12.515	61.00	K-55	ST&C
	.480	12.415	68.00	K-55	ST&C
	.480	12.415	68.00	N-80	BT&C
	.480	12.415	68.00	K-55	LT&C
	.514	12.347	72.00	L-80	LT&C
16	.375	15.250	65.00	H-40	ST&C
	.438	15.125	75.00	K-55	ST&C
	.495	15.010	84.00	K-55	ST&C
	.656	14.688	109.0	K-55	ST&C
16 5/8	.435	17.755	87.50	K-55	ST&C
20	.438	19.125	94.00	H-40	ST&C
	.438	19.125	94.00	K-55	ST&C
	.438	19.125	94.00	H-40	BT&C
	.500	19.00	106.50	K-55	ST&C
	.635	18.700	133.00	K-55	ST&C
	.812	18.376	169.00	K-55	ST&C



P.O. Box 932 • Breaux Bridge, LA 70517 USA
337.228.1998 • 337.228.1981 Fax
riverview@riverviewresources.com