

**\*\*\*READ & SAVE THESE INSTRUCTIONS \*\*\***  
**MODEL 20335**  
**INSTALLATION & OPERATION INSTRUCTIONS**

1) TOOLS AND MATERIALS REQUIRED

- ❖ Blade Screwdriver
- ❖ Star Screwdriver
- ❖ Wire Cutters
- ❖ Wiring supplies as required by Electrical Code
- ❖ 1 x A-19/60W Lamp (medium base)

**Attention:**

**Before assembling your lighting fixture, please read the following instructions.**

(2) GENERAL

1. To ensure the success of the installation, be sure to read these instructions thoroughly before beginning.
2. All electrical connections must be in accordance with local codes, ordinances, or the National Electrical Code. If you are unfamiliar with methods of installing electrical wiring, secure the services of a qualified licensed electrician.
3. These fixtures are intended for mounting to a standard 4" x 2 1/4" deep metal octagon outlet box. The box must be directly supported by the building structure.
4. Before commencing with the installation, **disconnect the power by turning off the circuit breaker** or by removing the fuse at the fuse box. Turning the power off using the light switch is not sufficient to prevent electrical shock.

**NOTE:**

**The important safeguards and instructions appearing in this manual are not meant to cover all possible conditions and situations that may occur. It must be understood that common sense, caution and care, are factors that cannot be built into any product. The person(s) caring for and operating the fixture must supply these factors.**

(3) UNPACKING THE FIXTURE

On checking the contents of the box you will find;

1. Fixture assembly
2. Hardware packet
3. Glass Diffuser

(4) PREPARE THE FIXTURE

1. If you are replacing an existing fixture, disconnect and remove the old fixture. Expose the supply wiring from the outlet box.
2. Lay the un-assembled fixture on a soft surface and carefully remove all the packing material.
3. Mount the universal crossbar to the J-box, ensuring that the two screws in the crossbar set face outward away from the wall.
4. Place the rectangular Gasket around the fixture back plate to ensure that the fixture maintains its waterproof integrity.
5. Connect the Black wire from the fixture to the Black supply wire and the White fixture wire to the White supply wire, fasten securely with supplied wire nuts and secure wire nuts with UL listed electrical tape (not supplied).
6. Connect the Green ground wire from the fixture to the electrical supply ground wire, or attach the ground wire directly to the ground screw on the universal crossbar.
7. Position the fixture back plate, such that the two screws protruding from the crossbar set are fitted through the supplied holes in the fixture back plate. Secure with the supplied nut and washers.
8. Screw the A-19/60W bulb into the socket.

**DO NOT EXCEED MAXIMUM WATTAGE AS STATED ON WARNING LABEL**

9. Fit glass diffuser onto fixture back plate. Position the cover such that holes in cover align with holes on the fixture back plate. Secure glass diffuser and cover with the four supplied screws.
10. Restore electricity and turn on light.

**CAUTION:**

- **Ensure that the Fitting is Cool and Switched off, Before Changing Bulbs.**
- **Do Not use Bulbs Exceeding Maximum Wattage as Per Caution Label.**
- **Do Not Touch the Bulb while fixture is in operation.**



MODEL NO.:20335

