



› PRINT › COPY › SCAN › FAX

TASKalfa 3011i

BLACK & WHITE
MULTIFUNCTIONAL SYSTEM

POWERFUL PERFORMANCE... CONNECTING PEOPLE AND INFORMATION.



The Kyocera TASKalfa 3011i Black and White MFP brings impressive performance to power your document needs. Print, Copy and Color Scan capabilities, along with advanced finishing options, deliver fast, professional output. A customizable 9" color touch screen offers easy access directly from the MFP to a wide array of flexible features and business applications to optimize workflow, while wireless and remote access capabilities ensure vital information is easily retrievable no matter where your business takes you.

- › Crisp Black and White Output up to 30 Pages per Minute
- › Customizable 9" Color Touch Screen with Intuitive, Tablet-Like Home Screen

- › Robust Portfolio of Business Applications that Can Optimize Your Document Workflow
- › Advanced Finishing Options for Professional Output, including a 1,000-Sheet External Finisher
- › Scalable Paper Capacity for Longer Job Runs
- › Flexible Media Support and Paper Sizes up to 11" x 17"
- › Standard USB Host Interface for On-the-Go Printing and Scanning
- › Efficient Color Scanning up to 160 ipm
- › Convenient Wireless Printing and Scanning
- › Apple AirPrint®, Google Cloud Print™ and KYOCERA Mobile Print Compatible for a Mobile Printing Solution
- › KYOCERA Fleet Services, a Secure Cloud-Based Monitoring System, Optimizes Device Uptime and Reduces Costs

BASIC SPECIFICATIONS

Configuration: Black and White Multifunctional System – Print/Scan/Copy/Optional Fax
Pages Per Minute: Letter: 30 ppm, Legal: 15 ppm, Ledger: 15 ppm
Warm Up Time: 18 Seconds or Less (Power On)
First Page Out: Copy: 3.6 Seconds or Less; Print: 4.2 Seconds or Less
Display: 9" Color Touch Screen Control Panel
Resolution / Bit Depth: 600 x 600 dpi; 9600 x 600 dpi interpolated / 8 bit depth
Memory / Hard Disk Drive: 2 GB RAM / 8 GB SSD / 320 GB HDD Standard
Duplex: Standard Stackless Duplex Supports Statement to Ledger (5.5" x 8.5" – 11" x 17"), 16 lb Bond – 140 lb Index (60 – 160gsm)
Standard Output Tray: Statement - 11" x 17"; 250 Sheets
Electrical Requirements: 120V, 60Hz, 11.6A; 220-240V, 50Hz, 6.3A
Typical Electricity Consumption (TEC): 120V: 1.8 kWh/week; 220V: 1.8 kWh/week
Dimensions / Weight: 23.39" W x 27.40" D x 26.77" H / 127.9 lbs
Maximum Monthly Duty Cycle: 125,000 Pages Per Month

PAPER SUPPLY

Standard Paper Sources:
 Dual 500 Sheet Trays, 100 Sheet MPT; Auto Selection/Switching
Optional Paper Sources:
 Dual 500 Sheet Trays (PF-791), Dual 1,500 Sheet Trays (PF-810)
Paper Capacity:
 Standard: 1,100 Sheets; Maximum: 4,100 Sheets
Paper Size: Trays 1, 2 and (PF-791): 5.5" x 8.5" – 11" x 17"; (PF-810): 8.5" x 11"; MPT: 5.5" x 8.5" – 11" x 17" (Multiple Sheets)
Paper Weight:
 Trays: 16 lb Bond – 90 lb index (60 – 163gsm); MPT: 12 lb Bond – 140 lb Index (45 – 256gsm)
Input Materials:
 Bond Paper, Recycled Paper, Transparencies, Cardstock, Envelopes

SECURITY SPECIFICATIONS

Standard: Local Authentication, Network Authentication (IPsec, HTTPS, LDAP over SSL, SNMPv3); Secure Print (IPP over SSL); Scan to e-mail (POP3/SMTP over SSL); Scan to FTP (FTP over SSL); Scan to SMB/PC/USB; SSL
Optional: Data Security Kit (E): Network Data Encryption, HDD Overwrite Mode, HDD Data Encryption

PRINT SPECIFICATIONS

Standard Controller: Freescale QorIQ T1024 (Dual Core) / 1.0GHz
PDLs / Emulations:
 Standard: PRESCRIBE, PCL6 (5e, XL), KPDL3 (PS3), XPS; Optional: UG-34 IBM ProPrinter, Line Printer, LQ-850
Print Resolution: 600 x 600 dpi; 9600 x 600 dpi interpolated / 8 bit depth
Fonts: 136 KPDL3, 93 PCL6, 8 Windows Vista, 1 Bitmap
Windows OS Compatibility: Windows XP/2003/Vista/2008/7/8/10/Server 2008 R2/Server 2012 R2
Novell OS Compatibility: Novel NetWare 3.x/4.x/5.x/6.x
Mac OS Compatibility: OS 10.x, AirPrint Enabled
UNIX OS Compatibility: Sun OS 4.1.x; Solaris 2.x; AIX; HP-UX(LPR)

Mobile Printing: Apple AirPrint®, Google Cloud Print™, KYOCERA Mobile Print

Interfaces: Standard: 10/100/1000BaseTX, Hi-Speed USB 2.0, 4 USB Host Interfaces, 2 Expansion Slots, Wireless LAN (communication distance 98.5 feet)
 Optional: 10/100/1000BaseTX (IB-50 for Dual NIC); IEEE 802.11 b/g/n IB-51 for Wireless LAN Interface, (communication distance 328.1 feet)

Network Print and Supported Protocols: TCP/IP, NetBEUI, FTP, LPR, IPv6, IPsec, SSL, WSD Print

Drivers: KX Driver, Mini Driver, KX Driver for XPS, XPS Mini Driver, Network Fax Driver, PPD for MAC

Utilities: KYOCERA Net Admin, KYOCERA Net Viewer, PDF Direct Print, Command Center RX

SCAN SPECIFICATIONS

Scan Type: Color and Black & White Scanner
Scan Resolution: 600 dpi, 400 dpi, 300 dpi, 200 dpi, 200 x 100 dpi, 200 x 400 dpi

File Formats: TIFF (MMR compression), PDF (MMR compression), PDF (high compression), OpenXPS, XPS, JPEG

PDF Extension: Searchable PDF (OCR) Option

Scan Speeds:

DP-7120: Simplex: 48 ipm B&W / 48 ipm Color (300 dpi); Duplex: 15 ipm B&W / 15 ipm Color (300 dpi)
DP-7100: Simplex: 80 ipm B&W / 80 ipm Color (300 dpi); Duplex: 48 ipm B&W / 48 ipm Color (300 dpi)
DP-7110: Simplex: 80 ipm B&W / 80 ipm Color (300 dpi); Duplex: 160 ipm B&W / 160 ipm Color (300 dpi)

Connectivity / Supported Protocols: 10/100/1000BaseTX, TCP/IP, Hi-Speed USB 2.0

Scanning Functions: Scan to Folder (SMB), Scan to e-Mail, Scan to FTP, Scan to FTP over SSL, Scan to USB, WSD Scan, TWAIN Scan

Original Size:

Through DP: Statement to Ledger (5.5" x 8.5" – 11" x 17"); Glass: up to 11" x 17"

Drivers: TWAIN Driver, WIA Driver

COPY SPECIFICATIONS

Copy Resolution: 600 x 600 dpi

Image Mode: Text, Photo, Text/Photo, Graphic/Map

Continuous Copy: 1-999/ Auto Reset to 1

Additional Features: Positive/Negative Reverse, Mirror Image, Rotate Copy, Border Erase, Split Copy, Electronic Sort, Margin Shift, Page Number, Form Overlay, XY Zoom, Prevent Bleed Through, Text Stamp, Bates Stamp, Blank Page Skip

Job Management: 1,000 Department Codes, Job Programs, Job Build, Shortcut Keys, Repeat Copy

Magnification / Zoom: Full Size, 4 Reduction, 4 Enlargement Preset Ratios, 25 - 400% in 1% step increments

Document Box: Custom Box, Job Box, Removable Memory Box, Fax Box (with optional Fax System)

DOCUMENT PROCESSOR¹

Type / Capacity:

DP-7120: Reversing Automatic Document Processor / 50 Sheets
DP-7100: Reversing Automatic Document Processor / 140 Sheets
DP-7110: Dual Scan Document Processor / 270 Sheets

Acceptable Originals: 5.5" x 8.5" – 11" x 17"

Acceptable Weights (Simplex / Duplex):

DP-7120: Simplex: 13 - 32 lb Bond (45 – 160gsm); Duplex: 13 - 32 lb Bond (50 – 120gsm)
DP-7100: Simplex: 13 lb Bond - 90 lb Index (35 – 160gsm); Duplex: 16 lb – 32 lb Bond (50 – 120gsm)
DP-7110: Simplex: 13 lb Bond – 120 lb Index (35 – 220gsm); Duplex: 16 lb – 120 lb Index (50 – 220gsm)

FAX SPECIFICATIONS (OPTION)

Fax Type: Fax System 12

Compatibility / Data Compression: G3 Fax / MMR, MR, MH, JBIG

Transmission Speed / Modem Speed: Approximately 3 seconds per page / 33.6 Kbps

Fax Memory: Standard 170 MB

Driver: Network Fax Driver

Fax Functions: Duplex TX/RX, Confidential RX/TX, F-Code RX/TX, Broadcasting, Fax Box, Dual Fax

OPTIONAL 1,000 SHEET FINISHER DF-7120^{3,4}

Stack / Staple Capacity: Main Tray: 1,000 Sheets / 50 Sheets (up to 24 lb Bond 90gsm)

Paper Size: 5.5" x 8.5" – 11" x 17"

Paper Weight: 16 lb Bond – 140 lb Index (60 – 256gsm)

Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 8.5" x 11" – 11" x 17", 13 lb Bond – 93 lb Cover (45 – 256gsm)

Dimensions: 21.57" W x 24.35" D x 41.34" H

OPTIONAL 3,000 SHEET FINISHER DF-791^{2,3}

Stack / Staple Capacity: Main Tray: 3,000 Sheets; Sub Tray(B): 200 Sheets; Sub Tray(C): 50 Sheets / 65 Sheets: 8.5" x 11"; 30 Sheets: 8.5" x 14", 11" x 17"

Paper Size: Main Tray: 8.5" x 11" – 11" x 17"; Sub Tray(B): 5.5" x 8.5" – 11" x 17"

Paper Weight: 16 lb Bond – 140 lb Index (60 – 256gsm)

Edge Staple Position: 3 Positions: Top Left, Bottom Left, Center Bind

Optional Punch: PH-7A 2 and 3 Hole Punch Unit, Supports 8.5" x 11" – 11" x 17", 13 lb Bond – 93 lb Cover (45 – 256gsm)

Dimensions: 23.91" W x 26.32" D x 37.45" H

Optional Multi-Bin Mailbox⁴: MT-730(B) includes 7 Trays; Supports 16 lb Bond – 90 lb Index (60 – 163gsm); Stack Capacity per bin: 100 Sheets: 5.5" x 8.5", 8.5" x 11"; 50 Sheets: 8.5" x 14", 11" x 17"

ADDITIONAL OPTIONS

AK-740 (Bridge Unit for Finisher), **IB-50** Gigabit NIC (Dual NIC), **IB-51** Wireless LAN, Card Authentication Kit (B), Cabinet, Card Reader Holder(E), Keyboard Holder (B), Data Security Kit (E), Scan Extension Kit (A) for Searchable PDF/OCR

¹ Only 1 Document Processor can be installed

² Only 1 Output Option can be installed

³ Requires Bridge Unit Attachment Kit (AK-740)

⁴ Requires DF-791

ONLY FROM KYOCERA

KYOCERA Document Solutions is a global leader in the digital imaging industry, with an award-winning line of document solutions that consistently set the standard for high performance, superior image quality, enhanced workflow applications, ease-of-use and durability.

Looking to streamline your document workflow? KYOCERA offers a robust portfolio of Business Applications that seamlessly and securely integrate with our MFPs. To learn more about which Business Applications are right for your business, visit the Solutions section on our website.

Specifications and design are subject to change without notice.
 For the latest on connectivity visit www.kyoceradocumentsolutions.com/us
 MAC and AirPrint are trademarks of Apple, Inc.
 Google Cloud Print is a trademark of Google, Inc.
 TASKalfa, PRESCRIBE, KX Driver, and Command Center RX are the trademarks of the Kyocera Companies.
 All other trademarks are the property of their respective owners.

KYOCERA Document Solutions America, Inc.
 Headquarters: 225 Sand Road, Fairfield, NJ 07004-0008, USA
 ©2016 KYOCERA Document Solutions America, Inc.
 ICS# 855D400472

