

ROCKWOOL Safe'n'Sound® for Floors and Ceilings

The new 6" thick stone wool batt insulation makes installation in ceilings between floors quicker and easier.

Features and Benefits

- Designed specifically for sound dampening to help prevent noise travelling from one floor to the next – providing a quieter, more comfortable home
- Friction fit between floors in a single layer, simplifying the process for greater efficiency - reducing installation time
- Non-combustible with a melting point of approximately 1177°C (2150°F)
- Water and moisture resistant - does not absorb moisture to maintain insulating value
- Does not rot or promote the growth of fungi or mildew
- GREENGUARD Gold certified - receiving the highest designation for indoor air quality



SKU Profile

Product Number	Stud type	Thickness	Width	Length	Coverage	Classification (minimum order qty.)
292641	16" Wood	6 in. (152.4 mm)	15 1/4 in. (387 mm)	47 in. (1194 mm)	29.9 ft. ² (2.78 m ²)	STD (1 pallet)
292905	19.2" Wood	6 in. (152.4 mm)	19 1/5 in. (487.7 mm)	47 in. (1194 mm)	31.3 ft. ² (2.91 m ²)	NSK (12 pallets)
292908	24" Wood	6 in. (152.4 mm)	23 in. (584 mm)	47 in. (1194 mm)	30 ft. ² (2.79 m ²)	STD (1 pallet)

ROCKWOOL

8024 Esquesing Line
Milton, ON L9T 6W3
Tel: 1 800 265 6878
www.rockwool.com/safensound

