

# XCEL IGA

## Instant Grab Adhesive Sell Sheet

### Product Description

XCEL IGA is a high strength, high viscosity, one-component elastic adhesive for indoor and outdoor applications based on MS Polymer. Specially designed for fast and non-rigid structural bonding in construction, metal industry, auto, marine, etc., with excellent adhesion to most substrates. Completely weather resistant, odourless and does not contain solvents, silicones or isocyanate's.

### Fields of application

Multi-purpose sealing and bonding in the building, automotive and manufacturing sectors.

- ✓ Bonds & Seals to most surfaces
- ✓ Kitchen & bathroom fixtures
- ✓ Counter-tops & back-splashes
- ✓ Windows & doors
- ✓ Wood & moulding/trim
- ✓ Thresholds, Sills, Siding & Vents
- ✓ Ductwork & HVAC
- ✓ Aluminium, Brass, Steel...
- ✓ Polystyrene, SM Insulation Board
- ✓ Stone, Brick, Fibre Cement & Tile
- ✓ Concrete, Glass, Wood & Porcelain
- ✓ Cultured Marble, Granite...

### Main Benefits

- ✓ Seals & bonds wet or dry
- ✓ Interior / exterior - paintable
- ✓ Environmentally friendly No VOC's
- ✓ Tensile strength 575 Psi
- ✓ Permanently waterproof, flexible, crack proof, mould resistant
- ✓ Non - sag
- ✓ Eliminate nails, screws or clamps
- ✓ Vibration and impact-resistant
- ✓ Cures in 24 hrs under normal conditions



### Directions for use

The substrates must be clean, dry, and free of old residues, polish, liquid sealants, wax, dust, grease and other contaminants which may affect the adhesion. Painted surfaces must be well cured and free of loose paint. The product is suitable for many types of construction materials, however, a preliminary adhesion test is recommended on every surface. After substrate preparation, apply with a manual- or pneumatic caulking gun in vertical strips. Press material firmly against substrate and hold for 5 seconds. Un-cured product may be easily removed with Xcel SDC. Cured sealant must be removed mechanically.



Xcel Products Inc. (North America)

T: +1-844-923-5776 | E: [Info@XcelProducts.ca](mailto:Info@XcelProducts.ca) | W: [www.XcelProducts.ca](http://www.XcelProducts.ca)

Xcel Products Limited (United Kingdom)

T: +44 (0845) 5442156 | E: [Info@XcelProducts.co.uk](mailto:Info@XcelProducts.co.uk) | W: [www.XcelProducts.co.uk](http://www.XcelProducts.co.uk)