



Hydropatch Plastic cement

CR225

The CR225 is a specially developed plastic cement for underwater application on completely soggy surfaces. This product is ideal for sealing leaks on roofs, on foundations and even in outdoor basins (except those of drinking water). It forms a durable, waterproof, flexible coating and applies well under all conditions.



Advantages

- Outstanding adhesion under water
- Ideal for urgent repairs
- Water repellent
- Flexible at low temperature
- Good UV resistance

Functions

- Repair
- Seal

Building components

- Roofing
- Foundation

Surfaces

- Asphalt shingles
- Concrete
- Metal
- Wood

Application tools

- Trowel
- Putty knife
- Glove

Application temperature

Any temperature but it is easier to apply the product when it is temperate.

Service temperature

-40°C to 85°C

Covering rate

- 0,32 m²/kg applied 3mm thick
- 1,56 ft²/lbs applied 1/8" thick

Standard

CAN/ONGC 37.5-M89

Colors

Black

% solid

70-80%

Surface preparation

Surfaces must be clean and free of dust, dirt or other contaminants.



Application

During colder periods, keep the product in a temperate place to facilitate its application. Do not apply if rain is expected. To repair joints and cracks, firmly apply enough product in depth to fill all the cavities and close the gaps. The application should be thin, uniform and the repair should extend about 150mm around the broken area. Apply the product in a slight excess above the surface to avoid water accumulation. Close the container after each use.

Drying

Allow about 4h for surface drying and about 48h for complete drying. The drying time depends on the application method, the ambient temperature, the surface and the thickness applied.

Cleaning

Mineral spirits

Storage

The product may be kept in its original sealed container up to 12 months after the date of purchase by the user.

Format

310ml / 4kg / 20kg

Restriction / Caution

Keep out of the reach of children. If the product is applied near a ventilation or air conditioning unit, take the necessary precautions to prevent infiltration of solvent odours toward the inside. Keep open container or freshly applied product away from open flames, sparks or other sources of heat. For outdoor use only.

Warranty

5 years limited warranty when installed and / or applied as recommended by the manufacturer. We will replace the product with a manufacturing defect. Under no circumstances will the manufacturer be liable for any amount exceeding the purchase price of the product used. The consumer must ensure that this product is suitable for the intended use. Because of atmospheric conditions, applicator competence and surface conditions being independent of the manufacturer's control, we limit our liability for one year following the date of purchase, with proof of purchase, to replacement of defective material only in its original hermetic container. Port paid factory (FAB factory).



2645 B. boul. Terra-Jet. Saint-Cyrille-de-Wendover (Qc) J1Z 1B3



819 474-6661



819 474-6681



www.condor.pro

DANGER



Flammable liquid and vapour.

May be fatal if swallowed and enters airways. Causes serious eye irritation. May cause cancer. Suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure.

PRECAUTIONARY: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Do not breathe dust/ fumes/ gas/ mist/ vapours/ spray. Wash exposed and/ or contaminated area thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/ protective clothing/ eye protection/ face protection.

IF SWALLOWED: Do NOT induce vomiting. Immediately call a POISON CENTER or a doctor. **IF IN EYES:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing. **IF EXPOSED:** Call a POISON CENTER or doctor/ physician. Get medical advice/ attention if you feel unwell. If eye irritation persists get medical advice/ attention. **IN CASE OF FIRE:** Use water fog, foam, dry chemical or carbon dioxide. Do not use straight of water. Store in a well ventilated place. Keep cool. Store locked up. Dispose of contents/ container by a local waste disposal company according to regional regulations.