

# Positive Placement PF250S

*Dependable,  
Lightweight,  
Compact and  
Accurate*



## DESCRIPTION/SUGGESTED SPECIFICATIONS

### Positive Placement Tool—

#### DESIGNED FOR PROFESSIONAL FRAMERS

Paslode is proud to introduce the latest customer-backed innovation. The Paslode® 21Z2" Positive Placement® Metal Connecting System is designed to provide installers the optimal way for fastening structural hardware to wood structures. The pneumatic system significantly reduces installation time, allowing jobs to be completed faster and reducing the need for additional labour.

#### POWERFUL



#### FAST



#### DEPENDABLE



## ADVANTAGES

- Dependable
- Accurate
- Lightweight and Compact

## SELECTION CHART

### 30 Degree Positive Placement Nails

LENGTH	SHANK DIAMETER	SHANK	DEGREE	COATING	PRODUCT NUMBER	NAILS PER PACK
1-1/2"	0.148	Smooth	30	Galvanized	650014	3,000
1-1/2"	0.148	Smooth	30	Brite	650026	3,000
1-1/2"	0.148	Smooth	30	Brite	650646	2,500
2-1/2"	0.148	Smooth	30	Brite	650027	1,000

## APPLICATIONS



Joist Hangers

## INCLUDES

- Positive Placement PF250S
- Safety Glasses
- Owner's Manual

## SPECIFICATIONS

#### Part No. 511800

- Weight: 7.8 lbs
- Height: 14"
- Length: 17.4"
- Nail Capacity: 55-60 Nails (2 strips)
- Nail Range: .131" to .162" (Shank)

Magazine Angle: 30 Degrees

Nail Type: 1-1/2" to 2-1/2" Positive Placement Hanger Nails – Brite and Galvanized

Air req: 80-120 PSI

Warranty: 90-day limited on wear parts, 1-year limited on magazine parts, 5-year limited on housing and cap parts