

THERE'S A REASON THEY — call it "building" — A REPUTATION.



| Votes |
|-----------|
| |
| |
| |
| |
| |
| Paslode P |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |





TABLE OF CONTENTS

| Tools at a Glance | . P 4 |
|--|-------|
| Cordless Impulse XP Framing Nailer | P 8 |
| PowerMaster Plus Framing Nailer | P 10 |
| Compact Framing Nailer | P 11 |
| PowerMaster Plus 4" Framing Nailer | P 12 |
| S200-S16 Framing Air Stapler | P 14 |
| S200-W16 Insulation Sheathing Stapler | P 15 |
| IMLi200 18 Gauge Brad Nailer | P 16 |
| IMLi250 16 Gauge Finish Nailer | P 17 |
| Positive Placement Tool PF250S | P 18 |
| 16 Gauge Straight Finish Air Staplerl | P 19 |
| 18 Gauge Brad Nailer | P 21 |
| 18 Gauge Brad Nailer/Stapler | P 22 |
| 18 Gauge Narrow Soffit Stapler | P 24 |
| 18 Gauge Narrow Crown Finisher Stapler | P 25 |
| US-100 Upholstery/Craft Stapler | P 26 |
| HP-100 Headless Pin Nailer | P 27 |
| 20 Gauge Hammer Stapler | P 28 |
| FloorMaster Plus™ | P 29 |
| Miscellaneous Fasteners | P 30 |

TOOL

DESCRIPTION

APPLICATIONS



CORDLESS IMPULSE XP 30°FRAMING NAILER

Drive 1200 nails per fuel cell Drive 9000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced.

Weight: 7.2 lbs Height: 14-1/2" Length: 12" Nail Capacity: 40 Range: 2" - 3-1/4" Shank: .113 - .131

FRAMING, JOISTS, RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS

DESIGNED FOR: FRAMERS & RENOVATORS

PART#:

905800

F350-S POWER MASTER+™

Durable construction requires less maintenance.

Proven performer for tough job site work with less jams or misfires

Powerful. Enduring. Reliable.

Weight: 8.4 lbs Height: 13-3/10" Lenath: 18"

Nail Capacity: (2 strips) 84 Range: 2" - 3-1/2" Shank: .113 - .131

RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS

FRAMING, JOISTS,

DESIGNED FOR: PROFESSIONAL FRAMERS



(see page P 10 for more details)

PART #: 501000

F325R COMPACT FRAMER™

Lightest-framing nailer ever (Only 5.9 lbs) **Smallest Framer Ever** (Only 12' long) **Remodel interiors easier** Compact. Lightweight

Weight: 5.9 lbs Height: 12-9/10" Length: 12-3/10" Range: 2" – 3-1/4" Shank: .113 - .131 Magagine Capacity: 44

FRAMING, JOISTS, RAFTERS, SOFFITS, STAIRS, SHEATHING, CRATING, FENCES AND DECKS

DESIGNED FOR: PROFESSIONAL RENOVATORS



PART #:

NAILER 30°

513000 **PSN100.1 – 4" FRAMING**

Designed to drive 4" nails Powerful to drive into engineered lumber Powerful. Fast. Durable.

Weight: 8.9 lbs Height: 14-1/2" Length: 19" Nail Capacity: 84 Range: 2" - 4" Shank: .113 - .131 LSL, LVL, PSL, AND OSB, **ENGINEERED LUMER FOR FRAMING**

DESIGNED FOR: PROFESSIONAL FRAMERS



PART#:

502900

TOOL (see page P 14 for more details) PART #:

S200 S16P - 16GA. FRAMING AIR STAPLER Heavy duty. Lightweight. Versatile

Weight: 4.9 lbs Height: 10-3/4" Length: 12-3/4" Staple Capacity: 150 Range: 3/4" - 2" Staple Type: 1/2" crown GS16

DESCRIPTION

ROOF SHEATHING, PLYWOOD SHEATHING, **VINYL SIDING** (WITH ATTACHMENT)

APPLICATIONS

S200 W16 - 16GA. **INSULATION SHEATHING** AIR STAPLER

501230

Reliable, Durable, Versatile

Weight: 4.9 lbs Height: 10-3/4" Length: 12-3/4" Staple Capacity: 150 Range: 3/4" - 2"Staple Type: 15/16" Crown

HOUSEWRAP, INSULATION, WIRE LATH AND SHEATHING

(see page P 15 for more details)

501265 PART #:

Drive 1200 nails per fuel cell



IMLi200 - 18GA. **BRAD NAILER**

Drive 12,000 nails per battery charge Proven for over 25 years Durable. Lightweight. Balanced. Weight: 4.5 lbs Height: 11-1/2" Length: 11" Nail Capacity: 100 Range: 3/4" - 2" Shank: 18 Gauge

CROWN, BASEBOARD MOULDINGS, **PANELLING** AND CARPENTRY

903700



IMLi250 16GA. STRAIGHT FINISH NAILER

Drive 1200 nails per fuel cell Drive 12,000 nails per battery charge Proven for over 25 years

Durable. Lightweight. Balanced.

Length: 10-1/2" Nail Capacity: 100 Range: 1-1/4" - 2-1/2"

Weight: 4.6 lbs

Height: 11-3/4"

Shank: 16 ga. Straight

DOOR AND WINDOW TRIM, CASING, CROWN AND **BASEBOARD MOULDING**

PART#:

PART #:

903800

Call our toll free number **800-387-9692** or visit **www.itwconstruction.ca** for general information. Visit Paslode's web site **www.paslode.ca** for the most current product and technical information.



DESCRIPTION TOOL APPLICATIONS POSITIVE PLACEMENT Weight: 7.8 IBS **JOIST HANGERS** Height: 14" **PF250S** Length:17.4" Dependable, Lightweight, Nail Capacity:55-60 Nails (2 strips) **Compact and Accurate** Nail Range: .131" to .162" (Shank) Magazine Angle: 30 Degrees Nail Type: 1-1/2" to 2-1/2" Positive Placement Hanger Nails – Brite and Galvanized PART #: 511800 (see page P 18 for more details) Air reg: 80-120 PSI T250S F16 - 16GA. Weight: 3.90 lbs WINDOW AND DOOR Height: 10" **FINISH NAILER** TRIM/FINISH Length: 10-3/4" Adjustable depth of drive APPLICATIONS, PANELLING Nail Capacity: 100 **Ergonomic design** AND CABINETRY Range: 3/4" - 2-1/2" Lightweight Nail Type: 16 ga. 502140 (see page P 19 for more details) PART #: Weight: 2.9 lbs. WINDOWS, DOORS, P18-200 18 GA. Height: 9-1/2" **BRAD NAILER FURNITURE, TRIM** Length: 10-1/4" Lightweight and well balanced **APPLICATIONS** Nail Capacity: 100 No mar tip Range: 5/8" - 2" Easy to access corners Nail Type: 18 ga. – Smooth, Galvanized Type: 18 ga. (see page P 21 for more details) PART#: P18-200 P18-FS200 18 GA. Weight: 2.9 lbs. WINDOWS, DOORS, Height: 9-1/2" **BRAD NAILER/STAPLER FURNITURE, TRIM** Length: 10-1/4" Lightweight and well balanced **APPLICATIONS** Nail Capacity: 100 No mar tip Range: 5/8" - 2" brad nails Easy to access corners and 5/8" - 1-1/2" staples (3/16" crown) Type: 18 ga. & 3/16 (see page P 22 for more details) PART #: P18-FS200 N18-125 - 1-1/4" Weight: 2.5 lbs. TRIM/FINISH, PLYWOOD, Height: 9" **NARROW SOFFIT STAPLER** SOFFITS/FACIAS, Length: 9-1/4" Specifically designed for soffit UNDERLAYMENT Staple Capacity: 100 installation with long narrow **APPLICATIONS** Range: 3/4" - 1 1/4" nosepiece for tight spots.



(see page P 25 for more details)

Staple Type: 3/16" crown

GSN18

N18-125

PART #:

| 18 GAUGE STAPLERS | (see page P 25 for more details) | N18 150 – 1-1/2" NARROW CROWN FINISH STAPLER Heavy Duty for long life 4000 Shots per batt. charge PART #: N18-150 | Weight: 2.8 lbs. Height: 9-3/4" Length: 11-1/2" Staple Capacity: 100 Range: 3/4" — 1 1/2" Staple Type: 3/16" crown GSN18 | APPLICATIONS TRIM/FINISH, PLYWOOD, SOFFITS/FASCIAS, UNDERLAYMENT APPLICATIONS |
|-------------------------------|----------------------------------|--|---|--|
| APLERS | (see page P 26 for more details) | US-100 — UPHOLSTERY/ CRAFT STAPLER Easy load magazine 5 Staples/second | Weight: 2.00 lbs. Height: 9-1/2" Length: 12-1/2" Staple Capacity: 100 Range: 3/8" — 9/16" Staple Type: 22 ga. Upholstery | UPHOLSTERY, CRAFTS, LIGHT PANELING AND HOME PROJECT APPLICATIONS |
| LITE GAUGE FASTENING STAPLERS | (see page P 27 for more details) | 23GA HEADLESS PIN NAILER Lightweight and compact No mar tip and nail lock out PART #: HP100 | Weight: 1.20 lbs. Height: 9-1/4" Length: 7-3/4" Staple Capacity: 100 Range: 1/2" — 1-1/2" Staple Type: 23 ga. | FINE WOODWORKING AND TRIM WORK |
| LITE GAI | (see page P 28 for more details) | HT550 – 20GA. HAMMER STAPLER Heavy duty, durable, quick clear jam, durable construction PART #: 1013292 | Weight: 2.0 lbs Height: 3-1/4" Length: 11-3/4" Staple Capacity: 168 Crown: 1/2" Staple Length: 5/32" — 5/16" Staple Type: 20 ga. 1/2" crown | CARPET PADDING, INSULATION, ROOF PAPER, HOUSE WRAP |
| FLOORING | | FLOORMASTER PLUS™ 2 IN 1 FLOORING NAILER/ STAPLER Drives staples and cleats to meet flooring manufacturers fastening specifications | Weight: 10.4 lbs Height: 18" Length: 16" Flooring Fasteners: 15ga staples & 16ga L-cleats Fastener Lengths: 2", 1-3/4, 1-1/2" | 3/4" HARDWOOD FLOORING |

F2N1-200

PART #:

(see page P 29 for more details)



IM325XP Cordless Impulse XP Framing Nailer

Portable freedom on the jobsite without hoses or compressors



INCLUDES

Cordless Li-ion Framing Nailer, Model IM325XP Rechargeable 7.4V Li-ion battery

Li-ion battery charger

Rugged carrying case

Owner's manual

Safety glasses

5/32" Hex Wrench

DESCRIPTION/SUGGESTED SPECIFICATIONS

Cordless Impulse XP Framing Nailer—

IT'S MORE THAN A NAILER, IT'S A NAILING SYSTEM THAT GETS THE JOB DONE RIGHT.

The Paslode Lithium Ion cordless Impulse nailer has provided framers and renovators the ability to wood frame without air hoses for over 25 years. New Li-ion battery technology drives 50% more nails per charge. 2-times faster charge time; 2 minute quick charge drives up to 200 nails. Tool free depth of drive adjustment, non slip grip, dual position utility hook, sequential operation triggers.

LIGHTWEIGHT

OUICK LOADING

EASY ACCESS







ADVANTAGES

- Portable, freedom on the jobsite without hoses or compressors
- Heavy-duty rafter/belt hook for taking jobsite
- Non-slip grip provides comfort and reduces hand fatique
- Tool free depth-of-drive nail adjustment changes nail depth in an instant - even while wearing gloves
- Nail lockout feature prevents blank driving

- Compact size fits between 16" o.c. studs, joists and roof trusses
- Li-ion battery provides 50% longer run time (up to 9,000 nails per charge) than NiCd battery
- 1-hour Full Charge; 2-minute Quick Charge for Up to 200 shots
- Lightweight 7.2 lbs. including battery for better comfort and control
- Works in cold temperature down to -10°C

SELECTION CHART

Pro-Strip RounDrive Fuel/Nail Packs

| LENGTH | SHANK DIAMETER | SHANK TYPE | HEAD STYLE | COATING | PRODUCT NUMBER | NAILS PER PACK | FUEL CELLS PER PACK |
|--------|-------------------|---------------|---------------|---------|-------------------|-------------------|---------------------------|
| 2-3/8" | 0.113 | Smooth | Roundrive | Brite | 1238FN | 1,000 | 1 |
| 2-3/8" | 0.113 | Smooth | Roundrive | Brite | 3238FN | 3,000 | 3 |
| 3" | 0.120 | Smooth | Roundrive | Brite | 3300FN | 3,000 | 3 |
| 3-1/4" | 0.120 | Smooth | Roundrive | Brite | 1325FN | 1,000 | 1 |
| 3-1/4" | 0.120 | Smooth | Roundrive | Brite | 3325FN | 3,000 | 3 |

See Page P 13 for additional framing nails that work with this tool.



Cordless Impulse XP Framing Nailer

APPLICATIONS



Framing

Joists and rafters

Soffits

Stairs

Sheathing

Crating

Fences and decks

TOOL ACCESSORIES



Part No. 902513 All Season Orange Fuel Cell



Part No. 902654C Li Ion Battery



Part No. 902667C Lithium Battery Charger



Part No. 901252 Cordless No mar tip



Part No. 401482 Impulse Oil



Part No. 219086 Degreaser

SPECIFICATIONS

Part No. 905800

Weight: 7.2 lbs

Height: 14-1/2"

Length: 12"

Width: 4"

Speed: 2-3 nails per second

Nail Capacity: 40

Range: 2" - 3-1/4"

Shank: .113 — .131

Nail Angle: 30°

Fuel Type: Spare Framing Fuel

Nails per Fuel Cell: Approximately 1200

Fuel life: 21 months from date of manufacture

Battery Life: 9000 nails per charge

Warranty: 1-year full warranty, 5-year limited warranty

INSUL 2 WOOD



Part No. INSULPROBE Insul2Wood — Insulprobe



Part No. IFW-314 & IWF-238 Nail and Washer Combo - 3-1/4" & 2-3/8" with Galvanized Washers (1000/box)



Rigid installation



Applications
Semi-rigid Insulation



House wrap Fastening







PF-350S PowerMaster Plus Framing Nailer

Durability, Balance and Versatility for all jobs



INCLUDES

PowerMaster™ Plus Pneumatic Framing Nailer

Bump fire trigger

Hex wrench (on tool)

Safety glasses

Owner's manual

TOOL ACCESSORIES



Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

PowerMaster Plus Framing Nailer—

DESIGNED FOR PROFESSIONAL FRAMERS

Heavy-duty jobs require a heavy-duty nailer. That's why the pros turn to the proven performance, durability and driving power, only a Paslode pneumatic framing nailer can provide. When used with Paslode nails, this nailing system can help you drive jobs home on time, every time.

POWERFUL



FAST



DEPENDABLE



ADVANTAGES

- Frame full walls faster. Heavy duty power.
- Reliable performance that saves time with less maintenance.
 - Durable construction requires less maintenance.
 - Proven performer for tough job site work with less jams or misfires
 - Compact size fits between 16" o.c. studs, joists and rafters.

- Soft grip handle for comfort
- Bolt-on end plug for easier service
- Depth of drive on the tool rather than the compressor saves time and energy
- Rafter hook, moves out of the way when not in need
- Adjustable air deflector cap

APPLICATIONS



Framing

iiiiiig

Joists and rafters

Soffits

Stairs

Sheathing

Crating

- .

Fences and decks

SPECIFICATIONS

Part No. 501000

Weight: 8.4 lbs

Height: 13-3/10"

Length: 18"

Speed: 12 nails per second*, sequential or selectable operation

Op. Pres. p.s.i (bar): 90 – 120 (5.5 - 8.3)

Nail Capacity: 2 strips (up to 84)
Nail Range: 2" — 3.5" in length,
.113" — .131" shank diameters

Nail Angle: 30°

Nail Type: Paslode RounDrive®

Offset Full Head

Air Req./100p.s.i. (6.9 bar): .082/cycle

Op. Pres. p.s.i (bar): 80 - 120 (5.5 - 8.3)

Warranty: 90-day limited on wear parts, 1-year limited on magazine parts,

5-year limited on housing and cap parts





F325R Compact Framing Nailer

Lightest weight framer ever



FRAMING NAILS SELECTION CHART

INCLUDES

Compact 30° Framing Nailer Safety glasses

Owner's manual

TOOL ACCESSORIES







Part No. 219090
Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

Compact Framing Nailer—

DESIGNED FOR RENOVATORS

With this nailing system, you'll have any interior remodeling job done in no time. Get the access and maneuverability you need in tight spaces with this lightweight yet powerful pneumatic nailing system. When used with Paslode nails, this nailing system can help you drive jobs home on time, every time.

PROFESSIONAL



LIGHTWEIGHT



EASY ACCESS



ADVANTAGES

- Remodel interiors easier. Lightest weight framer ever.
 - Remodel Interiors Fasier
 - First pneumatic nailer made especially with remodeler's needs in mind
 - Fits easily into the tightest spaces such as between 16" o.c. studs
- Great maneuverability to work comfortably overhead
- Lightest-framing nailer ever made: 5.9 lbs
- Quick 2-step nail strip reload
- Soft grip handle for comfort
- Works in bump mode for speed on jobsite

APPLICATIONS



Framing

Sheathing

Joists and rafters

Crating

Soffits

Stairs

Fences and decks

SPECIFICATIONS

Part No. 513000

Weight: 5.9 Pounds

Height: 12-9/10"

Width: 4-3/10"

Length: 12-3/10"

Fastener Range: 2" - 3 1/4"

Shank: .113 - .131

Magazine Capacity: 44

Op. Pres. p.s.i (bar): 90 - 120



PowerMaster Plus 4" Framing Nailer

Proven durability and reliability



INCLUDES

PowerMaster Plus 4" Framing Nailer

Safety glasses

Owner's manual

TOOL ACCESSORIES







Part No. 219090

Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

PowerMaster Plus 4"—

DESIGNED FOR TIMBER FRAMERS

The F400S is the PowerMaster Plus framing nailer with an extended power and driver blade for 4" applications.



FAST

Ō

DEPENDABLE



ADVANTAGES

- PowerMaster Plus Design Proven durability and reliability
- Versatile Drives a variety of nails from 1-1/2" to 4" in length.
- Ergonomic Design Centre of gravity is closer to the trigger, providing better balance.
- Durable And Reliable Rugged design will stand up to the demands of the job in any kind of weather.

APPLICATIONS



LSL, LVL, PSL, and OSB

Wall Sheathing

Framing

Floor Decking

Roof

SPECIFICATIONS

Part No. 502900

Weight: 8.9 lbs

Height: 14-1/2"

Length: 19"

Nail Capacity: 84

Range: 2" - 4"

Shank: .113 - .131

Back of to tool to Nosepiece: 14.5"

Magazine Angle: 30°

Nail Type: 30° Paper Tape, full head/clipped

OP. Pres. p.s.i. (bar): 80 – 120 (5.5 – 8.3)

Warranty: 90-day limited on wear parts,

6-month limited on magazine parts,

1-year limited on housing and cap parts.



Pneumatic Strip Framing Nailers

SELECTION CHART

Pro-Strip RounDrive Nails

| | mp near | | ridiis | | | | | |
|-----------|-------------------|---------------|---------------|---------|-------------------|-------------------|------------------------|----------------------|
| LENGTH | SHANK DIAMETER | SHANK TYPE | HEAD STYLE | COATING | PRODUCT NUMBER | NAILS PER PACK | QUANTITY PER MASTER | QUANTITY PER SKID |
| COATING T | YPE: BRITE | | | | | | | |
| 2" | 0.113 | Smooth | Roundrive | Brite | 097385 | 6,500 | 1 | 80 |
| 2" | 0.113 | Ring | Roundrive | Brite | 650273 | 5,500 | 1 | 80 |
| 2-3/8" | 0.113 | Smooth | Roundrive | Brite | 50238 | 5 Strips | | - |
| 2-3/8" | 0.113 | Smooth | Roundrive | Brite | 404238 | 1,000 | 4 | - |
| 2-3/8" | 0.113 | Smooth | Roundrive | Brite | 097394 | 5,000 | 1 | 96 |
| 2-3/8" | 0.113 | Ring | Roundrive | Brite | 097397 | 5,000 | 1 | 96 |
| 3" | 0.120 | Smooth | Roundrive | Brite | 097971 | 3,000 | 1 | 96 |
| 3" | 0.120 | Ring | Roundrive | Brite | 097973 | 3,000 | 1 | 96 |
| 211 | | | | | 450000 | 2 500 | | |





| COATING | ITING TYPE: BRITE | | | | | | | |
|------------|-------------------|--------|-------------|------------|--------|----------|---|-----|
| 2" | 0.113 | Smooth | Roundrive | Brite | 097385 | 6,500 | 1 | 80 |
| 2" | 0.113 | Ring | Roundrive | Brite | 650273 | 5,500 | 1 | 80 |
| 2-3/8" | 0.113 | Smooth | Roundrive | Brite | 50238 | 5 Strips | | - |
| 2-3/8" | 0.113 | Smooth | Roundrive | Brite | 404238 | 1,000 | 4 | - |
| 2-3/8" | 0.113 | Smooth | Roundrive | Brite | 097394 | 5,000 | 1 | 96 |
| 2-3/8" | 0.113 | Ring | Roundrive | Brite | 097397 | 5,000 | 1 | 96 |
| 3" | 0.120 | Smooth | Roundrive | Brite | 097971 | 3,000 | 1 | 96 |
| 3" | 0.120 | Ring | Roundrive | Brite | 097973 | 3,000 | 1 | 96 |
| 3" | 0.131 | Smooth | Roundrive | Brite | 650830 | 2,500 | 1 | 96 |
| 3-1/4" | 0.120 | Smooth | Roundrive | Brite | 50314 | 5 Strips | 1 | 125 |
| 3-1/4" | 0.120 | Smooth | Roundrive | Brite | 404314 | 1,000 | 4 | - |
| 3-1/4" | 0.120 | Smooth | Roundrive | Brite | 404058 | 3,000 | 1 | 96 |
| 3-1/4" | 0.131 | Smooth | Roundrive | Brite | 650839 | 2,500 | 1 | 96 |
| 3-1/4" | 0.131 | Ring | Roundrive | Brite | 097978 | 2,500 | 1 | 96 |
| 3-1/2" | 0.120 | Smooth | Roundrive | Brite | 404855 | 2,500 | 1 | 96 |
| 3-1/2" | 0.131 | Smooth | Roundrive | Brite | 097987 | 2,500 | 1 | 96 |
| 4" | 0.131 | Smooth | Roundrive | Brite | 2X0788 | 2,500 | 1 | 96 |
| COATING TY | /PE: HOT DIPPE | ED | | | | | | |
| 2" | 0.113 | Ring | Offset Oval | Hot Dipped | 484200 | 1,000 | 4 | - |
| 2" | 0.113 | Ring | Offset Oval | Hot Dipped | 403389 | 2,500 | 1 | 150 |
| 2-3/8" | 0.113 | Ring | Offset Oval | Hot Dipped | 404856 | 2,500 | 1 | 150 |
| 3" | 0.120 | Ring | Offset Oval | Hot Dipped | 404857 | 1,500 | 1 | 150 |
| 3 1/4" | 0.120 | Ring | Offset Oval | Hot Dipped | 50314G | 5 Strips | | - |
| 3-1/4" | 0.120 | Ring | Offset Oval | Hot Dipped | 404858 | 1,500 | | 150 |

Also works with Cordless Impulse Framing Nailer (see page P 8)

PRO-STRIP ROUNDRIVE NAILS FOR USE WITH



POWERMASTER PLUS



COMPACT FRAMER



POWERMASTER PLUS 4" FRAMER



CORDLESS IMPULSE XP FRAMING NAILER



S200-S16 Framing Air Stapler

Compact and lightweight for increased maneuverability



INCLUDES

S200-S16 Framing Air Stapler

Safety glasses

Quick clear

Owner's manual

TOOL ACCESSORIES



Part No. 403720 Pneumatic Oil



Part No. 219090 Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

S200-S16 Framing Air Stapler—

WITH THE RIGHT STAPLER AND STAPLES, YOU'LL HAVE THE JOB DONE IN NO TIME.

Paslode staples drive flush into even the hardest woods. And, because Paslode staples are made for Paslode air staplers, you'll have fewer jams, fewer misfires and faster loading only a Paslode stapling System can deliver.

POWERFUL







ADVANTAGES

- Extended bumper life, over 600,000 cycles without failure
- Two finger trigger provides more control
- Quick-clear nose to clear jams quickly
- Versatile, drives 3/4" 2" standard crown
- Top load magazine for easy reload and reduced nail waste

SELECTION CHART

16 Gauge Standard Crown Staples

| LENGTH | CROWN SIZE | STAPLE POINT | GAUGE | COATING | PRODUCT NUMBER | STAPLES PER PACK |
|--------|------------|-----------------|-------|------------|-------------------|---------------------|
| 1" | 1/2" | Chisel | 16 | Galvanized | 0T5242 | 16,500 |
| 1-1/4" | 1/2" | Chisel | 16 | Galvanized | 0T5238 | 13,500 |
| 1-1/2" | 1/2" | Chisel | 16 | Galvanized | 0T2695 | 10,500 |
| 1-3/4" | 1/2" | Chisel | 16 | Galvanized | 0T2250 | 9,000 |
| 2" | 1/2" | Chisel | 16 | Galvanized | 0T2258 | 7,500 |

APPLICATIONS



Roof sheathing

Plywood sheathing

Vinyl siding (with attachment)

SPECIFICATIONS

Part No. 501230

Weight: 4.9 lbs

Height: 10-3/4"

Length: 12-3/4"

Staple Capacity: 150

Staple Range: 3/4" - 2" 16 gauge,

standard crown (1/2")

Staple Type: 1/2" crown GS16

Galvanized/Brite

Air Reg./100p.s.i. (6.9 bar): .040/cycle

Op. Pres. p.s.i (bar): 80 - 120 (5.5 - 8.3)

Warranty: 1-year limited





S200-W16 Insulation Sheathing Stapler

Staples with ease, comfort and reliability.



INCLUDES

S200-W16 Insulation Sheathing Air Stapler Safety glasses

Owner's manual

TOOL ACCESSORIES







Part No. 219090 Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

S200-W16 Insulation Sheathing Air Stapler—

RELIABLE. DURABLE. VERSATILE.

Paslode staples drive flush into even the hardest woods. And, because Paslode staples are made for Paslode staplers, you'll have fewer jams, fewer misfires and faster loading only a Paslode Stapling System can deliver.

POWERFUL

FAST

LIGHTWEIGHT



ADVANTAGES

- Tool-less quick clear nose removes jams easily
- Soft grip handle, for on the job comfort
- Two finger trigger provides more control
- Extended bumper life, over 600,000 cycles without failure
- Versatile Drives 3/4" 2" wide crown (15/16") for a variety of uses
- Top load magazine Reloads easily and reduces nail waste
- Lightweight and well balanced

SELECTION CHART

16 Gauge Wide Crown Staples

| LENGTH | CROWN SIZE | STAPLE POINT | GAUGE | COATING | PRODUCT NUMBER | STAPLES PER PACK |
|--------|------------|-----------------|-------|------------|-------------------|---------------------|
| 5/8" | 15/16" | Chisel | 16 | Galvanized | 0T2851 | 25,500 |
| 3/4" | 15/16" | Chisel | 16 | Galvanized | 404068 | 9,000 |
| 7/8" | 15/16" | Chisel | 16 | Galvanized | 404069 | 9,000 |
| 1-1/4" | 15/16" | Chisel | 16 | Galvanized | 404071 | 9,000 |
| 1-1/2" | 15/16" | Chisel | 16 | Galvanized | 0T2855 | 10,500 |

APPLICATIONS

Wlire lath Housewrap Insulation Sheathing

SPECIFICATIONS

Part No. 501265

Staple Capacity: 150

Weight: 4.9lbs Staple Range: 3/4"-2" 16 gauge,

wide crown (15/16") Height: 10-3/4"

Air Req./100p.s.i. (6.9 bar): .040/cycle Length: 12-3/4" Op. Pres. p.s.i (bar): 80 - 120 (5.5 - 8.3)

Warranty: 1-year limited Staple Type: Galvanized



IMLi200 18 Gauge Brad Nailer

Lightweight and well balanced



TOOL ACCESSORIES

Part No. 902654C Lithium Ion 7.4v battery

Lithium Ion Battery Charger Part No. 902667C

Part No. 219236 3 Pack of No Mar Tips

Part No. 219086 Degreaser Cleaner

Part No. 401482 Impulse Oil

Part No. 650039 Yellow Fuel Cell (4 pk)

INCLUDES



Safety glasses

Ouick clear

Owner's manual

DESCRIPTION/SUGGESTED SPECIFICATIONS

18 Gauge Brad Nailer—

WE'VE GOT THE FACTS NAILED.

When you need precision in tight spaces, reach for the lightweight Paslode Cordless Finishing Nailing System. It gives great maneuverability to place the nail exactly where you want it wherever you're working: overhead, on ladders or on your knees. Our portable finish nailer, finish nails and fuel cells are designed to work in tandem so you get the job done right, right away

POWERFUL PRECISE











ADVANTAGES

- Li-lon for 50% more shots (12,000) per charge
- Quick charge to 80% in 30 minutes
- New battery standby position conserves charge
- New easier depth of drive thumbwheel
- New reversible belt hook
- 8% lighter 4.5 lbs with battery (compared with Ni-Cad battery)

SELECTION CHART

18 Gauge Fuel and Finish Nail Packs

| LENGTH | SHANK DIAMETER | SHANK TYPE | GAUGE | COATING | PRODUCT NUMBER | NAILS PER PACK |
|--------|-------------------|------------|-------|------------|-------------------|-------------------|
| 1-1/2" | 0.048 | Chisel | 18 | Galvanized | FFP-118112 | 1,000 |
| 2" | 0.048 | Chisel | 18 | Galvanized | FFP-118002 | 1,000 |



See Page F radditional finish nails that work with this tool.

APPLICATIONS





Crown and baseboard mouldings

Panelling

Carpentry

SPECIFICATIONS

Part No. 903700

Weight: 4.5 lbs

Height: 11-1/2" Length: 11"

Nail Capacity: 100

Nail Range: 3/4" - 2"

Nail Type: 18 ga

Warranty ar limited





IMLi250 16 Gauge Finish Nailer

Lightweight and well balanced



TOOL ACCESSORIES

Part No. 902654C Lithium Ion 7.4v battery
Part No. 902667C Lithium Ion Battery Charger
Part No. 219236 3 Pack of No Mar Tips
Part No. 219086 Degreaser Cleaner
Part No. 401482 Impulse Oil
Part No. 650039 Yellow Fuel Cell (4 pk)

INCLUDES



Li ion Battery Charger

No-Mar Tips

Rugged Carrying Case

Owner's Manual & Safety Glasses

DESCRIPTION/SUGGESTED SPECIFICATIONS

16 Gauge Straight Cordless Finish Nailer—

GREAT MANEUVERABILITY.

It gives great maneuverability to place the nail exactly where you want it wherever you're working: overhead, on ladders or on your knees. Our portable finish nailer, finish nails and fuel cells are designed to work in tandem so you get the job done right, right away.

POWERFUL











ADVANTAGES

- Powerful precision Finish right the first time.
- Li-ion Battery Drives up to 12,000 nails per charge
- Lightweight Only 4.6 pounds for added comfort and control
- Use Paslode Universal Trim Fuel Drives approx. 1,000 nails
- Battery Standby Position Conserves battery power
- 1 Hour Rapid Charger 80% charge in 20 min

SELECTION CHART

16 Gauge Fuel and Finish Nail Packs

| LENGTH | SHANK DIAMETER | SHANK TYPE | GAUGE | COATING | PRODUCT NUMBER | NAILS PER PACK |
|--------|-------------------|------------|-------|------------|-------------------|-------------------|
| 1 1/2" | 0.063 | Chisel | 16 | Galvanized | FFP-116112 | 1,000 |
| 2" | 0.063 | Chisel | 16 | Galvanized | FFP-116002 | 1,000 |

See Page for additional finish nails that work with this tool.

APPLICATIONS



Door and window trim

Casing

Crown and baseboard moulding

SPECIFICATIONS

Part No. 903800

Weight: 4.6 lbs

Height: 11-3/4"

Length: 10-1/2"

Nail Capacity: 100

Nail Range 4" 2 1/2"

Nail Type: 16 ga Straight







Positive Placement PF250S

Dependable, Lightweight, Compact and Accurate



DESCRIPTION/SUGGESTED SPECIFICATIONS

Positive Placement Tool—

DESIGNED FOR PROFESSIONAL FRAMERS

Paslode is proud to introduce the latest customer-backed innovation. The Paslode® 21Ž2″ Positive Placement® Metal Connecting System is designed to provide installers the optimal way for fastening structural hardware to wood structures. The pneumatic system significantly reduces installation time, allowing jobs to be completed faster and reducing the need for additional labour.

POWERFUL





ADVANTAGES

- Dependable
- Lightweight and Compact

Accurate

SELECTION CHART

30 Degree Positive Placement Nails

| LENGTH | SHANK DIAMETER | SHANK | DEGREE | COATING | PRODUCT NUMBER | NAILS PER PACK |
|--------|-------------------|--------|--------|------------|-------------------|-------------------|
| 1-1/2" | 0.148 | Smooth | 30 | Galvanized | 650014 | 3,000 |
| 1-1/2" | 0.148 | Smooth | 30 | Brite | 650026 | 3,000 |
| 1-1/2" | 0.148 | Smooth | 30 | Brite | 650646 | 2,500 |
| 2-1/2" | 0.148 | Smooth | 30 | Brite | 650027 | 1,000 |

APPLICATIONS



Joist Hangers

INCLUDES

Positive Placement PF250S

Safety Glasses

Owner's Manual

SPECIFICATIONS

Part No. 511800

Weight: 7.8 lbs

Height: 14"

Length:17.4"

Nail Capacity: 55-60 Nails (2 strips) Nail Range: .131" to .162" (Shank) Magazine Angle: 30 Degrees

Nail Type: 1-1/2" to 2-1/2" Positive Placement

Hanger Nails — Brite and Galvanized

Air reg: 80-120 PSI

Warranty: 90-day limited on wear parts, 1-year limited on magazine parts, 5-year limited on housing and cap parts





T250S F16 16 Gauge Finish Nailer

Precise placement Lightweight Compact



DESCRIPTION/SUGGESTED SPECIFICATIONS

T250S F16 - 16 Gauge Finish Nailer—

PRECISION AND POWER, LIKE OUR FINISHING NAILER AND NAILS, MAKE A GREAT PAIR.

Our Pneumatic Finishing Nailer is designed to deliver consistent power to drive nails flush, while our finishing nails feature a chisel point design to help prevent wood splitting. When a system works together this perfectly, the results are easy to see.

LIGHTWEIGHT



PRECISE



PROFESSIONAL



ADVANTAGES

- Consistent power even in hard to reach spots.
 - Compact, open line of sight drives nails where you want it to even in tight spots
 - Reliable power, delivers consistent drive energy in all types of wood
 - 16 gauge reduces wood splitting and nail visibility
- Tool-free depth of drive nail adjustment

- Powerful performer drives 3/4" 2 -1/2" nails into the hardest woods
- Nail lockout prevents misdrives and surface damage
- Rotating exhaust cap easily moves dust out of the way

APPLICATIONS



Window and door trim/finish applications

Panelling

Cabinetry

INCLUDES

T250S F16 – 16 Gauge Finish Nailer

Safety glasses

Carrying case

Owner's manual

SPECIFICATIONS

Part No. 502140

Weight: 3.9 lbs

Height: 10"

Length: 10-3/4"

Nail Capacity: 100 (2 strips)

Nail Range: 3/4" - 2 1/2"

Magazine Angle: Straight

Nail Type: 16 gauge Straight –

Smooth, Galvanized

Air Req./80 p.s.i: .040/cycle

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts,

1-year limited on housing and cap parts

16 Gauge Straight Finish Nailer

SELECTION CHART

| 16 Gauge Finish Na | iils |
|--------------------|------|
|--------------------|------|

| LENGTH | SHANK DIAMETER | SHANK Type | GAUGE | COATING | PRODUCT NUMBER | NAILS PER PACK |
|--------|-------------------|---------------|-------|------------|-------------------|-------------------|
| 1" | 0.063 | Chisel | 16 | Galvanized | 095203 | 5,000 |
| 1-1/4" | 0.063 | Chisel | 16 | Galvanized | 095205 | 5,000 |
| 1-1/2" | 0.063 | Chisel | 16 | Galvanized | 095257 | 4,000 |
| 1-3/4" | 0.063 | Chisel | 16 | Galvanized | 095435 | 2,500 |
| 2" | 0.063 | Chisel | 16 | Galvanized | 095436 | 2,500 |
| 2-1/2" | 0.063 | Chisel | 16 | Galvanized | 090025 | 2,500 |
| MULTI | 0.063 | Chisel | 16 | Galvanized | 116000 | 2,000 |
| 1" | 0.063 | Chisel | 16 | Galvanized | 116001 | 1,000 |
| 1-1/4" | 0.063 | Chisel | 16 | Galvanized | 116114 | 1,000 |
| 1-1/2" | 0.063 | Chisel | 16 | Galvanized | 116112 | 1,000 |
| 1-3/4" | 0.063 | Chisel | 16 | Galvanized | 116134 | 1,000 |
| 2" | 0.063 | Chisel | 16 | Galvanized | 116002 | 1,000 |
| 2-1/4" | 0.063 | Chisel | 16 | Galvanized | 400601 | 2,500 |
| 2-1/2" | 0.063 | Chisel | 16 | Galvanized | 116025 | 1,000 |



16 GAUGE FINISH NAILS FOR USE WITH







IMLi250 - 16 GAUGE FINISH NAILER

TOOL ACCESSORIES



Part No. 403720 Pneumatic Oil



Part No. 219090 Pneumatic Oil w/ Antifreeze



P18-200 18 Gauge Brad Nailer

Jobsite tough all metal housing and magazine



SEE PAGE P 22 FOR 18 GAUGE NAILS SELECTION CHART

INCLUDES

P18-200 18 Gauge Brad Nailer

3 no mar tips

Air fitting

0il

Safety glasses

Allen wrenches

DESCRIPTION/SUGGESTED SPECIFICATIONS

P18-200 18 Gauge Brad Nailer —

BUILT-IN SIGHT LINE ON HOUSING AND NOSE TO ENSURE ACCURATE NAILING.

Paslode driving power with the features contractors demand: depth of drive guide, dual action trigger, dry fire lockout, magazine gauge, easy jam clearing, no slip rubber handle, extra no mar tips and 360° adjustable exhaust. Actuation tip behind nose piece for clear view of work surface. Built-in sight line on housing and nose to ensure accurate nailing.

LIGHTWEIGHT



PRECISE



EASY ACCESS



ADVANTAGES

- All metal housing & magazine
- Adjustable drive depth
- Bump & sequential fire switch
- Last nail lockout

- Quick-release nose
- 360° adjustabler exhaust
- 5/8" to 2" nails

APPLICATIONS

Windows

Doors

Furniture

Trim applications

SPECIFICATIONS

Part No. P18-200

Weight: 2.9 lbs

Height: 9.5"

Length: 10.25"

Nail Capacity: 100

Nail Range: 5/8" — 2"

Magazine Angle: Straight

Nail Type: 18 Gauge - Smooth, Galvanized

OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts



P18-FS200 18 Gauge Brad Nailer/ Stapler

Paslode driving power with the features contractors demand



PAGE P 22 FOR 22 GAUGE STAPLES
SELECTION CHART

INCLUDES

P18-FS200 18 Gauge Brad Nailer/Stapler

3 no mar tips

Air fitting

0il

Safety glasses

Allen wrenches

DESCRIPTION/SUGGESTED SPECIFICATIONS

P18-FS200 18 Gauge Brad Nailer/Stapler —

BUILT-IN SIGHT LINE ON HOUSING AND NOSE TO ENSURE ACCURATE NAILING.

Paslode driving power with the features contractors demand: depth of drive guide, dual action trigger, dry fire lockout, magazine gauge, easy jam clearing, no slip rubber handle, extra no mar tips and 360° adjustable exhaust. Actuation tip behind nose piece for clear view of work surface. Built-in sight line on housing and nose to ensure accurate nailing.

LIGHTWEIGHT



PRECISE



EASY ACCESS



ADVANTAGES

- All metal housing & magazine
- Adjustable drive depth
- Bump & sequential fire switch
- Last nail lockout

- Quick-release nose
- 360° adjustable exhaust
- 5/8" to 2" Nails, 5/8" to 1-1/2" staples

APPLICATIONS

Windows

Doors

Furniture

Trim applications

SPECIFICATIONS

Part No. P18-FS200

Weight: 2.9 lbs

Height: 9.5"

Length: 10.25"

Nail Capacity: 100

Nail Range: 5/8" - 2" brad nails and 5/8" - 1-1/2" staples (3/16" crown)

Magazine Angle: Straight

Nail Type: 18 Gauge - Smooth,

Galvanized Nails and 1/4" Crown Staples

OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.




18 Gauge Brad Nailers/Stapler

SELECTION CHART

18 Gauae Finish Nails

| IO Gui | age i iiiis | шкепе | | | | |
|--------|-------------------|---------------|-------|------------|-------------------|-------------------|
| LENGTH | SHANK DIAMETER | SHANK TYPE | GAUGE | COATING | PRODUCT NUMBER | NAILS PER PACK |
| MULTI | 0.048 | Chisel | 18 | Galvanized | 118000 | 2,000 |
| 1" | 0.048 | Chisel | 18 | Galvanized | 118001 | 1,000 |
| 2" | 0.048 | Chisel | 18 | Galvanized | 118002 | 1,000 |
| 3/4" | 0.048 | Chisel | 18 | Galvanized | 118034 | 1,000 |
| 5/8" | 0.048 | Chisel | 18 | Galvanized | 118058 | 1,000 |
| 1-1/2" | 0.048 | Chisel | 18 | Galvanized | 118112 | 1,000 |
| 1-1/4" | 0.048 | Chisel | 18 | Galvanized | 118114 | 1,000 |
| 1-3/4" | 0.048 | Chisel | 18 | Galvanized | 118134 | 1,000 |
| 1" | 0.048 | Chisel | 18 | Galvanized | 950001 | 3,000 |
| 2" | 0.048 | Chisel | 18 | Galvanized | 950002 | 3,000 |
| 3/4" | 0.048 | Chisel | 18 | Galvanized | 950034 | 6,000 |
| 5/8" | 0.048 | Chisel | 18 | Galvanized | 950058 | 6,000 |
| 1-1/2" | 0.048 | Chisel | 18 | Galvanized | 950112 | 3,000 |
| 1-1/4" | 0.048 | Chisel | 18 | Galvanized | 950114 | 3,000 |
| 1-3/4" | 0.048 | Chisel | 18 | Galvanized | 950134 | 3,000 |





18 GAUGE FINISH NAILS FOR USE WITH



P18-200 -18 GAUGE BRAD NAILER



P18-FS200 -18 GAUGE BRAD NAILER/STAPLER



IMLI200 - 18 GAUGE FINISH NAILER

TOOL ACCESSORIES



Part No. 403720 Pneumatic Oil



Part No. 219090 Pneumatic Oil w/



N18-125 1-1/4" Narrow Soffit Stapler

Adjustable Exhaust

- Maintains a
Cleaner Working
Environment



INCLUDES

N18-125 - 1-1/4" Narrow Soffit Stapler

Safety glasses

Carrying case

Owner's manual

TOOL ACCESSORIES



Part No. 403720
Pneumatic Oil



Part No. 219090
Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

N18-125 - 1-1/4" Narrow Soffit Stapler—

POWERFUL – MOTOR DRIVES INTO THE HARDEST OF WOODS.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.

POWERFUL



EASY ACCESS



PROFESSIONAL



ADVANTAGES

- Ergonomically Balanced and Lightweight —
 To reduce arm fatigue.
- Quick Clear Nose Piece- to reduce down time on the job if a jam should occur.
- Narrow Nose Piece Allows the tool to fit into tight corners.
- Magnesium Metal Housing Durable and provides longer tool life.

SELECTION CHART

18 Gauge 1/4" Crown Staples

| LENGTH | CROWN SIZE | STAPLE POINT | GAUGE | COATING | PRODUCT NUMBER | STAPLES PER PACK |
|--------|------------|-----------------|-------|------------|-------------------|---------------------|
| 1/2" | 1/4" | Chisel | 18 | Galvanized | 180121 | 1,000 |
| 3/4" | 1/4" | Chisel | 18 | Galvanized | 180341 | 1,000 |
| 1" | 1/4" | Chisel | 18 | Galvanized | 180011 | 1,000 |
| 1" | 1/4" | Chisel | 18 | Galvanized | 140015 | 5,000 |
| 1 1/4" | 1/4" | Chisel | 18 | Galvanized | 181141 | 1,000 |
| 1 1/4" | 1/4" | Chisel | 18 | Galvanized | 141145 | 5,000 |

APPLICATIONS



Trim/Finish

Plywood

Soffits/facias

Underlayment Applications

SPECIFICATIONS

Part No. N18-125

Weight: 2.5 lbs

Height: 9"

Length: 9-1/4"

Nail Capacity: 100

Nail Range: 3/4" - 1-1/4"

Nail Type: GSN 18, 3/16 inch Crown

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts,

1-year limited on housing and cap parts.





1-1/2" Narrow Crown Finish Stapler

Ergonomically
Balanced and
Lightweight –
To Reduce
Arm Fatigue

INCLUDES

N18-150 — 1-1/2" Narrow Crown Finish Stapler

Safety glasses

Carrying case

Owner's manual

TOOL ACCESSORIES







Part No. 219090

Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

N18-150 - 1-1/3" Narrow Crown Finish Stapler—

POWERFUL – MOTOR DRIVES INTO THE HARDEST OF WOODS.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.

POWERFUL



PRECISE



PROFESSIONAL



ADVANTAGES

- Adjustable Exhaust Maintains a cleaner working environment.
- Quick Clear Nose Piece to reduce down time on the job if a jam should occur.
- Narrow Nose Piece Allows the tool to fit into tight corners.
- Magnesium Metal Housing Durable and provides longer tool life.

SELECTION CHART

18 Gauge 1/4" Crown Staples

| LENGTH | CROWN SIZE | STAPLE POINT | GAUGE | COATING | PRODUCT NUMBER | STAPLES PER PACK |
|--------|------------|-----------------|-------|------------|-------------------|---------------------|
| 1/2" | 1/4" | Chisel | 18 | Galvanized | 180121 | 1,000 |
| 3/4" | 1/4" | Chisel | 18 | Galvanized | 180341 | 1,000 |
| 1" | 1/4" | Chisel | 18 | Galvanized | 180011 | 1,000 |
| 1" | 1/4" | Chisel | 18 | Galvanized | 140015 | 5,000 |
| 1 1/4" | 1/4" | Chisel | 18 | Galvanized | 181141 | 1,000 |
| 1 1/4" | 1/4" | Chisel | 18 | Galvanized | 141145 | 5,000 |
| 1 1/2" | 1/4" | Chisel | 18 | Galvanized | 141125 | 5,000 |

APPLICATIONS



Trim/Finish

Plywood

Soffits/facias

Underlayment Applications

SPECIFICATIONS

Part No. N18-150

Weight: 2.8 lbs

Height: 9-3/4"

Length: 11-1/2"

Nail Capacity: 100

Nail Range: 3/4" - 1-1/2"

Nail Type: GSN 18, 3/16 inch Crown

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts, 1-year limited on housing and cap parts.







US-100 Upholstery/ Craft Stapler

Easy-load Magazine





INCLUDES

US100 Upholstery/Craft Stapler

TOOL ACCESSORIES





P 26



Part No. 219090 Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

US-100 Upholstery/Craft Stapler—

LONG NARROW NOSEPIECE FOR TIGHT SPOTS

Lightweight - At only 2 lbs this tool is very easy to handle and decreases operator fatigue. Heavy-duty driver blade.

FAST



PRECISE



QUICK LOAD



ADVANTAGES

Drives 3/8" - 9/16" upholstery staples.

Fast - Shoots 5 staples per second

SELECTION CHART

22 Gauge Upholstery Staples

| LENGTH | CROWN SIZE | STAPLE POINT | GAUGE | COATING | PRODUCT NUMBER | STAPLES PER PACK |
|--------|------------|-----------------|-------|------------|-------------------|------------------|
| 3/8" | 3/8" | Chisel | 22 | Galvanized | 422038 | 4,000 |

APPLICATIONS



Upholstery

Crafts

Light paneling

Home project applications

SPECIFICATIONS

Part No. US-100

Weight: 2.8 lbs

Height: 9-1/2"

Length: 12-1/2"

Nail Capacity: 100

Nail Range: 3/8" - 9/16"

Nail Type: 22 Gauge Upholstery

OP. Pres. p.s.i. (bar): 80-120 (5.5-8.3)

Warranty: 90-day limited on wear parts, 6-month limited on magazine parts,

1-year limited on housing and cap parts.



HP100 Headless Pin Nailer





TOOL ACCESSORIES







Part No. 219090

Pneumatic Oil w/ Antifreeze

DESCRIPTION/SUGGESTED SPECIFICATIONS

HP100 Headless Pin Nailer—

COMPACT – LIGHTWEIGHT.

Multi-directional exhaust port. Pin nails leave a very small hole for easy finishing and painting.



ADVANTAGES

Quick release nose piece

Drives 1/2" to 1-1/2" pin nails

SELECTION CHART

23 Gauge Pin Nails

| LENGTH | SHANK DIAMETER | SHANK TYPE | GAUGE | COATING | PRODUCT NUMBER | NAILS PER PACK |
|--------|-------------------|------------|-------|---------|-------------------|-------------------|
| 1" | 0.025 | Chisel | 23 | Brite | 323001 | 3,000 |
| 3/4" | 0.025 | Chisel | 23 | Brite | 323034 | 3,000 |
| 1-1/2" | 0.025 | Chisel | 23 | Brite | 323112 | 3,000 |
| 1-3/8" | 0.025 | Chisel | 23 | Brite | 323138 | 3,000 |

APPLICATIONS



Fine woodworking and trim work

INCLUDES

HP100 Headless Pin Nailer

Safety glasses

Tool case

Allen wrench and oil

SPECIFICATIONS

Part No. HP100

Weight: 1.2 lbs

Height: 9-1/4"

Length: 7-3/4"

Nail Capacity: 100

Nail Range: 1/2" - 1-1/2"

Magazine Angle: Straight

Nail Type: 23 Gauge - Smooth, Galvanized Pin Nails

OP. Pres. p.s.i. (bar): 80-120

Warranty: 90-day limited on wear parts,

6-month limited on magazine parts,
1-year limited on housing and cap parts.





HT550 20 Gauge Hammer Stapler

Quick Clear Jam Clearing



DESCRIPTION/SUGGESTED SPECIFICATIONS

HT550 – 20 Gauge Hammer Stapler—

HEAVY DUTY, DURABLE CONSTRUCTION.

Precision pneumatic trim tools to do the job right. Whether you're a professional contractor or a "week-end" craftsman, the compact and durable. Lite Line series has the right tool for any trim or hobby application. Featuring the same rugged quality as our other heavy duty professional tools.

FAST



POWERFUL



DEPENDABLE



ADVANTAGES

- Rear Loading Magazine
- Quick Clear Jam Clearing
- Two Strip Capacity

APPLICATIONS



Carpet Padding

Insulation

Roof Paper

House Wrap

INCLUDES

HT550 - 20 Gauge Hammer Stapler

SPECIFICATIONS

Part No. 1013292

Weight: 2.0 lbs

Height: 3-1/4"

Length: 11-3/4"

Staple Capacity: 168

Staple Range: 5/32" - 5/16"

Magazine Angle: Staight

Nail Type: 20Ga, 1/2" Crown

OP. Pres. p.s.i. (bar): N/A (Manual Tool)



FloorMaster Plus[™]

Floormaster Plus™ 2 in 1 Flooring Nailer/Stapler





Compact design gets you closer to walls

INCLUDES

Tool & Mallet

DESCRIPTION/SUGGESTED SPECIFICATIONS

2 in 1 Flooring Nailer/Stapler—

THE PROFESSIONAL GRADE 2 IN 1 FLOORING TOOL.

Optimal performance and solid reliability. Easy maintenance and low cost of ownership. Lightweight – 10.4 lbs

PRECISE FAST POWERFUL

ADVANTAGES

- Easy Actuation
 - Only 4 lbs of pressure anywhere on poppet valve
 - Compact all-around striking surface to avoid marking/damaging walls
- Industry-Best Design & Ergonomics
 - Reverse handle with foam grip for reduced fatique
 - Compact size for nailing boards closer to the end walls

SELECTION CHART

Flooring Staples and Cleats

| LENGTH | SHANK DIAMETER | SHANK TYPE | GAUGE | COATING | PRODUCT NUMBER | NAILS PER PACK |
|--------|-------------------|------------|-------|---------|-------------------|-------------------|
| 13/4" | Staple | Chisel | 15 | Brite | 151134 | 1,000 |
| 13/4" | Staple | Chisel | 15 | Brite | 155134 | 5,000 |
| 2" | Staple | Chisel | 15 | Brite | 151002 | 1,000 |
| 2" | Staple | Chisel | 15 | Brite | 155002 | 5,000 |
| 2" | Cleat | Cleat | 16 | Brite | 100002 | 1,000 |

APPLICATIONS



3/4" Hardwood flooring



SPECIFICATIONS

Part No. F2N1-200

Weight: 10.4 lbs

Height: 18"

Length: 16"

Flooring Fasteners: 15GA staples &

16GA L-cleats

Fastener Lengths: 1-3/4", 2" 15GA staples &

2" 16 GA L-cleats



Miscellaneous Fasteners

SELECTION CHART

MISCELLANEOUS FASTENERS

| 18 Gauge Flo | oring Cleats | | | | | |
|--------------|-------------------|-----------------|--------|------------|-------------------|--------------------|
| LENGTH | ТҮРЕ | STAPLE POINT | GAUGE | COATING | PRODUCT NUMBER | CLEATS PER PACK |
| 2" | Cleat | Chisel | 18 | Brite | 150018 | 1,000 |
| 15 Degree Co | oil Nails | | | | | |
| LENGTH | SHANK DIAMETER | SHANK | DEGREE | COATING | PRODUCT NUMBER | NAILS PER PACK |
| 2" | 0.099 | Spiral | 15 | Brite | 404582 | 4,500 |
| 2-1/4" | 0.099 | Spiral | 15 | Brite | 404583 | 4,500 |
| 2-1/2" | 0.099 | Spiral | 15 | Brite | 404584 | 4,500 |
| 3" | 0.12 | Spiral | 15 | Brite | 404508 | 4,500 |
| 3-1/4" | 0.12 | Spiral | 15 | Brite | 404510 | 4,500 |
| 18 Gauge GE | N-ER-X 7/32" C | rown Staples | | | | |
| LENGTH | ТҮРЕ | STAPLE POINT | GAUGE | COATING | PRODUCT NUMBER | STAPLES PE PACK |
| 5/8" | 7/32" | Chisel | 18 | Galvanized | 732058 | 5,000 |
| 1" | 7/32" | Chisel | 18 | Galvanized | 732001 | 5,000 |
| 1-3/8" | 7/32" | Chisel | 18 | Galvanized | 732138 | 5,000 |

| Notes |
|-----------|
| |
| |
| |
| |
| |
| Paslode P |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

TW Construction Products*

National Headquarters

120 Travail Road Markham, Ontario, L3S 3J1

Tel: 905-471-7403 800-387-9692

Fax: 905-471-7208 800-668-8688

Technical and Customer Service Support

Tel: 800-387-9692

Fax: 800-668-8688

Regional Warehouses

- Markham, Ontario
- Coquitlam, British Columbia
- Calgary, Alberta

Ramset, T3, T3Cup, Trakfast, GypFast, Mastershot, Triggershot, Hammershot, PowerPoint, TE Pin and Climacoat are trademarks of Illinois Tools Works, Inc.

A7, C6+, Dynabolt, G5, Hammer-Set, LDT, Multi-Set II, Poly Set, Red Head, Redi-Drive, S7, Striker, and Trubolt are trademarks of ITW Red Head and Illinois Tool Works, Inc.

Teks, TruGrip GT, Scots, Maxiseal, Dek-Cap, Tapcon,SG, Tapcon, Maxi-Set Tapcon, Condrive, E-Z Ancor, E-Z Toggle, Twist-N-Lock, E-Z Lite, E-Z Mini, Stud Solver, Hi-Lo, S-12, Backer-On, Rock-On, DecKing, Dec-U-Drive, Dek-Cap, Grid-Mate, Grid-Mate, PB, Climaseal, Spex, Climacoat, UltraShield, Climashield and Building Ideas That Work are trademarks of ITW Buildex and Illinois Tool Works. Inc.

Sammy X-Press, Sammy X-Press It, Sammy X-Press Swivel, Sammy X-Press Sidewinder, Tapcon, Sammy Saddle, Speedy Pole Tool, Spot-Rite Level, and Truss-T Hanger are trademarks of ITW Buildex and Illinois Tool Works, Inc.

The term "Paslode" is a trademark and the Paslode logo and all related product and service names, designs and slogans are Paslode trademarks. Paslode, RounDrive, Impulse, Positive Placement are registered trademarks, PowerFramer and quicklode are trademarks of Illinois Tool Works.

R4, RSS, Kameleon, Fin/Trim, RT Composite, Low Profile Cabinet, Pheinox, Top Star, VWS, Caliburn, and The GRK Fasteners Canada Ltd. and all associated designs and logos are trademarks of GRK Fasteners Canada Ltd., used under license.

Hilti is a registered trademark of Hilti, Corp

DensGlass is a registered trademark of Georgia Pacific Building Products.

Dekstrip, Dektite, Retrofit Dektite, and Dektite are registered trademarks of Deks Industries Pty Ltd.

Phillips Square-driv is a registered trademark of the Phillips Screw Company.

© 2018 Illinois Tool Works, Inc. Form. No. 01/18

Take Advantage of these Contractor Services from ITW Construction Products Canada

From job sites to engineering firms, from Safety Seminars to on-site services, we hope you take advantage of our many contractor services—at no charge! After all, it's one thing to offer the quality products you need to do your job. It's another to provide you with superior service, engineering expertise and total product support.

At ITW Construction Products Canada, we are proud of the partnerships we have built through the years with our distributor network and contractors. Thanks to quality products, innovative services and on-time delivery, we will continue to build new relationships and strengthen existing ones today... and into the next century.

- Factory representatives with years of training and service experience will go out to your job site to provide you with product, service and technical assistance.
- We provide architects and engineers with complete submittal packages which gives them the technical data needed to specify ITW Construction Products Canada products. Contact your ITW Construction Products Canada Distributor or your nearest Customer Service location to request submittal packages.

Technical Application Assistance:

Our staff of application specialists are ready to assist you with any type of application or code approval question during any phase of your project. Call 1-800-387-9692 between 8:00 a.m. and 5:00 p.m. EST, Monday through Friday.

Distributed By

The information and recommendations in this document are based on the best information

The information and recommendations in this document are based on the best information available to us at the time of preparation. We make no other warranty, expressed or implied, as to its correctness or completeness, or as to the results or reliance of this document.