POWER EQUIPMENT

POWEREASE 420 ENGINE

MODEL: 85.570.150

FEATURES

- Powerease engines have been used by BE
 Power Equipment for well over ten years and
 have proved themselves to be powerful and
 reliable. Their reputation has earned the trust to
 be used on a wide range of power equipment.
- **Replacement engine** for equipment that accepts a keyed, 1" horizontal shaft.
- Air cooled, 4-stroke, Over Head Valve (OHV)
 design enables higher compression ratio to
 obtain greater power output.
- Uses common SAE 10W30 motor oil to splash lubricate the components in the crankcase.
- Automatic low-oil sensor will shut down the engine if the oil level drops to dangerous levels.
- Fuel recommended to use is regular unleaded that is 86 octane or more. It is best to use fuel with no ethanol, but ethanol blends of up to 10% is acceptable.





Scan the QR code with your mobile device and discover more about this BE Engine.

ENGINE SPECS

MODEL: POWEREASE 420
TYPE: AIR COOLED, 4-STROKE OHV
DISPLACEMENT: 420CC
NET POWER: 15 HP @ 3,600 RPM
NET TORQUE: 17.8 FT/LB @ 2,500 RPM

FUEL TYPE: UNLEADED MIN OCTANE: 86 OR MORE MAX ETHANOL: 10%

FUEL TANK CAPACITY: 6.1 L / 1.6 US GAL
OIL TYPE: SAE 10W30
OIL CAPACITY: 1.1L/1.16 US QTS
LUBRICATION: FORCED SPLASH

COMPRESSION RATIO: **8.2:1**START SYSTEM: **RECOIL**

SHAFT TYPE: KEYED 1" HORIZONTAL
SHAFT ROTATION: COUNTER CLOCKWISE
VALVE CLEARANCES: .06" IN TAKE / .08" OUT TAKE

REPLACEMENT PARTS

AIR FILTER ELEMENT: 85.550.004 AIR FILTER ASSEMBLY: 85.571.029E MUFFLER ASSEMBLY: 85.571.030 85.571.031 FUFI TANK: FUEL TANK CAP: 85.571.013 FUEL TANK CAP STRAINER: 85.571.042 RECOIL ASSEMBLY: 85.571.026 **IGNITION COIL:** 85.571.032 ON/OFF SWITCH: 85.571.008 OIL PLUG & DIPSTICK: 85.571.025 CARBURETOR ASSEMBLY: 85.571.028 THROTTLE CONTROL KIT: 85.571.137 CYCLINDER COVER: 85.571.022 SPARK PLUG: 85.519.001 AUTO LOW OIL SENSOR: 85.571.003

BOXED SIZE

LxWxH: 17" x 18" x 18" WEIGHT: 68 LBS



UNIT WEIGHT: 66 LBS

WARRANTY

ENGINE: 2 YEARS OR 1000 HOURS UPC: 777897146370

06-202