

EZ-8

Fueling people on the go **for over 18 years**
with gas station equivalent flow!



LEGACY OF RETAIL
FUEL TRANSFER SOLUTIONS

8
GPM | **30**
L/min

12V DC
Voltage (Power Source)



Item# 137100-01 shown

The GPI 12V DC EZ-8 Fuel Transfer Pump is

THE PUMP OF CHOICE

for refueling recreational vehicles, featuring a rotary gear design made from durable, lightweight, corrosion-resistant diecast aluminum.

The 12V DC motor delivers gas station equivalent flow rates of up to **8 GPM for gasoline, diesel fuel, ethanol blends, and kerosene**. It is the perfect pump for on-the-go fueling for agriculture and automotive applications. Mount this dependable pump to fuel drums or tanks up to 100 gallons, and you are ready to go off-roading, cruise the lake, or achieve "yard of the week" mowing status.

EASY MAINTENANCE

Self-priming, low maintenance design

SMART DESIGN

Extremely lightweight design, less stress on small tanks and barrels

EASY INSTALLATION

Easy installation and direct tank mounting

LONG LIFE

Thermal overload protection extends pump life

Gas Station Equivalent FLOW RATE



Suitable for gasoline up to E15, diesel fuel up to B20, and kerosene

Lightweight, RUGGED



EZ-8 pump weighs only 8.5 lbs. Powder-coated motor can and aluminum body provides corrosion resistance.

Special Models AVAILABLE

- Spin Collar Mount
Item# 137100-05



GREAT PLAINS INDUSTRIES



EZ-8

Fueling people on the go for over 18 years
with gas station equivalent flow!



LEGACY OF RETAIL
FUEL TRANSFER SOLUTIONS

LIGHT & DEPENDABLE FUEL PUMP

that delivers gas station equivalent flow rate (up to 8 GPM)

Extremely Compact Design allowing easy installation and versatile pump mounting

Direct Mount fits all standard 2 in. NPT tank fittings

3/4 in. Manual Shut-off Nozzle

Factory-Installed Power Cord reduced installation time

SPECS (ALL MODELS)

Max. Flow Rate:		8 GPM 30 L/min
Voltage, Input:		12V (DC)
Pump Technology:		Rotary Gear
Motor HP:		0.10
Duty Cycle:		15 min. on / 30 min. off
Max. Discharge Pressure:		Up to 15 PSI (1.03 bar)
Suction Pipe:		Polypropylene, Telescoping 15 to 40 in. x 1 in. MNPT
At Sea Level 70° F (21.1° C)	Suction Lift:	Up to 5 ft. (1.5 m)
	Discharge Lift:	Up to 10 ft. (3 m)
Pump Housing:		Powder-Coated Motor Can, Corrosion-Resistant Diecast Aluminum Body
Warranty:		Two-Year Pump Warranty

Refer to manual for wiring instructions

The preferred pump for fueling on the go in agriculture, recreational, landscaping, and more!



FLUIDS+

Gasoline up to E15 | Diesel Fuel up to B20 | Kerosene



See Available Models

