



On when
it counts.



Application

- Pedestrian Crossing with Countdown

Features & Benefits

- 16 x 18 Pedestrian Signal Module
- Incandescent appearance
- Countdown of Walk Option Capable by Switching Dip SW3 ON*
- Maintenance saving

Environmental

Operating Temperature -40°C to +74°C

Construction

Lens Material Polycarbonate

Housing Material Polycarbonate

Gasket Material Neoprene

Connector* Fast-on connector with spade terminal insert

* Consult Dialight for alternate connector options

- Vibration resistant to Mil-STD-883 Test method 2007
- Moisture resistant per MiL-STD-810F, Method 506.4 for rain and blowing rain
- Meets ITE PTCSI Part 2 LED Pedestrian Traffic Signal Module Specification dated 8/04/2010
- All products traceable by serial number

Part Number	Housing Size	Symbol Color			Nominal Wattage (W)			Minimum Luminance (cd/m2)		
		Countdown	Hand	Person	Countdown	Hand	Person	Countdown	Hand	Person
430-6479-001XW*	16 x 16	Portland Orange	Portland Orange	Lunar White	8	11	10	1,400	1,400	2,200

*Product not shipped with walk option enabled, must be enabled by the end user. Countdown during the walk cycle is not MUTCD compliant

Dialight reserves the right to make changes at any time in order to supply the best product possible. The most current version of this document will always be available at: www.dialight.com. Warranty Statement: EXCEPT FOR THE WARRANTY EXPRESSLY PROVIDED [HEREIN / ABOVE / BELOW], DIALIGHT DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING, WITHOUT LIMITATION, ANY WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, TITLE, AND NON-INFRINGEMENT