

LOW-PRO FLATDECK WITH SINGLES (LS)

Length: 20-40' | Deck Width: 102"

Deck Height: 33.5"

Couplers: Bumper Pull, **Gooseneck** & Pintle

GVWR: 15,680 lbs (20' GN w/2x7k axles)

Load Capacity: 11,120 lbs (20' GN)

Weight: 4,560 lbs (20' GN)



Ultra Low 33.5" Deck Height

The ultra low 33.5" deck height makes loading equipment easier. It also drops the center of gravity for better towing.



Pierced Beam Cross-Members

We plasma cut our I-beam frame allowing the 3" channel cross-members to be lowered.



68" Ultra Wide Main Frame

The wider 68" I-beam frame makes for improved stability and cornering under load.

33.5"
DECK HEIGHT

15.6k
BASE GVWR

25k
GOOSENECK COUPLER

12"
14" X 22 LB. I-BEAM FRAME

3"
CHANNEL CROSSMEMBERS

DIAMOND
LOW-PRO DIAMOND PLATE FENDERS

10 Ply
235/80R16 RADIAL TIRES

DDEXTER
DEXTER EZ LUBE AXLES

TORSION
TORSION SUSPENSION

102"
WIDE DECK

16"
CROSSMEMBER CENTERS

MONSTER
MONSTER STEPS

I
PIERCED I-BEAM MAIN FRAME

TREATED
TREATED PINE DECK

7-WAY
7-WAY RV PLUG

LED
LIFETIME LED LIGHTS

SHERWIN
SHERWIN WILLIAMS POWDER COAT