




# TJ HD EQUIPMENT TILT 6" CHANNEL

## STANDARD CONFIGURATION SPECS

THESE ARE THE DEFAULT SPECS THAT ARE INCLUDED IN THE BASE CONFIGURATION OF THIS MODEL.

 Deck Width: <b>82" (81.5" Between Fenders)</b>	 Deck Height: <b>23"</b>	 Axles: <b>Tandem Torsion (2 x 8,000 lb.)</b>	 Choose the optional Blackwood Pro decking for added durability and grip when wet.
 Length: <b>20' - 24'</b>	 Couplers: <b>Bumper Pull, Gooseneck, &amp; Pintle</b>	 Load Capacity: <b>12,750 - 11,520 lbs.</b>	
 GVWR: <b>16,000 lbs.</b>	 Weight: <b>3,520 - 4,480 lbs.</b>	 Tilt Angle: <b>12°</b>	



Our Gravity Tilt uses a hydraulic cylinder and proportioning valve to control the rate of tilt bed movement for additional safety when loading and unloading.

### HYDRAULIC CUSHIONED GRAVITY TILT



Simplify brake maintenance with our Forward Self-Adjusting Brakes, engineered to self-adjust for optimal braking performance. This innovative system reduces downtime and ensures consistent stopping power.

### FORWARD SELF-ADJUSTING BRAKES



Benefit from enhanced cargo securement with our standard Rubrail, stake pockets and pipe spools. In addition to the built-in stake pockets, the Rubrail provides extra attachment points for securing your load. Customize your trailer further by adding optional D-rings.

### CARGO CONTROL STANDARD



Our 30" Diamond plate knife edge tail makes it super-easy to load low clearance equipment like scissor lifts and fork lifts.

### KNIFE EDGE TAIL

**PJ TRAILERS**

Visit [pjtrailers.com](http://pjtrailers.com) for a complete list of trailer options.