

6" CHANNEL SUPER-WIDE TILT (TS)



Length: 18-24' Load Angle: 11°
 Deck Height: 21" Deck Width: 102"
 Couplers: Bumper Pull, Gooseneck & Pintle

GVWR: 14,000 (BP) / 15,680 lbs (GN)
 Load Capacity: 9,920 lbs (20' Bumper Pull)
 Weight: 4,080 lbs (20' Bumper Pull)



HYDRAULIC CUSHIONED GRAVITY TILT

With no battery or hydraulic pump to worry about, you can simply tilt the bed with a turn of the valve. The 3"x16" cylinder, reservoir and proportioning valve allows you to control the tilt rate.



DRIVE-OVER FENDERS

The TS features 1/4" diamond plate steel fenders, allowing you to use the full 102" width of the deck and drive your equipment or oversized vehicles right over them!



SUPER-WIDE DECK

The 102" rail to rail deck width of the TS makes it an excellent choice for hauling 4x4s, rock crawlers, trucks, and other vehicles that exceed the typical 83" deck width.

21"

DECK HEIGHT

14k

BASE GVWR

2 5/16"

ADJUSTABLE COUPLER

6"

CHANNEL FRAME & TONGUE

3"

CHANNEL CROSSMEMBERS



DRIVE-OVER FENDERS

16"

235/80R16 10 PLY RADIAL TIRES



DEXTER DEXTER TORSION AXLES



TORSION SUSPENSION

102"

SUPER-WIDE DECK

16"

CROSSMEMBER CENTERS

11°

LOAD ANGLE

10k

SPRING LOADED DROP-LEG JACK



TREATED PINE DECK



7-WAY RV PLUG



LIFETIME LED LIGHTS



POWDER COAT