

HORIZONTAL, 4U, 84HP

- Advanced EMC shielded 19" chassis, powder coated black (RAL 9005)
- Chassis applicable for CompactPCI, CompactPCI Packet Switching (cPSB) PICMG 2.16, VMEbus and VME64x backplanes
- VITA 31.1 and VITA 41 backplanes
- Noise reduction thanks to Elma's FanController
- System platform for horizontal boards (6 U)
- ON/OFF Switch: rear



Image similar

SPECIFICATIONS

Backplane

Type	CPSB
Slots	8
System slot	System slot right
Orientation	Horizontal

Dimensions

Height	4U
Width	84HP
Depth	298 mm
Weight	Approx. 11 kg

Cooling

Air flow front, free blow	360 m³/h
Air flow rear, free blow	48,6 m³/h

Power supply

Output (max.)	750 W (pluggable)
Output voltages per unit (max.)	+3.3 V: 36 A, +5 V: 25 A, +12 V: 3 A, -12 V: 0,5 A
Input voltage	100 – 240 VAC
Frequency	47 - 63 Hz

Environmental Data

Operating temperature range:	0 °C to +50 °C
Storage temperature range:	-40 °C to +80 °C
Humidity	30 % - 80 %, non-condensing

Card cage

Front	160 mm
Rear I/O	80 mm

Part number

484H2-P08R-75PA1-100