

GUARDIAN® ANSI/ASSE Z359.18-2017

607 East Sam Houston Pkwy S
Suite 800, Pasadena, TX 77503
800-466-6385

Test Report Number: 202301161400052
Job Number: Test 660, 202212061400052
Product SKU#: 1400052
Product Type: Type A Anchor
Product Description: Removable 5000 lb Concrete Anchor
Testing Standard: ANSI/ASSE Z359.18-17 Safety Requirements for Anchorage Connectors for Active Fall Protection Systems
Dates of Manufacture: 12/01/2022
Date(s) of Testing: 12/06/2022, 12/07/2022, 12/22/2022

REQUIREMENT VERIFICATION

<u>Requirement Description</u>	<u>Clause/Section</u>	<u>Result</u>
Design Requirements	3.1 Design Requirements	Meets or Exceeds
Low-Temperature Performance	3.1.3.2.1 Low-Temperature Performance	Meets or Exceeds
Performance Requirements	3.2 Performance Requirements	Meets or Exceeds
Markings and Instructions	5. Markings and Instructions	Meets or Exceeds

QUALIFICATION TESTING

<u>Test Description</u>	<u>Test Date</u>	<u>Clause/Section</u>	<u>Result</u>
Static Strength (A), Inline	12/06/2022	4.2.1.1 Static Strength Testing of Type A Anchorage Connectors	Pass
Dynamic Strength (A), Inline	12/07/2022	4.2.2.1 Dynamic Strength Testing of Type A Anchorage Connectors	Pass
Residual Strength (A), Inline	12/07/2022	4.2.3.1 Residual Strength Testing of Type A, T, & D Anchorage Connectors	Pass
Static Strength (A), Sheer	12/06/2022	4.2.1.1 Static Strength Testing of Type A Anchorage Connectors	Pass
Dynamic Strength (A), Sheer	12/07/2022	4.2.2.1 Dynamic Strength Testing of Type A Anchorage Connectors	Pass
Residual Strength (A), Sheer	12/07/2022	4.2.3.1 Residual Strength Testing of Type A, T, & D Anchorage Connectors	Pass
Corrosion Resistance	12/22/2022	4.2.5.1 Type A and Type D Anchorage Connectors	*See attached Corrosion Test Report

This test report covers these additional products:

Please contact quality@guardianfall.com for signed report.

Test Equipment		
Equipment	Model	Serial
Load Cell	1220ACK-25K-B	367976A
Test Weight	282 lb	GFP001
Tape Measure	TX1-25	20243698
Environmental Chamber	S-8-8200	46336
Environmental Chamber	SM-16-8200	49357
Scale	Totalcomp	02314063019

Notes

3.1	Design Requirements	
3.1.1	a) Connection points shall support only one user or system at a time	Meets or exceeds
	b) A connection point eye on a type T anchorage connector shall be a closed eye with a minimum 1 inch inside radius	NA
	c) Anchorage connectors shall not have closed loops that could be mistaken for a connection point	NA
	d) Any operable gates, rings, buckles, or other hardware covered by ANSI Z359.12-2012 shall comply with ANSI Z359-12-2012	NA
	e) Multiple connections shall only be permitted on tripod or davit style anchorages	Meets or exceeds
3.1.2	Surfaces shall be free from burrs, pits, sharp corners and roughness	Meets or exceeds
3.1.3.1	Hot-dipped galvanized steel shall conform with ASTM A123/123M	Meets or exceeds
3.1.3.2.1	Type A and Type T anchorage connectors shall maintain toughness at temps between -30 degrees F and +130 degrees F. Each dynamic strength test sample shall be conditioned at -35 +/-2 C for a minimum of 8 hours and removed no more than five minutes before testing.	Meets or exceeds
3.1.4.1	Textiles shall not contain natural fibers	NA
3.1.4.2	If a subsystem uses stitching for connection of load-bearing components, the equipment manufacturer shall produce the stitching and cutting and meet the following requirements:	
	a) Use lock stitching	NA
	b) Secure the ends of threads by backstitching, overlapping stitching, or other methods	NA
	c) Threads used for sewing shall be physically compatible with the webbing and of a quality comparable to that of the webbing	NA
	d) Hot-cut or fuse thermoplastic materials, cord, tape, and webbing to prevent fraying	NA
	e) The thread color or shade shall contrast with that of the webbing to facilitate visual inspection	NA

Notes

5	Markings and Instructions	
5.1	Marking Requirements	
5.1.1	General: The following markings shall appear in English on a label, marking or tag that is designed to last for the lifetime of the anchorage connector and is permanently affixed to the anchorage connector	
	a) The manufacturer's name and mark	Meets or exceeds
	b) The year of manufacture	Meets or exceeds
	c) Model number	Meets or exceeds
	d) "ANSI Z359.18" and the type	Meets or exceeds
	e) Markings to indicate restrictions on directions of loading, if applicable	Meets or exceeds
	f) Where specified by the manufacturer, the working load	Meets or exceeds
	g) An individual serial number or a lot or batch number that provides traceability	Meets or exceeds
	h) Minimum Breaking Strength, followed by "MBS."	Meets or exceeds
5.1.2	Specific: As required for the specific anchorage connector, the following markings shall appear in English on a label, marking or tag that is designed to last for the lifetime of the anchorage connector and is permanently affixed to the anchorage connector	Meets or exceeds
5.1.2.1	An anchorage connector that incorporates a closed loop not intended for connection, but may be mistaken for a connection point shall be permanently labeled with a warning not to connect a fall protection system or suspended component to the closed loop when used in a cinching operation	Meets or exceeds
5.1.2.3	The minimum service temperature for the anchorage connector according to 3.1.3.2	Meets or exceeds
5.1.2.4	For tripods and davit systems, the maximum number of users permitted on the system	Meets or exceeds

Notes

3.1.3.2.1 Low-Temperature Performance Type A & Type T Anchorage Connectors requirements per 3.2.2.1

- Condition sample at -40°C for 3 hours
- Install the anchorage connector, conditioned according to the applicable requirements of this section, on the test anchorage in accordance with the requirements of 4.1.2.
- Connect one end of the test lanyard to the connection point of the anchorage connector to be loaded or to the arrest force measuring instrumentation, as applicable
- Connect the other end of the test lanyard to the test weight specified in 4.1.3
- Raise the test weight to achieve a free-fall distance of 3, +0.1/-0, ft (0.9, +0.03/-0m)
- Release the test weight by means of the quick-release mechanism
- Evaluate the test results per 3.2.2.1

3.1.3.2.1 Low-Temperature Performance Type A & Type T Anchorage Connectors requirements per 3.2.2.1

Samples	Sample # 01
Anchorage Connector arrests test weight	Yes
If gates are present, no separation more than 1/8"	NA
Result/Assessment	Pass

3.1.3.2.1 Low-Temperature Residual Performance Type A & Type T Anchorage Connector requirements per 3.2.2.1

- Condition sample at -40°C for 3 hours
- Install the anchorage connector, conditioned according to the applicable requirements of this section, on the test anchorage in accordance with the requirements of 4.1.2.
- Connect one end of the test lanyard to the connection point of the anchorage connector to be loaded or to the arrest force measuring instrumentation, as applicable
- Connect the other end of the test lanyard to the test weight specified in 4.1.3
- Raise the test weight to achieve a free-fall distance of 3, +0.1/-0, ft (0.9, +0.03/-0m)
- Release the test weight by means of the quick-release mechanism
- Evaluate the test results per 3.2.2.1

3.1.3.2.1 Low-Temperature Residual Performance Type A & Type T Anchorage Connector requirements per 3.2.2.1

Samples	Sample # 01
Anchorage connector arrests test weight	Yes
Anchorage connector supports test weight for minimum one minute	Yes
If gates are present, no separation more than 1/8"	NA
Result/Assessment	Pass

Notes

The above tests were performed with a 24 x 26 x 6 in. concrete block substrate with an average PSI of <4,000 lb. The anchor was inserted in a 0.75 in. diameter hole with an orientation allowing for inline forces.

5.2	Instruction Requirements	
5.2.1	General: Provide the following instructions and information in English with each anchorage connector	
5.2.1.1	Overall:	
	a) A statement that the anchorage connector has been tested in compliance with the requirements of ANSI/ASSE Z359.7, and caution that the ANSI compliance testing covers only the hardware and does not extend to the anchorage and substrate to which the anchorage connector is attached	Meets or exceeds
	b) Specifications for appropriate anchorages(s) to which the anchorage connector can be attached, including instructions on how to proceed when the user is unable to determine whether the anchorage meets the manufacturer's specification and instructions that the anchorage connector shall only be connected to anchorages that:	Meets or exceeds
	i) Can withstand 5,000 lb (22.2kN) without failure, except that lower strengths are acceptable when permitted by applicable legislation; or	Meets or exceeds
	ii) Are certified by a professional engineer as having the required strength for fall arrest or travel restraint, as applicable, or;	Meets or exceeds
	iii) The manufacturer may provide specifications of allowable materials including the minimum shapes, sizes and geometry of structural elements to which the anchorage connector may be fastened. A qualified person shall approve these specifications.	Meets or exceeds
	c) The manufacturer shall clearly label the minimum service temperature for the anchorage connector according to 3.1.3.2	Meets or exceeds
	d) The manufacturer shall supply complete specifications for fasteners	Meets or exceeds
	e) The anchorage type	Meets or exceeds
	f) The permitted uses of the anchorage connector	Meets or exceeds
	g) The connection point(s), working load limit	Meets or exceeds
	h) The material used in the anchorage connector's construction	Meets or exceeds
	i) The length of the anchorage connector and any other dimensions that may affect its compatibility with anchorage to which it may be connected	Meets or exceeds
	j) The manufacturer shall make available upon request information for the design of systems, such as AAF and/or force vs. displacement curve(s) for the device	Meets or exceeds
	k) A statement that only one fall protection system or positioning system may be attached to an individual connection point	Meets or exceeds
	l) Specification providing the intended directions(s) of loading of the anchorage connector	Meets or exceeds
	m) A complete list of the anchorage connector components provided by the manufacturer at the time of sale	Meets or exceeds
	n) A warning against unauthorized alterations, relocations or additions to the anchorage connector	Meets or exceeds

5.2.1.2	Use:	
	a) Instructions on proper installaion and use, including, but not limits to, compatibility with other fall protection components	Meets or exceeds
	b) The length of the anchorage connector and any other dimensions that may affect its compatability with anchorages to which it may be connected	Meets or exceeds
	c) Where applicable, directions regarding the appropriate length of lanyard to use with the anchorage connector to compensate for the additional length that it may add to the lanyard	Meets or exceeds
	d) Permitted and forbidden uses, including clear description of and the recommended ways of dealing with applicable compatibility concerns	Meets or exceeds
	e) A warning to remove any surface contamination such as concrete, stucco, roofing material, etc., that could accelerate cutting or abrading of attached components	Meets or exceeds
	f) Warnings concerning environments and conditions that may degrade the anchorage connector	Meets or exceeds
	g) Training requirements	Meets or exceeds
5.2.1.3	Inspection and Field Testing:	
	a) Instructions on testing, if needed	Meets or exceeds
	b) Where applicable, directions for the installer to performs and document proof testing upon installation. Directions shall include proof load forces and acceptable methods	Meets or exceeds
	c) Field serviceability testing: The manufacturer shall provide guidelines for how often field load testing must be undertaken to prove that the anchorage connector continues to be adequately secured to the structure. These guidelines shall include recommended methods for testing, including the direction and point of application of test loads	Meets or exceeds
	d) The recommended frequencies and procedures for inspection, maintenance, and when applicable, testing	Meets or exceeds
	e) Instructions for inspecting and servicing an anchorage connector after it is subjected to a fall or an inspection reveals an unsafe condition	Meets or exceeds
	f) If applicable, guidelines for retirement of the anchorage connector	Meets or exceeds
	g) The action to be taken if an inspection of an anchorage connector reveals an unsafe condition	Meets or exceeds
	h) The action to be taken after the anchorage connector is subjected to a fall	Meets or exceeds
	i) Criteria for removal of an anchorage connector from service if deformed from its original installed configuration	Meets or exceeds
5.2.1.4	Cinching and Non-Cinching Style Anchorage Connectors	
	a) Where the anchorage connector includes an abrasion pad, provide directions that the abrasion pad shall be installed between the anchorage and the load bearing strap	Meets or exceeds
	b) The proper method of installing the anchorage connector including, as applicable for non-cinching anchorage connectors, the maximum angle permitted between connection legs	Meets or exceeds

4.2.1.1 Static Strength Testing of Type A Anchorage Connectors requirements per 3.2.1.1

- A new anchorage connector may be used for each test
- The test force shall be 5,000 pounds (22.2kN) +50/-0 pounds (+0.22/-0kN). Apply these forces in accordance with the requirements of 4.1.2.
- Install the anchorage connector on the test anchorage in accordance with the requirements of 4.1.2
- Apply the load to the anchorage connector in the direction(s) of loading specified in 4.1.2.5
- Apply the load at a rate not greater than 2 inches (51mm) per minute. Maintain the load above 5,000 pounds (22.2kN) for at least 3 minutes
- Release the load
- Evaluate the test results per 3.2.1.1

4.2.1.1 Static Strength Testing of Type A Anchorage Connectors requirements per 3.2.1.1

Samples	Sample # 02	Sample # 03	Sample # 04
Anchorage Connector Withstands Applied Load for >3 mins	Yes	Yes	Yes
Actual load applied (lb)	5081.73	5042.39	5033.56
If gates are present, no separation more than 1/8"	NA	NA	NA
Result/Assessment	Pass	Pass	Pass

4.2.2.1 Dynamic Strength Testing of Type A Anchorage Connectors requirements per 3.2.2.1

- Install the anchorage connector, conditioned according to the applicable requirements of this section, on the test anchorage in accordance with the requirements of 4.1.2.
- Connect one end of the test lanyard to the connection point of the anchorage connector to be loaded or to the arrest force measuring instrumentation, as applicable
- Connect the other end of the test lanyard to the test weight specified in 4.1.3
- Raise the test weight to achieve a free-fall distance of 3, +0.1/-0, ft (0.9, +0.03/-0m)
- Release the test weight by means of the quick-release mechanism
- Evaluate the test results per 3.2.2.1

4.2.2.1 Dynamic Strength Testing of Type A Anchorage Connectors requirements per 3.2.2.1

Samples	Sample # 05	Sample # 06	Sample # 07
Anchorage Connector arrests test weight	Yes	Yes	Yes
If gates are present, no separation more than 1/8"	NA	NA	NA
Result/Assessment	Pass	Pass	Pass

Notes

The above tests were performed with a 24 x 26 x 6 in. concrete block substrate with an average PSI of <4,000 lb. The anchor was inserted in a 0.75 in. diameter hole with an orientation allowing for inline forces.

4.2.3.1 Residual Strength Testing for Type A Anchorage Connectors requirements per 3.2.2.1

- a) Install the anchorage connector, conditioned according to the applicable requirements of this section, on the test anchorage in accordance with the requirements of 4.1.2.
- b) Connect one end of the test lanyard to the connection point of the anchorage connector to be loaded or to the arrest force measuring instrumentation, as applicable
- c) Connect the other end of the test lanyard to the test weight specified in 4.1.3
- d) Raise the test weight to achieve a free-fall distance of 3, +0.1/-0, ft (0.9, +0.03/-0m)
- e) Release the test weight by means of the quick-release mechanism
- f) Evaluate the test results per 3.2.2.1

4.2.3.1 Residual Strength Testing for Type A Anchorage Connectors requirements per 3.2.2.1

Samples	Sample # 05	Sample # 06	Sample # 07
Anchorage connector arrests test weight	Yes	Yes	Yes
Anchorage connector supports test weight for minimum one minute	Pass	Pass	Pass
If gates are present, no separation more than 1/8"	NA	NA	NA
Result/Assessment	Pass	Pass	Pass

Notes

The above tests were performed with a 24 x 26 x 6 in. concrete block substrate with an average PSI of <4,000 lb. The anchor was inserted in a 0.75 in. diameter hole with an orientation allowing for inline forces.

4.2.1.1 Static Strength Testing of Type A Anchorage Connectors requirements per 3.2.1.1

- A new anchorage connector may be used for each test
- The test force shall be 5,000 pounds (22.2kN) +50/-0 pounds (+0.22/-0kN). Apply these forces in accordance with the requirements of 4.1.2.
- Install the anchorage connector on the test anchorage in accordance with the requirements of 4.1.2
- Apply the load to the anchorage connector in the direction(s) of loading specified in 4.1.2.5
- Apply the load at a rate not greater than 2 inches (51mm) per minute. Maintain the load above 5,000 pounds (22.2kN) for at least 3 minutes
- Release the load
- Evaluate the test results per 3.2.1.1

4.2.1.1 Static Strength Testing of Type A Anchorage Connectors requirements per 3.2.1.1

Samples	Sample # 09	Sample # 10	Sample # 11
Anchorage Connector Withstands Applied Load for >3 mins	Yes	Yes	Yes
Actual load applied (lb)	5040.11	5025.98	5028.97
If gates are present, no separation more than 1/8"	NA	NA	NA
Result/Assessment	Pass	Pass	Pass

4.2.2.1 Dynamic Strength Testing of Type A Anchorage Connectors requirements per 3.2.2.1

- Install the anchorage connector, conditioned according to the applicable requirements of this section, on the test anchorage in accordance with the requirements of 4.1.2.
- Connect one end of the test lanyard to the connection point of the anchorage connector to be loaded or to the arrest force measuring instrumentation, as applicable
- Connect the other end of the test lanyard to the test weight specified in 4.1.3
- Raise the test weight to achieve a free-fall distance of 3, +0.1/-0, ft (0.9, +0.03/-0m)
- Release the test weight by means of the quick-release mechanism
- Evaluate the test results per 3.2.2.1

4.2.2.1 Dynamic Strength Testing of Type A Anchorage Connectors requirements per 3.2.2.1

Samples	Sample # 12	Sample # 13	Sample # 14
Anchorage Connector arrests test weight	Yes	Yes	Yes
If gates are present, no separation more than 1/8"	NA	NA	NA
Result/Assessment	Pass	Pass	Pass

Notes

The above tests were performed with a 24 x 26 x 6 in. concrete block substrate with an average PSI of <4,000 lb. The anchor was inserted in a 0.75 in. diameter hole with an orientation allowing for shear forces.

4.2.3.1 Residual Strength Testing for Type A Anchorage Connectors requirements per 3.2.2.1

- a) Install the anchorage connector, conditioned according to the applicable requirements of this section, on the test anchorage in accordance with the requirements of 4.1.2.
- b) Connect one end of the test lanyard to the connection point of the anchorage connector to be loaded or to the arrest force measuring instrumentation, as applicable
- c) Connect the other end of the test lanyard to the test weight specified in 4.1.3
- d) Raise the test weight to achieve a free-fall distance of 3, +0.1/-0, ft (0.9, +0.03/-0m)
- e) Release the test weight by means of the quick-release mechanism
- f) Evaluate the test results per 3.2.2.1

4.2.3.1 Residual Strength Testing for Type A Anchorage Connectors requirements per 3.2.2.1

Samples	Sample # 12	Sample # 13	Sample # 14
Anchorage connector arrests test weight	Yes	Yes	Yes
Anchorage connector supports test weight for minimum one minute	Pass	Pass	Pass
If gates are present, no separation more than 1/8"	NA	NA	NA
Result/Assessment	Pass	Pass	Pass

Notes

The above tests were performed with a 24 x 26 x 6 in. concrete block substrate with an average PSI of <4,000 lb. The anchor was inserted in a 0.75 in. diameter hole with an orientation allowing for sheer forces.

Pictured: 1400052
Represents all part #s



Labels
Applicable to all Part #s

GUARDIAN
guardianfall.com

A5
Concrete
Expansion Anchor

ANSI Z359.18-17
OSHA 1926.502 & 1910.140



91723-A-1

Part #

1400052

Date of Manufacture

MM | YY

Lot #

Serial #

91723-A-2

WARNING

Read instructions before using. Failure to follow instructions may result in serious injury or death. Avoid contact with sharp and abrasive edges and surfaces. NEVER make incompatible connections.

Type A anchorage connector

User Weight Range (including tools and equipment): 100 - 420 lb (45 - 191 kg)

Minimum Breaking Strength (MBS): 5,000 lb (22,2 kN)

Minimum Service Temperature: -30F

Maximum 1 connection per anchor.

91723-A-3

Date of First Use

Inspection Date

Initials

DO NOT REMOVE LABELS

Designed and Tested in USA
Made in China

91723-A-4

Test Type:	48 Hour Neutral Salt Spray Test (NSS)	Test Description:	48 Hour Neutral Salt spray Test
Lab Technician:	Sutton Cameron	ISO 9227:2022:	5.2.2 Neutral Salt Spray (NSS) Test
Start of Test:	12/20/2022	End of Test:	12/22/2022
Part Number:	1400052	Number of Samples:	3
Description:	Removable 5000 lb. Concrete Anchor	Water Type:	Type IV Deionized Water
Salt Purity (Percent):	>97.7%	Testing on Behalf of:	Guardian

Solution


per 5.2.2 Neutral Salt Spray (NSS) Test

Adjust the pH of the salt solution so that the pH of the sprayed solution collected within the test cabinet is 6.5 to 7.2 at 25°C ± 2°C. Check the pH using electrometric measurement. Measurements of pH shall be done using electrodes suitable for measuring in weakly buffered sodium chloride solutions in deionized water. Make any necessary corrections by adding hydrochloric acid, sodium hydroxide or sodium bicarbonate solution of analytical grade.


Density		PH
Temp. 25°C ± 2°C	Measurement 1.029 - 1.036 g/cm³	Measurement 6.5 - 7.2
Within Tolerance	Within Tolerance	Within Tolerance

Interval				Quantity	Specific Gravity		PH
Exposure Time	Actual Time Log	Water Jacket Temperature	Bubble Tower Temperature	Measurement mL/h/80cm²	Collection Temperature	Density g/cm³	Measurement 6.5-7.2
Start	1409	95°F	116.5°F	1.27cm²	82.6°F	1.035 g/cm³	6.74
24 Hours	1433	95°F	116.5°F	1.34cm²	74.4°F	1.035 g/cm³	7.18
48 Hours	1457	95°F	116.5°F	1.27cm²	85.1°F	1.035 g/cm³	6.62


Before Test



During Test



Post Test



Please contact quality@guardianfall.com for signed report.