

WEB HLL

HORIZONTAL LIFELINE

TECHNICAL DATA SHEET

CARABINERS INCLUDED

Double-locking with 3,600 lbs. strength gate

NYLON STORAGE BAG

Allows for easy transportation & storage.

TWO 6' CROSS ARM STRAPS

Serve as anchorage for both ends of HLL. Also compatible with variety of other anchorage connectors.

REMOVABLE HANDLE

Ergonomic ratchet handle is removable to prevent tampering after installation

shown
04662

INTEGRAL ENERGY ABSORBER

In-line shock absorber reduces loads transmitted to anchorage

STRONGHOLD TETHER

Tethers handle to suitable anchor to prevent drops

INCLUDES O-RINGS

Two O-rings for easy connection and smooth movement along webbing.

VISUAL TENSION INDICATOR

Tension HLL until indicator shows green – no measuring needed.



Tensioner: Zinc-Plated Steel **Webbing:** Double-Braided Polyester
Cross Arm Straps: Double-Braided Polyester & Galvanized Steel
O-Rings: Zinc-Plated Steel
Capacity (per user): 1 User: 130-420 lbs. 2 Users: 130-310 lbs.

FOR MORE INFO, PLEASE CALL 1.800.466.6385 OR VISIT GUARDIANFALL.COM

WEB HLL

HORIZONTAL LIFELINE

TECHNICAL DATA & SELL SHEET - ISSUE 1

Standards

- OSHA 1910
- OSHA 1926 Subpart M



Performance:

- Maximum Users: 2
- Minimum Breaking Strength (MBS): 5,000 lbs.

Notes:

- If HLL anchorage is installed below worker's harness dorsal D-ring, worker must use an extended free fall connecting device
- Not for simultaneous use in Fall Arrest & Fall Restraint

Applications



Personal Fall Arrest: Web HLL may be used to support a MAXIMUM 2 PFAS for use in Fall Arrest applications. Structure must withstand loads applied in the directions permitted by the system of at least 3,600 lbs. Maximum free fall is 6', or up to 12' if used in combination with equipment explicitly certified for such use. Applicable D-ring: Dorsal.



Restraint: Web HLL may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, & Shoulder.

Prod. Code	Description	Length	User Weight
04662	Web Horizontal Lifeline with 2x O-rings, 2x Cross Arm Straps, Tool Tether, and Carry Bag	65'	130-310 lbs