

# ADJUSTABLE ROPE POSITIONING LANYARD

## KERNMANTLE ROPE

High-strength, low-stretch rope provides solid feel under load

## POLYESTER SHEATH

Additional protection against abrasions and cuts

## SEWN TERMINATIONS

Lightweight, strong terminations are easy to inspect

36102 shown

## DOUBLE-LOCKING CARABINERS OR SNAP HOOKS

Aluminum or Steel with 3,600 lbs. Gate Strength

## ALUMINUM LOCKING MECHANISM

Spring-loaded trigger allows one-handed operation

**Lanyard Material:** High-Strength Nylon Kernmantle Rope

**Capacity:** 130-420 lbs.

**Connectors:** Steel or Aluminum Carabiners or Snap Hooks

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**

PROD CODE

**#36100 - 36103**

# ADJUSTABLE ROPE POSITIONING LANYARD

## TECHNICAL DATA SHEET

### Standards

- OSHA 1910.140
- OSHA 1926.502
- ANSI Z359.3-2019
- ANSI A10.32-2012



#### Performance:

- Maximum Users: 1

#### Notes:

- Use suitable back-up Fall Arrest system

## Applications



**Work Positioning:** Adjustable Rope Positioning Lanyard may be used in Work Positioning applications. Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands. Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs. Maximum allowable free fall is 2'. Applicable D-rings: Side (Pairs only).

### CONFIGURATIONS:

Prod. Code	Description	Length
36100	Adjustable Rope Positioning Lanyard with Aluminum Carabiners	8'
36101	Adjustable Rope Positioning Lanyard with Aluminum Snap Hooks	8'
36102	Adjustable Rope Positioning Lanyard with Steel Carabiners	8'
36103	Adjustable Rope Positioning Lanyard with Steel Snap Hooks	8'

FOR MORE INFO, PLEASE CALL **1.800.466.6385** OR VISIT **GUARDIANFALL.COM**

PROD CODE

**#36100 - 36103**