

Tether Cinch Loop Series

Installation and Usage Instructions

85511 (Rev. A)

Please read instructions carefully and fully before installation and/or usage.



IMPORTANT INFORMATION:

- Dispose of if a drop is experienced
- Inspect prior to each use for the following and discard if found:
 - wearing of the rope
 - degraded stitching
 - fraying or cuts to the rope
 - deformation of metal components

TETHCNCHLPSW

Inspect prior to each use for the following and discard if found:



1. Deformation of the swivel ring
2. Wearing of the rope at the swivel cup attachment
3. Degraded stitching
4. Fraying or cuts to the rope

WARNINGS

ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DO NOT USE THIS PRODUCT ON OR NEAR ROTATING EQUIPMENT. IMPROPER USE COULD RESULT IN DEATH OR DISMEMBERMENT. IF ANY CRACKS, RIPS OR TEARS ARE NOTED, PRODUCT REPLACEMENT IS REQUIRED.

Step 1



Inspect tool tether hole to assure there are no burrs or sharp edges that could cut the cinch loop.

Step 3



Pull on the swivel ring/eye hole to tighten and position to the desired location.

Step 2



Insert the rope end loop through the tool tether hole as shown and feed the other end back through the loop.

Step 4



Attach tool tether to the swivel ring/eye hole and begin use.

TOOL SELECTION GUIDE

Part No.	Weight Rating	Max Tether	Use With	Do Not Use With
TETHCNCHEY	10 lbs / 4.53kg	5' (152.40 cm)	Screw drivers, Nut Drivers, Brushes, Scissors, Levels, Adjustable Wrenches, Pipe Wrenches, Ratchets, Hammers and much more.	Tools with handles that are not attached. Tools with holes that will damage the tether.
TETHCNCHDT	10 lbs / 4.53kg	5' (152.40 cm)		
TETHCNCHLPSW	10 lbs / 4.53kg	4' (121.92 cm)		

INSTALLATION

TY-FLÖT

Ty-Flot, Inc. • 305 Massabesic Street • Manchester, NH 03103
 www.ty-flot.com • Phone: 603-669-5169 • Fax: 603-669-5113
CUTTING-EDGE PREVENTION™