

SINGLE FUNCTION LOCKING BUNGEE

TOOL TETHER

Installation and Usage Instructions

Please read instructions carefully and fully before installation and/or usage.



Initial Setup Instructions

- 1 Use the Tool Attachment Guide to ensure proper tool pairing.
- 2 Set up and/or locate an appropriate attachment point on the tool.

Usage Instructions

- 1 Attach one end of the tether to a tool and the other end to the user or anchor point.
 - a. Use an anchor point whenever possible
- 2 Ensure anchor point is fixed (for example ladders are not fixed)
- 3 Destroy and discard if
 - a. there is any evidence of wear or damage
 - b. tool is dropped and tether is fully extended
 - c. any doubt to product's integrity
- 4 Do not suspend a tool on its tether and do not use at full extension
- 5 Inspect prior to every use
- 6 When storing do not put tools on top of the tether
- 7 Monitor the cord-lock and periodically tighten if it starts to loosen

IMPORTANT NOTES

TOOL USE ONLY. Bungee style tool tethers are not intended for use on the wrist. Never attach tether to a pant loop. Never tie a knot to attach the tether. Avoid tangles as they may unintentionally open carabiner. Always cinch corded ends, never wrap.

WARNINGS

ALWAYS WEAR APPROPRIATE PROTECTIVE EQUIPMENT. DO NOT USE THIS PRODUCT ON OR NEAR ROTATING EQUIPMENT. IMPROPER USE COULD RESULT IN DEATH OR DISMEMBERMENT. IF ANY CRACKS, RIPS OR TEARS ARE NOTED, PRODUCT REPLACEMENT IS REQUIRED.

CARABINER ENDS

Step 1



Hook carabiner on appropriate attachment point. See Tool Attachment Guide below.

Step 2



Ensure carabiner is fully closed

- 1 Spring Action – Closed/Latched
- 2 Triple Lock – Lock Engaged

Step 3



Only cinch carabiner end on anchor points and belts and only when the tool used is incapable of backing through.

CORD ENDS

Step 4



Cinch cord around proper point. See Tool Attachment Guide below.

Step 5



Tighten cord-lock down over the cinch (if supplied).

IMPORTANT




Never cinch a cord or carabiner around the wrist.

TOOL ATTACHMENT GUIDE

Never attach more than 6 lbs to the body. Never overload a tool tether for any reason.

Part No.	Weight Rating
BNGEXTCCAL	5lb/2.2kg
BNGEXTRPRP	15lb/6.8kg
BNGEXTRPSS	15lb/6.8kg
BNGEXTRP3T	15lb/6.8kg
BNGEXTCCSS	15lb/6.8kg
BNGEXTCC3T	20lb/9kg



Attach on tool areas that are fully closed and/or points where tool shape would prevent release.



Avoid Tangles. Do not cinch without attachment point or significant geometry.

