

# BUNGEE TOOL TETHER

Part # 10736

## Instruction Manual



### Contents

2	Important Notes
2	Applicable Safety Standards
2	Safety Information
3	Installation
4	Specifications and Materials

✘ Do not throw instructions away.

⚠ Read and understand instructions before using this equipment.

## Important Notes

- Tool tethers are suitable only for hand tools weighing the specified weight rating or less that have manufacturer's intended attachment features, such as Stronghold attachment point products, rings or holes, that can be properly secured with the various tether end types.
- This product is intended for use by personnel who are trained and knowledgeable regarding working with hand tools at height and/or near machinery.
- Inspect before each use for damage and proper function:
  1. Check all hardware for abrasion, deformity, cuts and sharp edges.
  2. Check for tears, cuts, fraying, abrasion, discoloration, burns, holes, mold, unsplicing, pulled or broken stitches, or other signs of wear or damage.
  3. For coil style products for cracks, slits, stress risers or lack of retraction memory in coil material.
  4. Do not use and always quarantine if any of the above apply or if damaged or not functioning correctly.
- Tool tethers should only be attached to anchors (i.e. belts and harnesses) that have manufacturer's intended attachment specifications.
- Tool tethers are not intended for use on the wrist.

## Applicable Safety Standards

Meets or exceeds:

- ANSI / ISEA 121-2018

## Safety Information

- ▲ **WARNING!** Do not use near moving parts, mechanisms, running machinery or rotating equipment.
- ▲ May contain electrically conductive materials.
- ▲ Do not alter product in any way from its original state.
- ▲ Use only with tools that are specifically designed for tethering, or by using appropriate Stronghold brand attachment products.

## Installation

### ■ Carabiner Ends

Hook or cinch carabiners as shown.



Ensure carabiners are closed and remain locked and/or tight throughout use.

### ■ Corded Ends

Cinch cord as shown.



Always cinch corded ends, never wrap.



## Specifications

### Bungee Style Tool Tethers

Part #	Max Tool Weight	Tether Length	Clearance Distance*
10736	15 lbs (6.8 kg)	52" (132 cm)	52" (132 cm)

\*To determine how far a tool could fall before stopping add clearance distance of all products used.

## Materials

**Nylon and zinc-plated steel**

## Maintenance, Cleaning, and Storage

**Clean with a damp cloth and mild soap, wipe off excess and thoroughly dry.**

**Store this product away from tools and other objects that could cause damage.**

---

607 East Sam Houston Parkway South, Suite 800  
Pasadena, TX 77503

+1 (800) 466 6385  
info@guardianfall.com

**guardianfall.com**