

MOBI Skylight Netting



Part #: 70024; 70025

70024: 6.5' x 6.5'

70025: 9.8' x 9.8'

Compliant with the following regulations and consensus standards:
OSHA 1926.502, OSHA 1910.140, and EN795-2012.

Custom configurations not available. Not repairable.
Contact customer service for details.



MOBI Skylight Netting is suitable for the following applications:



Personal Fall Arrest: MOBI Skylight Netting may be used in Personal Fall Arrest applications to support a **MAXIMUM 1** Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs. Maximum free fall is 6' unless used in combination with equipment explicitly certified for extended free fall. Applicable D-ring: Dorsal.



Restraint: MOBI Skylight Netting may be used in Restraint applications. Restraint systems prevent workers from reaching the leading edge of a fall hazard. Always account for fully deployed length of lanyard/SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs. No free fall is permitted. Restraint systems may only be used on surfaces with slopes up to 4/12 (vertical/horizontal). Applicable D-rings: Dorsal, Chest, Side, Shoulder.



Fall Prevention: MOBI Skylight Netting may be used in Fall Prevention applications. Fall Prevention Systems are placed around the leading edges of any and all fall hazards to prevent a worker from going over an edge, and may be used in substitute of Fall Protection or safety netting systems. Installation requirements for Parapet Anchor Systems set forth in this manual **MUST** be adhered to.

**For all applications: worker weight capacity range
(including all clothing, tools, and equipment) is 130-310 lbs., or up to 420 lbs.
if used in combination with equipment explicitly certified for such use.**

Materials: galvanized steel and polypropylene.

Follow product instructions for correct set-up and use.

MAXIMUM 1 connection per MOBI Skylight Netting.

UPC-A Code(s):

70024: 672421700243

70025: 672421700250

