

## C-SLAB GRABBER

**GUARDRAIL**

FOR MORE INFO, PLEASE CALL  
1.800.466.6385 OR VISIT [GUARDIANFALL.COM](http://GUARDIANFALL.COM)

### FEATURES & BENEFITS:

- DURABLE, POWDER-COATED STEEL
- COMPATIBLE WITH WIDE RANGE OF CONCRETE SLABS
- QUICK-ADJUST HANDLE
- EASY TO MOVE AS WORK PROGRESSES
- RESISTANT TO CORROSION AND DAMAGE

**ALSO COMPATIBLE WITH CABLE AND SNAP-ON METAL RAILS.**



▶ **OVERLAP 2X4'S OR 2X6'S**

▶ **BACKUP SAFETY SYSTEM**

▶ **ANTI-SLIP TAPE**

▶ **IDEAL SOLUTION FOR INSTALLING GUARDRAILS ON CONCRETE DECKING**

### ▶ SPECS

#### STANDARDS:

OSHA 1910 & 1926 SUBPART M

#### MATERIALS:

POWDER-COATED STEEL AND GALVANIZED STEEL

#### MORE SPECS & REQUIREMENTS:

- C-SLAB GRABBER CAN BE ADJUSTED TO FIT CONCRETE BEAMS FROM 1½" TO 36" THICK.
- MAXIMUM PERMITTED SPACING BETWEEN C-SLAB GRABBERS IS 8'
- TOPRAILS MUST BE 42" (+/- 3") ABOVE THE WORK SURFACE OR, IF USED IN STILT WORK APPLICATIONS, 42" PLUS HEIGHT OF STILTS.

- TOEBOARDS ARE REQUIRED ON SURFACES WITH SLOPES MORE THAN 4/12 (VERTICAL/HORIZONTAL).
- TOEBOARDS MUST BE A MINIMUM 3½" FROM THEIR TOP EDGE TO THE WORK SURFACE, AND MUST NOT HAVE GREATER THAN ¼" CLEARANCE BETWEEN THEIR BOTTOM EDGE AND THE WORK SURFACE.

### DESCRIPTION: CONCRETE SLAB GRABBER

PART #: **15500**

WEIGHT: **22 LBS**

### C-SLAB GRABBERS ARE SUITABLE FOR THE FOLLOWING APPLICATIONS:

- **FALL PREVENTION:**
  - C-Slab Grabber Guardrail Systems may be used in Fall Prevention applications ONLY.
  - Fall Prevention Systems are placed around the leading edges of any and all fall hazards to prevent a worker from going over an edge and may be used in substitute of Fall Protection or safety netting systems.
  - Installation requirements for C-Slab Grabber Guardrail Systems set forth in equipment instructions MUST be adhered to.
  - Fall Arrest, Work Positioning, Climbing, Rescue, and any other systems must NEVER be connected to Fall Prevention Systems.