

FABX2A-LE

50FT SRL-LE

TECHNICAL DATA SHEET - ISSUE 8



The FABX2A-LE is available with 50ft galvanized steel cable. The FABX2A-LE has all the features of the other FABX self retracting lifelines, lightweight handling, excellent serviceability and exceptional performance with the addition of a leading edge rating of 0.005" or above.



Hand Grip

The ergonomic handle is designed for comfort when handling or performing the function test.



Force Management System

Energy is dissipated during a fall using the force management system which is all concealed within the hand grip.



Carry Handle Attachments

Optional shoulder strap and carrying handle are available which can be easily fitted by the user.




Fall Indicator Hook

The swivel hook includes a fall indicator, which clearly shows if the device has been subjected to a shock load.



Leading Edge Rated

After extensive research and development the FABX2LE has a horizontal edge rating radius of 0.005" or above.



BCS Brush Cleaning System

The entry aperture has a pair of opposing brushes to minimize take up of debris into the device.

FABX2A-LE

50FT SRL-LE

TECHNICAL DATA SHEET - ISSUE 8

SKU	Description	Weight
32101	50' Galvanized Steel Cable SRL-LE with Aluminum Swivel Carabiner	15 lbs
32101CSA	50' Galvanized Steel Cable SRL-LE with Aluminum Swivel Carabiner	15 lbs



Features

- **Hand Grip**
Designed for comfort when performing function test
- **PC/ABS Housing**
Lightweight, high strength housing
- **Independent brake pawls**
The two pawls work independently of one another, this ensures a "fail safe" capability.
- **Carry handle attachment**
Optional shoulder strap and carrying handle are available which can be easily fitted by the user
- **User weight**
130-310 lbs (inc. tools and equipment)

Standards

- ANSI Z359.14:2014 SRL-LE Class B (overhead use)
- ANSI A10.32-2012
- OSHA 1910 & OSHA 1926 Subpart M
- CSA Z259.2.2-2017 (32101CSA)

