

## TRUSS BOSS ANCHOR

ANCHORAGE CONNECTOR

### FEATURES & BENEFITS

- Installs on roof truss, and is ideal for use during construction of framework
- Lightweight and durable
- Kits include anchor cap and waterproof flashing to protect from weather for both composite and tile roofs
- Kit can be installed without penetrating roof sheathing
- Easy to install

Anchor Cap  
& Waterproof Flashing



SHOWN:  
**PART #00432**

# SPECIFICATIONS

## STANDARDS:

OSHA 1926 Subpart M & 1910

## MATERIALS:

Zinc-plated & Galvanized Steel

## WORKER CAPACITY:

130 - 310 lbs., or up to 420 lbs. if used in combination with equipment explicitly certified for such use.

## PERFORMANCE:

- Maximum Users: 1

## NOTES:

- Can be installed on truss while truss is still on the ground for additional safety

## PART #

## DESCRIPTION

00420

Truss Boss Anchor Kit: Truss Boss Anchor, Weather Flashing, Anchor Cap, & Nails

00423

Truss Boss Flashing Kit: Weather Flashing & Anchor Cap

00432

Truss Boss Anchor

00442

Tile Truss Boss Anchor Kit: Truss Boss Anchor, Weather Flashing, & Anchor Cap

# APPLICATIONS



## PERSONAL FALL ARREST:

Truss Boss anchors may be used in Personal Fall Arrest applications to support:

- Maximum 1 Personal Fall Arrest System (PFAS). Structure must withstand loads applied in the directions permitted by the system of at least 5,000 lbs.
- Maximum allowable free fall is 6'.
- Applicable D-rings: Dorsal.



## WORK POSITIONING:

Truss Boss anchors may be used in Work Positioning applications.

- Work Positioning systems allow a worker to be supported while in suspension and work freely with both hands.
- Structure must withstand loads applied in the directions permitted by the system of at least 3,000 lbs.
- Maximum allowable free fall is 2'.
- Applicable D-rings: Side.



## RESTRAINT:

Truss Boss anchors may be used in Fall Restraint applications to support:

- Maximum 1 PFAs
- Prevent workers from reaching the leading edge of a fall hazard.
- Always account for fully deployed length of SRL. Structure must withstand loads applied in the directions permitted by the system of at least 1,000 lbs.
- No free fall is permitted.
- May only be used on surfaces with slopes up to 4/12 (vertical/horizontal).
- Applicable D-rings: Dorsal, Chest, Side, & Shoulder.



**NEED MORE INFORMATION?**

P: 1.800.466.6385 | VISIT OUR WEBSITE: [GUARDIANFALL.COM](http://GUARDIANFALL.COM)