



WORLD'S STRONGEST BOND™

# Technical Data Sheet

Revised 05/2022

## MufflerSeal™

### PRODUCT BRIEF

J-B Weld Muffler Cement is a metal-containing paste that prevents and seals leaks at seams and gaps of pipe and exhaust connection points. When fully cured, this paste dries to a cement-like hardness that is heat resistant up to 850°F.



Part Number	Container Size
37906	6oz Tube
37912	12oz Tube

### PRODUCT BENEFITS

- High temperature resistant to 850°F
- Sets in 30 min
- Negligible, if any shrinkage

### TYPICAL APPLICATIONS

- Sealing cracks, small gaps and connections
- Mufflers, tailpipes, grills, water heater pipes

### DIRECTIONS FOR USE

1. CLEAN: Clean the entire surface area of oil, dirt and rust.
2. WET: Wet area to be repaired with water.
3. APPLY: Apply sealant liberally around surface area to be sealed or filled. Seal or fit pipe or joint pieces together. Clean away any excess sealant.
4. CURE: Allow 30 minutes to dry, then run vehicle for 10 minutes. Allow for longer cure in colder temperatures.

### VOC STATUS:

Compliant for sale in all 50 states.

### DISCLAIMER

*\*Not recommended for Polyethylene Plastic (PE), Polypropylene Plastic (PPE), Nylon, and other highly flexible materials and non-porous surfaces.*

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.

