



WORLD'S STRONGEST BOND™

Technical Data Sheet

Revised 10/2020

ClearWeld™

PRODUCT BRIEF

ClearWeld™ is a quick setting, multipurpose two-part epoxy that provides a strong and lasting bond on most surfaces including tile, most plastics, ceramic, glass, wood and metal. ClearWeld™ is designed to cure with a clear, transparent bond when used at thicknesses of less than 15 mil. ClearWeld™ has a 1:1 mixing ratio, sets in 5 minutes and will fully cure within an hour. With a strength of 3900 PSI, ClearWeld™ sets to a hard, permanent bond.

Part Number	Container Size
50114	Carded 14ml Syringe w/ static mixer

PRODUCT BENEFITS

- Dries Clear
- Strength is 3900 PSI
- Sets in 5 minutes
- Cures in 1 hour
- Includes static mixer for easy mixing

TYPICAL APPLICATIONS

- Use on Metal, Plastic*, Wood, Concrete, Ceramic & Tile, Fiberglass
- Home, Auto, Toy, Plumbing, Industrial and Marine Repairs
- Crafts and Outdoor Equipment

DIRECTIONS FOR USE

1. **PREPARE SURFACE:** Clear repair area of dirt, grease, oil, paint, rust, etc. For best results use a detergent or degreaser to clean the surface, then roughen surface with file or coarse sandpaper to provide the best repair.
2. **ATTACH:** Snap off cap. Press E-Z Mixer down and turn clockwise to attach.
3. **APPLY:** Press down on plunger and apply with E-Z Mixer directly onto surface in even coat, weld bead, or extruded shape as needed. Dispose of E-Z Mixer and use removeable cap located on plunger to store.
4. **DRY:** Sets in 5 minutes. Cures in 1 hour. If temperature is below 40°F, then set time is longer.

VOC STATUS:

Compliant for sale in all 50 states.

DISCLAIMER

**Not recommended for Polyethylene Plastic (PE), Polypropylene Plastic (PPE), Nylon, and other highly flexible materials and non-porous surfaces.*

The information and recommendations contained herein are based on our research and are believed to be accurate, but no warranty, express or implied, is made or should be inferred. Purchasers should test the products to determine acceptable quality and suitability for their own intended use.

