LED Exterior Ceiling



START FROM HERE

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- · Prepare everything in a clear area
- Wear gloves at all times during this installation
- · Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Technical Support: 1-855-855-8926

Please Note:

- This Kuzco LED fixture comes with pre-wired LED module(s)
- Unless instructed, Do Not touch any part of the LED module(s) as any unnecessary contact with the module could cause permanent damage
- Use 0-10V type of dimmer for dimming application
- · Must be installed on a covered ceiling
- 120-277V input

1. Remove fixture from its original package.

2. Separate fixture body (2a) from mounting plate (1c) by removing set screws (2f) with allen key.

3. Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package.

4. Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts **(1b)** provided in hardware package.

5. Attach fixture body **(2a)** to mounting plate **(1c)** with set screws **(2f)** and allen key.

6. For Wall Mount Only: To prevent moisture from entering the electrical junction box (1a) and causing a short, seal around the top perimeter between the fixture and the wall with weather resistant caulking (Illustration 1).

| PRODUCT ID | PART |
|---------------|-------------------------|
| 1c. | XHBCC1078-BK |
| 1e. | XHPP832-8 |
| 2f. | XHSSM5-14 |
| Lens | XLS-EC34111-FR |
| LED Driver | XDR-BQ-BQE25-600-UNV-UD |
| Allen Key | XHAK-M5 |





