



if it flows,
we go with it

1.800.665.4499
barrplastics.com

HARDWARE:
 (8) HEX HEAD CAP SCREWS, 5/16 X 1-1/4
 (8) 5/16 LOCK WASHERS
 (8) 5/16 HEX NUTS

14 GA FORMED BOX
 5 1/2 X 22 X 1 1/8 OUTSIDE
 WELD CORNERS
 3" DIA HOLE IN CENTER

2 X 1 X 1/8 CHANNEL
 (2) REQ'D.

3/16 X 1 FLAT
 5-1/4 LONG
 (2) REQ'D.
 WELD TO CHANNEL

1-1/2 X 1-1/2 X 3/16 ANGLE,
 18 LONG, WELD TO CHANNELS
 (2) REQ'D.

1-1/2 X 35 X 14 GA BANDS, (2) REQ'
 (37 BLANK LENGTH)

NOTE: ALL HOLES 3/8 DIA.
 FINISH ALL STEEL PARTS WITH
 BLACK ENAMEL

NORWESCO		REV
ST. BONIFACIUS, MN		
STAND - 35 USG (132 LTRS) INDUCTOR TANK		
WT. (LBS) 28.0	DWG NO. 65517	

ALL INFORMATION CONTAINED IN THIS DRAWING IS STRICTLY CONFIDENTIAL AND PROPERTY OF BARR PLASTICS INC. NO PART SHALL BE COPIED OR REPRODUCED WITHOUT THE WRITTEN CONSENT OF BARR PLASTICS INC.

<p>Customer Drawing Approval</p> <p>Customer _____</p> <p>Barr Plastic Inc. _____</p>		<p>PROJECT: - TANK APPROVAL DWG</p> <p>CLIENT: -</p> <p>DRAWING REF: -</p> <p>DATE: 15 SEP 05</p> <p>SCALE: -</p> <p>REV: -</p>	<p>MATERIAL SPECIFICATIONS</p> <p>HDPE 1.5 SPG</p> <p>ALL FITTINGS ARE POLYPROPYLENE WITH EPDM GASKETS</p>
--	--	---	--