



Rainwater Harvesting Pumps

The Divertron Submersible Pumps

- Divertron X Model is equipped with a 1" FPT stainless steel intake fitting for use with floating suction assemblies
- Divertron model has a screened intake around bottom of pump
- Automatic operation (on/off) when taps are opened and closed
- Built-in electronic pressure switch and flow sensor
- Equipped with dry-run protection and built-in non return check valve
- Easy to use
- No wiring or pumpstart relay rec irrigation systems
- High reliability
- High performance 4-stage pump
- Supplied with 48 ft. power cord
- 115V A/C, 10 Amps Max
- 157' Max Total Dynamic Head (1
- Up to 25 GPM
- Up to 64 PSI
- CSA Approved



Part #	Motor Type & HP	Max PSI/ Head	Max Flow Capacity	Inlet/Outlet Size (in)	Liquid Temp	Elec. Volt/ Amp/PH	Solid Handling
Divertron 1200 / 60113145	Electric, 3/4 HP	118 ft	25 GPM	1 Bottom Screen Intake / 1	120 F / 49 C	115 V, 10 Amp Max, 1PH	No
Divertron 1200X / 60113167	Electric, 1 HP	157 ft	25 GPM	1-Jan	120 F / 49 C	115 V, 10 Amp Max, 1PH	No