HB1239 L.003

1

2 3

4

5

6

7

8 9

10

11 12

13

14

15 16

17

18 19

20

21

22 23

24 25

26

27 28

29 30

31

32

33

34

HOUSE COMMITTEE OF REFERENCE AMENDMENT

Committee on Transportation, Housing & Local Government. HB24-1239 be amended as follows:

Amend printed bill, page 2, after line 1 insert:

"SECTION 1.	In Colorado Revised Statutes,	add 24-32-135 as
follows:		

- 24-32-135. Single exit building code definitions. (1) AS USED IN THIS SECTION, UNLESS THE CONTEXT OTHERWISE REQUIRES:
- (a) "AUTOMATIC SPRINKLER SYSTEM" MEANS AN INTEGRATED SYSTEM OF UNDERGROUND AND OVERHEAD PIPING DESIGNED IN ACCORDANCE WITH FIRE PROTECTION ENGINEERING STANDARDS. THE SYSTEM MUST INCLUDE A SUITABLE WATER SUPPLY. THE PORTION OF THE SYSTEM ABOVE GROUND MUST BE A NETWORK OF SPECIALLY SIZED OR HYDRAULICALLY DESIGNED PIPING INSTALLED IN A STRUCTURED AREA, GENERALLY OVERHEAD, AND TO WHICH AUTOMATIC SPRINKLERS ARE CONNECTED IN A SYSTEMATIC PATTERN.
 - (b) "BOARDING HOUSE" MEANS A BUILDING ARRANGED OR USED FOR LODGING FOR COMPENSATION, WITH OR WITHOUT MEALS, AND NOT OCCUPIED AS A SINGLE-FAMILY UNIT.
 - (c) "COURT" MEANS AN OPEN, UNCOVERED SPACE, UNOBSTRUCTED TO THE SKY, BOUNDED ON THREE OR MORE SIDES BY EXTERIOR BUILDING WALLS OR OTHER ENCLOSING DEVICES.
- (d) "DIVISION" MEANS THE DIVISION OF LOCAL GOVERNMENT CREATED IN SECTION 24-32-103.
- (e) "DWELLING UNIT" MEANS A SINGLE UNIT PROVIDING COMPLETE, INDEPENDENT LIVING FACILITIES FOR ONE OR MORE PERSONS, INCLUDING PERMANENT PROVISIONS FOR LIVING, SLEEPING, EATING, COOKING, AND SANITATION.
- (f) "EGRESS COURT" MEANS A COURT OR YARD THAT PROVIDES ACCESS TO A PUBLIC WAY FOR ONE OR MORE EXITS.
- (g) "EXIT" MEANS THE PORTION OF A MEANS OF EGRESS SYSTEM BETWEEN THE EXIT ACCESS AND THE EXIT DISCHARGE OR PUBLIC WAY.
- (h) "EXIT ACCESS" MEANS THE PORTION OF A MEANS OF EGRESS SYSTEM THAT LEADS FROM ANY OCCUPIED PORTION OF A BUILDING OR STRUCTURE TO AN EXIT.
- (i) "EXIT DISCHARGE" MEANS THE PORTION OF A MEANS OF EGRESS SYSTEM BETWEEN THE TERMINATION OF AN EXIT AND A PUBLIC WAY.
- 35 (j) "FIRE-RESISTANCE RATING" MEANS THE PERIOD OF TIME A 36 BUILDING ELEMENT, COMPONENT, OR ASSEMBLY MAINTAINS THE ABILITY 37 TO CONFINE A FIRE, CONTINUES TO PERFORM A GIVEN STRUCTURAL 38 FUNCTION, OR BOTH.
- 39 (k) "GRADE PLANE" MEANS A REFERENCE PLAN REPRESENTING THE 40 AVERAGE OF FINISHED GROUND LEVEL ADJOINING THE BUILDING AT

EXTERIOR WALLS. WHERE THE FINISHED GROUND LEVEL SLOPES AWAY 1 FROM THE EXTERIOR WALLS, THE REFERENCE PLAN MUST BE ESTABLISHED 2 BY THE LOWEST POINTS WITHIN THE AREA BETWEEN THE BUILDING AND 3 THE LOT LINE OR, WHERE THE LOT LINE IS MORE THAN SIX FEET FROM THE 4 BUILDING, BETWEEN THE BUILDING AND A POINT SIX FEET FROM THE 5 6 BUILDING.

- (1) "GROUP R-2 OCCUPANCY" MEANS A RESIDENTIAL OCCUPANCY CONTAINING SLEEPING UNITS OR MORE THAN TWO DWELLING UNITS WHERE THE OCCUPANTS ARE PRIMARILY PERMANENT IN NATURE.
- (m) "INTERIOR EXIT STAIRWAY" MEANS AN EXIT COMPONENT THAT SERVES TO MEET ONE OR MORE MEANS OF EGRESS DESIGN REQUIREMENTS, SUCH AS REQUIRED NUMBER OF EXITS OR EXIT ACCESS TRAVEL DISTANCE, AND PROVIDES FOR A PROTECTED PATH OF EGRESS TRAVEL TO THE EXIT DISCHARGE OR PUBLIC WAY.
- "MEANS OF EGRESS" MEANS A CONTINUOUS AND (n) UNOBSTRUCTED PATH OF VERTICAL AND HORIZONTAL EGRESS TRAVEL FROM ANY OCCUPIED PORTION OF A BUILDING OR STRUCTURE TO A PUBLIC WAY. A "MEANS OF EGRESS" CONSISTS OF AN EXIT, EXIT ACCESS, AND EXIT DISCHARGE.
- (0) "OCCUPANT LOAD" MEANS THE NUMBER OF PERSONS FOR WHICH THE MEANS OF EGRESS OF A BUILDING OR A PORTION OF A BUILDING IS DESIGNED.
 - (p) "OPENING" MEANS A CAVITY THAT ALLOWS AIRFLOW.
- (q) "PUBLIC WAY" MEANS A STREET, ALLEY, OR OTHER PARCEL OF LAND OPEN TO THE OUTSIDE AIR LEADING TO A STREET THAT HAS BEEN DEEDED, DEDICATED, OR OTHERWISE PERMANENTLY APPROPRIATED TO THE PUBLIC FOR PUBLIC USE AND WHICH HAS A CLEAR WIDTH AND HEIGHT OF NOT LESS THAN TEN FEET.
- "SINGLE-FAMILY UNIT" MEANS ONE DWELLING UNIT DESIGNATED OR CONSTRUCTED TO SERVE ONLY ONE HOUSEHOLD OR FAMILY AS THE PRIMARY RESIDENCE.
- (s) "Unprotected opening" means a doorway, window, or OPENING OTHER THAN ONE EQUIPPED WITH A CLOSURE HAVING THE REQUIRED FIRE PROTECTION RATING.
- (t) "YARD" MEANS A DEFINED AREA WITHIN THE PROTECTED PREMISES. A ZONE CAN DEFINE AN AREA FROM WHICH A SIGNAL CAN BE RECEIVED, AN AREA TO WHICH A SIGNAL CAN BE SENT, OR AN AREA IN WHICH A FORM OF CONTROL CAN BE EXECUTED.
- (2) On or before September 1, 2026, the division shall CREATE A CODE THAT ESTABLISHES THAT NOT MORE THAN FIVE STORIES 41 OF GROUP R-2 OCCUPANCY IN A BUILDING ARE PERMITTED TO BE SERVED 42 BY A SINGLE EXIT UNDER THE FOLLOWING CONDITIONS: 43

(a) THE BUILDING HAS SIX STORIES OR LESS ABOVE GRADE PLANE;

39 40

7

8

9

10

11 12

13

14

15

16 17

18 19

20

21

22

23

24

25

26

27

28

29

30 31

32

33

34

35

36

37

38

3 An

(c) THE BUILDING HAS NO MORE THAN FOUR DWELLING UNITS ON ANY FLOOR;

(d) The building must have a fire-resistance rating of one hour or more and must also be equipped throughout with an automatic sprinkler system. Residential-type sprinklers shall be used in all habitable spaces in each dwelling unit.

(e) THERE ARE NO MORE THAN TWO SINGLE-EXIT STAIRWAY CONDITIONS ON THE SAME PROPERTY;

(f) The Building has an exterior stairway or interior exit stairway. If the building has an interior stairway, the doors in the stairway must swing into the interior exit stairway regardless of the occupant load served, provided that doors from the interior exit stairway to the building exterior are permitted to swing in the direction of exit travel. The interior exit stairway, including any related exit passageway, must also be pressurized.

(g) THE BUILDING HAS A CORRIDOR THAT SEPARATES EACH DWELLING UNIT ENTRY OR EXIT DOOR FROM THE DOOR TO AN INTERIOR EXIT STAIRWAY, INCLUDING ANY RELATED EXIT PASSAGEWAY, ON EACH FLOOR. A DWELLING UNIT ENTRY OR EXIT DOOR MUST NOT OPEN DIRECTLY INTO AN INTERIOR EXIT STAIRWAY, BUT MAY OPEN DIRECTLY INTO AN EXTERIOR STAIRWAY.

(h) There are no more than twenty feet of travel to the exit stairway from the entry or exit door of any dwelling unit in the building;

(i) THERE ARE NO MORE THAN ONE HUNDRED TWENTY-FIVE FEET OF TRAVEL DISTANCE WITHIN THE EXIT ACCESS PORTION OF A MEANS OF EGRESS SYSTEM;

(j) THE BUILDING'S EXIT DOES NOT TERMINATE IN AN EGRESS COURT WHERE THE COURT DEPTH EXCEEDS THE COURT WIDTH UNLESS IT IS POSSIBLE TO EXIT IN EITHER DIRECTION TO THE PUBLIC WAY;

(k) The Building's elevators are either pressurized, unless the building official approves natural ventilation to be substituted for pressurization where the ventilation would prevent the accumulation of smoke or toxic gases, or open into elevator lobbies;

(1) OTHER OCCUPANCIES IN THE BUILDING DO NOT COMMUNICATE WITH THE GROUP R OCCUPANCY PORTION OF THE BUILDING OR WITH THE SINGLE-EXIT STAIRWAY, EXCEPT THAT PARKING GARAGES AND OCCUPIED ROOFS ACCESSORY TO THE GROUP R OCCUPANCY MAY COMMUNICATE WITH THE EXIT STAIRWAY;

(m) THE EXIT SERVING THE GROUP R OCCUPANCY IN THE BUILDING

- DOES NOT DISCHARGE THROUGH ANY OTHER OCCUPANCY, INCLUDING AN 1 2 ACCESSORY PARKING GARAGE; AND
- (n) THERE ARE NO OPENINGS WITHIN TEN FEET OF UNPROTECTED 3 OPENINGS INTO THE STAIRWAY IN THE BUILDING OTHER THAN REQUIRED 4
- EXIT DOORS HAVING A FIRE-RESISTANCE RATING OF ONE HOUR OR MORE. 5
- 6 (3) THE DIVISION SHALL UPDATE THE CODE ESTABLISHED IN 7 SUBSECTION (2) OF THIS SECTION AS NECESSARY.".
- 8 Renumber succeeding sections accordingly.
- 9 Page 2, line 13, strike "AND ADOPT OR".
- Page 2, strike lines 14 through 17 and substitute "THE SINGLE EXIT 10
- BUILDING CODE ESTABLISHED IN SECTION 24-32-135.". 11
- 12 Page 3, strike line 5 and substitute "DIVISION OF LOCAL GOVERNMENT
- 13 SHALL PROVIDE THE SINGLE EXIT BUILDING CODE ESTABLISHED IN SECTION
- 14 24-32-135 TO ASSIST".
- 15 Page 3, line 24, strike "AND ADOPT OR".
- 16 Page 3, strike lines 25 through 27.
- Page 4, strike line 1 and substitute "THE SINGLE EXIT BUILDING CODE 17
- 18 ESTABLISHED IN SECTION 24-32-135.".
- Page 4, strike line 9 and substitute "THE DIVISION OF LOCAL GOVERNMENT 19
- 20 SHALL PROVIDE THE SINGLE EXIT BUILDING CODE ESTABLISHED IN SECTION
- 21 24-32-135 TO ASSIST".
- 22 Page 4, line 10, strike "ASSISTANCE".

** *** ** *** **