EZ FABRIC S SHAPE COUNTER


PRODUCT CODE: EZ-CRVFABCTR-GS





















Nylon Carry Bag

PRODUCT DESCRIPTION

Two opposingly-connected aluminum counter frames create the S-Shape. Just secure using four screws with wing nuts. Push button snaps connect the lightweight aluminum framework together. One graphic covers the double counter! Position the frame inside the fabric graphic, pullover to fully cover frame, then zip shut the backside. Attach countertop. Graphics available on front, back, sides and top. See your printed graphic through the frosted acrylic countertop piece! Carry bag included. Wooden shelf inserts optional.

DISPLAY DIMENSION	81" W x 38" H x 29.5" L
GRAPHIC DIMENSIONS	118" W x 40" H

GRAPHIC MATERIAL

Stretch Fabric

One piece. Inside hem. Two top zippers.

Aluminum Frame Acrylic Counter Top

SHIPPING WEIGHTS & DIMENSIONS

51 lbs (2 frames only) 53 lbs (2 frames with graphic)

Shipping Dimensions 50" H x 21" W x 14" D

LARGE QUANTITY FREIGHT

Freight Shipping	15 boxes per 49" L x 40" W x 75" H skids
Freight Weight	810 lbs (2 frames only)
	840 lbs (2 frames & graphic)

GRAPHIC TURN AROUND TIME

2 business days after proof approval

Curved Shelf

Curved Stiell	
AVAILABILITY	CA and PA
TOP WEIGHT CAPACITY	75 lbs
SHELF WEIGHT CAPACITY	7 lbs



Optional Curved Shelf

PARTS LIST



Qty 2 - Top Base (Pre-drilled for acrylic counter)



Qty 8 - 33" Vertical Support Bar




Qty 2 - Acrylic Top Counter



Qty 4 - Screw & Wingnut



Qty 2 - Bottom Base



Qty 4 - 13.25" Horizontal Support Bar



Qty 4 - Large Head Bolt


REQUIRED TOOLS



Flathead Screwdriver*



Insert head bolt.



Then screw and tighten.

SET UP INSTRUCTIONS 1/2

Step 1

First, start by building both vertical sides of the EZ Fabric Counter.



Step 3

Set out your bottom base on a flat surface. Be sure not to confuse this base with the top, which has [2] pre-drilled holes for the acrylic counter top. Locate the push-out caps on the inside of the posts.



Step 5

The frame is now ready for the top base. Make sure it appears as shown above.



Step 7

Be sure that there is (1) pre-drilled hole on each side, facing up on the top base.



Step 2

Take (2) 33"support bars and (1) 13.25" support bar and connect them as shown above. Repeat the same process for another set.



Step 4

Push in and then hold the push-out cap on the bottom base so the support bar will slide on. Now slide each bar completely on to the bottom base. You will slide in one push-out cap at a time.



Step 6

Slide on the top base just as mentioned in step 4.



Step 8

Complete the first frame.



SET UP INSTRUCTIONS 2/2

Step 9

Repeat same process for second frame and place frames side by side.



Step 11

Starting from the bottom, slide the graphic on to the frame.



Step 13

Locate the pre-drilled hole on the top base. Make sure this hole aligns with the finished hole on the graphic.




Step 15

The install is now complete.



Step 10

Connect frames with balts and wing nuts.



Step 12

Zip up the graphic around the frame.



Step 14

Align the acrylic counter top holes and insert the large head screws to secure the counter top to the frame.

