

## NITRILE FUEL HOSE 300 PSI

**Construction:**

Tube: Black,smooth,NBR rubber.  
Reinforcement: High strength synthetic yarn.  
Cover: Ozone ,oil resistant synthetic nitrile rubber.

**Application:**

Softwall hose Designed for the delivery of petroleum-based product s,diesel,gasoline,lubricants,fuel,with aromatic content up to 50%

**Temperature:** -32°C(-90°F ) to +82°C(+180°F)

**Characteristics:**

- Weather and abrasion resistant cover
- Flexible and less distortion
- For aromatic content up to 50%



Item Code	I.D		O.D	W.P		B.P		L	M <sup>3</sup>	kg
	inch	mm	mm	bar	psi	bar	psi	m	m <sup>3</sup> /roll	kg/m
RFS-05	3/16"	5	12	20	300	60	900	100	410x410x100	0.15
RFS-06	1/4"	6	13	20	300	60	900	100	440x440x110	0.17
RFS-08	5/16"	8	15	20	300	60	900	100	490x490x120	0.22
RFS-10	3/8"	10	17	20	300	60	900	100	500x500x125	0.25
RFS-13	1/2"	13	22	20	300	60	900	100	480x480x135	0.46
RFS-16	5/8"	16	25	20	300	60	900	50	480x480x150	0.52
RFS-19	3/4"	19	29	20	300	60	900	50	520x520x185	0.64
RFS-25	1"	25	36	20	300	60	900	50	590x590x210	0.85
RFS-32	1-1/4"	32	43	10	150	30	450	50	0.17	1.20
RFS-38	1-1/2"	38	50	10	150	30	450	50	0.19	1.39
RFS-51	2"	51	65	10	150	30	450	50	0.41	1.80

## TEXTILE COVER FUEL HOSE/ GLP HOSE

**Construction:**

Tube:Oil and fuel resistant NBR rubber.  
Cover:Textile braid.

**Application:**

It is applied to circulating diesel, biodiesel, hydraulic oil, machinery oil and lubricating oil etc or the oil products.

**Characteristic:**

- 100% New NBR Materials
- Aging resistant; insulation; oil resistant; acid and alkaline resistant

**Temperature :** -40°C(-104°F ) to +100°C(+212°F )



Item Code	I.D		O.D		W.P		B.P		L	Item Code	I.D		O.D		W.P		B.P		L
	mm	mm	Bar	Psi	Bar	Psi	Bar	Psi	m		mm	mm	Bar	Psi	Bar	Psi	Bar	Psi	m
TCF032	3.2	7	10	150	30	450	100			TCF075	7.5	12.5	10	150	30	450	100		
TCF032	3.5	7.5	10	150	30	450	100			TCF080	8	15	10	150	30	450	100		
TCF041	4	8	10	150	30	450	100			TCF100	10	17	10	150	30	450	100		
TCF042	4	9	10	150	30	450	100			TCF120	12	18	10	150	30	450	100		
TCF050	5	10	10	150	30	450	100			TCF140	14	22	10	150	30	450	100		
TCF055	5.5	10.5	10	150	30	450	100			TCF160	16	23	10	150	30	450	50		
TCF061	6	11	10	150	30	450	100			TCF180	18	26	10	150	30	450	50		
TCF062	6	12	10	150	30	450	100			TCF190	19	27	10	150	30	450	50		
TCF070	7	12	10	150	30	450	100			TCF250	25	33	10	150	30	450	50		