

SH electric wire rope hoist (1/2 rope reeving)

| Technical parameters | | | | | | |
|----------------------|---------------|---------------|----------------------|-----------------|-------------------------|----------------------|
| Type | Capacity(kg) | Working group | Lifting speed(m/min) | Motor power(kw) | Travelling speed(m/min) | Travelling motor(kw) |
| SH3 (2/1A) | 1000 | M4 | 8.4 8.4/2.1 | 1.5 1.5/0.4 | 20 20/6.7 | 0.37 0.37/0.12 |
| SH4(2/1A) | 2000 | M4 | 7.2 7.2/2.4 | 3 3/1 | 20 20/6.7 | 0.37 0.37/0.12 |
| SH5(2/1A) | 3200 | M4 | 7 7/1.6 | 4.5 4.5/1.1 | 20 20/6.7 | 0.37 0.37/0.12 |
| SH6(2/1A) | 5000 | M4 | 7.6 7.6/1.8 | 7.5 7.5/2.0 | 20 20/6.7 | 0.37 0.37/0.12 |
| SH7(2/1A) | 8000 | M4 | 8 8/2 | 13 13/3.4 | 20 20/6.7 | 0.37 0.37/0.12 |
| SH8(2/1A) | 10000 | M4 | 6.4 6.4/1.6 | 13 13/3.4 | 20 20/6.7 | 0.37 0.37/0.12 |