ORIENTFLEX
Quality hose serve the world

WELDING & GAS HOSE

RUBBER TWIN WELDING HOSE 300 PSI

Construction:
Tube : Black, smooth, synthetic rubber
Reinforcement:High strength synthetic yarn braiding
Cover:Blue/green/red, smooth, synthetic rubber

Application:
Designed for welding, cutting and allied processes. Specific welding hose cartering for oxygen, carbon dioxide, nitrogen, argon and fuel gases including acetylene, natural gas, methane and propane available upon request.

Temperature: -32℃ (-90 ℉) to 80℃ （+176 ℉）

Characteristics:
- Anti abrasion smooth cover
- Weather and ozone resistant cover
- Flexible,light weight,less distortion.

Item code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
TWH005	3/16"	4.8+4.8	12+12	20	300	60	900	100	330
TWH006	1/4"	6.4+6.4	13+13	20	300	60	900	100	330
TWH008	5/16"	7.9+7.9	15+15	20	300	60	900	100	330
TWH810	5/16"+3/8"	7.9+9.5	15+17	20	300	60	900	100	330
TWH010	3/8"	9.5+9.5	17+17	20	300	60	900	100	330

RUBBER LPG/ PROPAN/GAS HOSE 300 PSI

Construction:
Tube: Black, smooth, Nitrile synthetic rubber
Reinforcement: High strength synthetic yarn braiding
Cover: orange/red/black, smooth, synthetic rubber NBR or chloroprene CR

Application:
For commercial and family gas cooker oven, the connection of gas system of industrial device. Transport media:LPG,CNG,CH4 etc

Temperature: -32℃ (-90 ℉) to 80℃ （+176 ℉）

Characteristics:
- Anti abrasion smooth cover
- Weather and ozone resistant cover
- Flexible,light weight,less distortion
- Certification: ISO3821,EN559

Item code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	PSI	bar	PSI	m	ft
GASH005	3/16"	4.8	12	20	300	60	900	100	330
GASH006	1/4"	6.4	13	20	300	60	900	100	330
GASH008	5/16"	7.9	15	20	300	60	900	100	330
GASH010	3/8"	9.5	17	20	300	60	900	100	330
GASH012	1/2"	12.7	21	20	300	60	900	100	330

E-mail: john.wu@orientrubber.com Cellphone/Whatsapp/Wechat:0086-13930110983 Skype:orientrubber