

WATER SUCTION HOSE 150 PSI



Construction:

Tube: Black, smooth, NR, SBR rubber compound.

Reinforcement: Multi plies High strength synthetic fibre and helix steel wire

Cover: Black, smooth, cloth impression, SBR rubber compound

Temperature:

-30°C (-22°F) to +80°C (+176°F)

Application:

Hardwall hose designed for suction and discharge of water, and non-corrosive fluids used in construction sites and light duty industrial applications. Ideal high pressure water discharge hose for rugged, tough operating conditions

Characteristics:

- weathering and ozone resistant.
- Anti-aging cover compound
- Flexible and light weight

Item Code	I.D		O.D	W.P		B.P		VACUUM	L	
	inch	mm	mm	bar	psi	bar	psi	bar	m	ft
WSDH-019	3/4"	19.1	30	10	150	30	450	0.8	60	200
WSDH-025	1"	25.4	36	10	150	30	450	0.8	60	200
WSDH-032	1-1/4"	31.8	44	10	150	30	450	0.8	60	200
WSDH-038	1-1/2"	38.1	51	10	150	30	450	0.8	60	200
WSDH-050	2"	50.8	64	10	150	30	450	0.8	60	200
WSDH-063	2-1/2"	63.5	77	10	150	30	450	0.8	60	200
WSDH-076	3"	76.2	90	10	150	30	450	0.8	60	200
WSDH-089	3-1/2"	88.9	104	10	150	30	450	0.8	60	200
WSDH-102	4"	101.6	118	10	150	30	450	0.8	30	200
WSDH-127	5"	127	145	10	150	30	450	0.8	30	100
WSDH-152	6"	152.4	170	10	150	30	450	0.8	30	100
WSDH-203	8"	203.2	224	10	150	30	450	0.8	30	100
WSDH-276	10"	254	276	10	150	30	450	0.8	12	40
WSDH-326	12"	304	326	10	150	30	450	0.8	12	40
WSDH-378	14"	350	378	10	150	30	450	0.8	12	40