

## MULTI-PURPOSE HOSE 300PSI

### Construction:

Tube and Cover: Rubber or TPR (NBR/PVC), smooth, oil resistance

Reinforcement: 1ply or 2ply polyester thread braiding

### Application:

For air, oil and medium grade fuels used in construction, shipyards, mining and agriculture.

### Temperature:

-30°C (-22°F) to +80°C (+176°F)

### Characteristics:

- Oil mist resistant tube and cover.
- Ozone and weather resistant.
- Resistant to ultra-violet (UV)



### Rubber Multipurpose Hose

Item Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
MPH-005	3/16"	4.8	12	20	300	60	900	100	330
MPH-006	1/4"	6.4	13	20	300	60	900	100	330
MPH-008	5/16"	7.9	15	20	300	60	900	100	330
MPH-010	3/8"	9.5	17	20	300	60	900	100	330
MPH-012	1/2"	12.7	21	20	300	60	900	100	330
MPH-016	5/8"	15.9	26	20	300	60	900	100	330
MPH-019	3/4"	19.1	29	20	300	60	900	100	330
MPH-025	1"	25.4	36	20	300	60	900	100	330
MPH-032	1-1/4"	31.8	44	15	225	45	675	60	200
MPH-038	1-1/2"	38.1	54	15	225	45	675	60	200
MPH-050	2"	50.8	66	15	225	45	675	60	200

### TPR(Rubber & Pvc Mixed) Multipurpose Hose

Item Code	I.D		O.D	W.P		B.P		L	M <sup>3</sup>	kg
	inch	mm	mm	bar	psi	bar	psi	m	m	Kg/m
RTPR--06	1/4"	6	12	20	300	60	900	100	440x440x110	0.114
RTPR--08	5/16"	8	15	20	300	60	900	100	490x490x120	0.171
RTPR--10	3/8"	10	17	20	300	60	900	100	500x500x125	0.200
RTPR--13	1/2"	13	22	20	300	60	900	50	480x480x135	0.334
RTPR--16	5/8"	16	25	20	300	60	900	50	480x480x150	0.391
RTPR--19	3/4"	19	28	20	300	60	900	50	520x520x185	0.448
RTPR--25	1"	25	35	20	300	60	900	50	590x590x210	0.636