

LI-ION RECHARGEABLE

DICATA™ INTRINSICALLY SAFE DUAL-LIGHT USB HEADLAMP

XPR-5562GX

# NIGHTSTICK®

Life Depends on Light™



**MAGMATE™** Magnetic Coupler  
USB Rechargeable.



**Enlarged front-mounted dual switches**, easily toggle through the beam options with gloves on.



**Low Profile for Visor Clearance**, on most helmets & hard hats.



**Dual-Light Technology**, focused spotlight and area floodlight at the same time.



**CLASS I  
DIV 1**

**DUAL  
LIGHT®  
TECHNOLOGY**

**IP-67  
DUST/WATER  
PROOF**

**300 LUMENS**

CERTIFIED



1-800-233-2155 • 1-469-326-9400 • [nightstick.com](http://nightstick.com)

© 2020 Bayco Products Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit [nightstick.com](http://nightstick.com) for product updates.

# INTRINSICALLY SAFE DUAL-LIGHT HEADLAMP

## LI-ION BATTERY

**ITEM NUMBER/UPC**

- XPR-5562GX, UPC 0 17398 80774 6

**MARKET APPLICATIONS**

- Hazardous work environments, industrial, fire & rescue

**CERTIFICATIONS**

- cULus, ATEX, IECEX, CE, NFPA

**CASE MATERIAL**

- Engineered polymer

**SPOTLIGHT LUMENS/RUNTIME**

- HIGH: 275L, 6 hrs. runtime  
 - LOW: 100L, 15 hrs. runtime

**FLOODLIGHT LUMENS/RUNTIME**

- HIGH: 250L, 6 hrs. runtime  
 - LOW: 100L, 15 hrs. runtime

**DUAL-LIGHT LUMENS/RUNTIME**

- 300L, 5 hrs. runtime

**CANDELA**

- HIGH: 3,660

**BEAM DISTANCE**

- 120 m

**WATER RATING**

- ANSI IP-67 dustproof / waterproof

**DROP RATING**

- 2 meters

**DIMENSIONS**

- LENGTH: 1.25 in (31 mm)  
 - WIDTH: 3.75 in (95 mm)  
 - DEPTH: 1 in (25 mm)  
 - WEIGHT: 5.8 oz (164 g) without battery

**POWER SOURCE**

- Integrated Li-ion

**WARRANTY**

- Limited lifetime

**WHAT'S INCLUDED**

- Headlamp  
 - Li-ion Battery  
 - Heavy-duty rubber head strap  
 - 4' (304 mm) USB Male (Type A) Magnetic Coupler Charge Cord  
 - Instruction Manual

FL 1 STANDARD	SPOT HIGH	FLOOD HIGH	DUAL-LIGHT
	275 LUMENS	250 LUMENS	300 LUMENS
	6h	6h	5h
	120m		
	3660cd		

**Bayco Products, Inc. XPR-5562GX**  
 640 S. Sanden Blvd., Wylie, TX 75098  
 Ex ia FLASHLIGHT FOR USE IN HAZARDOUS LOCATIONS  
 UL listed for use with Bayco Li-ion Battery Pack 5562-BATT

CLASS I DIV 1 GRPS A-D T4	Ex ia op is IIC T4 Ga
CLASS II & III DIV 1 GRPS E-G T130°C	DEMKO 20 ATEX 2267
CLASS I ZONE 0 AEx ia op is IIC T4 Ga	IECEX UL 20 0036
Ex ia op is IIC T4 Ga	-20°C ≤ Tamb ≤ +40°C
	3.7V/Cell 5562-BATT
	Um 4.2V

CE 2575  
 WARNING: Do not charge battery in a hazardous location  
 SEE INSTRUCTION MANUAL / VOIR MANUEL  
 Meets Requirements of NFPA-1971-8.6 (2013)

WARNING: Do not replace battery when an explosive atmosphere is present  
 MFG MM-YY  
 US Patent 9,713,217



© 2020 Bayco Products, Inc. Items shown are intended as a visual representation for informational purposes only and are subject to change without notice. Visit nightstick.com for product updates. XPR-5562-Series-20

