

## WATER DISCHARGE HOSE 150 PSI



### Construction:

Tube:Black,smooth,NR,SBR rubber compound.

Reinforcement:Multi plies high strength synthetic fibre

Cover:Black,smooth,cloth impression, SBR rubber compound

### Application:

Designed for water and non-corrosive fluids used in construction ,mines and light duty industrial applications.

### Temperature:

-40°C (-104 °F) +70°C (+158 °F)

### Characteristics:

- Weathering and ozone resistant.
- Flexible and light weight
- Max 60m/200ft

Item Code	I.D		O.D	W.P		B.P		L	
	inch	mm	mm	bar	psi	bar	psi	m	ft
WDH1-005	3/16"	4.8	12	10	150	30	450	100	330
WDH1-006	1/4"	6.4	13	10	150	30	450	100	330
WDH1-008	5/16"	7.9	15	10	150	30	450	100	330
WDH1-009	3/8"	9.5	16	10	150	30	450	100	330
WDH1-012	1/2"	12.7	22	10	150	30	450	100	330
WDH1-016	5/8"	15.9	26	10	150	30	450	100	330
WDH1-019	3/4"	19.1	29	10	150	30	450	100	330
WDH1-022	7/8"	22.2	32	10	150	30	450	100	330
WDH1-025	1"	25.4	35	10	150	30	450	100	330
WDH1-032	1-1/4"	31.8	42	10	150	30	450	60	200
WDH1-038	1-1/2"	38.1	48	10	150	30	450	60	200
WDH1-050	2"	50.8	62	10	150	30	450	60	200
WDH1-063	2-1/2"	63.5	76	10	150	30	450	60	200
WDH1-076	3"	76.2	89	10	150	30	450	60	200
WDH1-089	3-1/2"	88.9	103	10	150	30	450	60	200
WDH1-102	4"	101.6	116	10	150	30	450	60	200
WDH1-127	5"	127	142	10	150	30	450	30	100
WDH1-152	6"	152.4	167	10	150	30	450	30	100
WDH1-203	8"	203.2	219	10	150	30	450	30	100
WDH1-254	10"	254	274	10	150	30	450	12	40
WDH1-305	12"	304.8	322	10	150	30	450	12	40