

NITRILE PETROL SUCTION HOSE 150 PSI



Construction:

Tube: Black, smooth, Nitrile rubber

Reinforcement: Multi plies high strength synthetic fabric and steel wire helix skeleton

Cover: Black, wrapped surface, weather and ozone resistant, synthetic rubber

Application:

For suction and discharge of petroleum-based products, diesel, gasoline, lubricants, fuel, with aromatic content up to 50%.

Temperature:

-32°C (-90°F) to +82°C (+180°F)

Characteristics:

- Weather and abrasion resistant cover
- Both smooth and corrugated cover available
- Flexible and full vacuum
- For aromatic content up to 50%

Item Code	I.D		O.D	W.P		VACUUM	R		L	
	inch	mm	mm	bar	psi	bar	inch	mm	m	ft
OSDH019	3/4	19.1	31	10	150	0.8	6	152	61	200
OSDH025	1	25.4	37	10	150	0.8	6	152	61	200
OSDH032	1-1/4	31.8	44	10	150	0.8	8	200	61	200
OSDH038	1-1/2	38.1	51	10	150	0.8	9	230	61	200
OSDH050	2	50.8	64	10	150	0.8	10	254	61	200
OSDH064	2-1/2	63.5	76	10	150	0.8	15	380	61	200
OSDH076	3	76.2	91	10	150	0.8	18	460	61	200
OSDH089	3-1/2	88.9	107	10	150	0.8	22	550	61	200
OSDH100	4	101.6	120	10	150	0.8	24	610	61	200
OSDH125	5	127	147	10	150	0.8	30	760	30.6	100
OSDH150	6	152.4	172	10	150	0.8	36	916	30.5	100
OSDH200	8	203.2	229	10	150	0.8	48	1200	30.5	100
OSDH254	10	254	282	10	150	0.8	50	1250	11.8	39
OSDH300	12	304.8	329	10	150	0.8	60	1520	11.8	39