

# COM XRT 2.0



# COM XRT 2.0


The COM (common belt) series sorting equipment covers the range of applications which require a belt feeding system. The belt principle allows the presentation of a less uniform feed. The particles can stabilize on the belt before they are scanned by the sensor(s). Two sensor technologies are available, XRT and EM.

#### **TECHNOLOGY XRT**

X-ray transmission technology enables materials to be recognized and separated based on their specific atomic density. It is based on a planar projection of X-ray attenuation of single particles in a stream. This technology makes it possible to obtain a high separation performance in sorting materials irrespective of size, moisture, dust or dirt on a surface.

#### **TECHNOLOGY EM**

The optional EM sensor allows the discrimination of particles by permeability and conductivity properties. The highly sophisticated SUPPIXX® image processing technology enhances the resolution of the digitalized sensor signals. Thus it is possible to identify the finest conductive particles with great precision and subsequently separate them with a high degree of efficiency.



#### **BENEFITS**













## **STANDARD APPLICATIONS**

## **DIAMONDS (KIMBERLITE, ALLUVIAL)**Primary Diamond Concentration // XRT

## INDUSTRIAL MINERALS (E.G. PHOSPHATE, LIMESTONE, MAGNESITE, LITHIUM)

Waste rock reduction //
Transport, wear and process cost savings // XRT

### FERROUS METALS (E.G. CHROMITE, IRON ORE)

Lump ore production // Pre-concentration // Transport and process cost savings // XRT

## BASE METALS (E.G. TUNGSTEN, TIN, LEAD, ZINC, COPPER)

Pre-concentration // Increase productivity //
Reduced cash costs // Marginal resources turned into reserves // XRT // EM

#### **PRECIOUS METALS (E.G. GOLD)**

Pre-concentration // Increase productivity //
Reduced cash costs // Marginal resources turned into reserves // XRT // EM









TOMRA Sorting Solutions offers a variety of configurations for different tasks and conditions.

You are welcome to check your individual material in one of our test centers. E-mail: mining-sorting@tomra.com








#### **INSTALLATION EXAMPLE**


COM XRT 2.0

#### **COM XRT 1200 2.0**





#### **COM XRT 2400 2.0**





	COM XRT 1200 2.0
A	2600 mm
В	2400 mm
C	9850 mm

	COM XRT 2400 2.0
A	2900 mm
В	3650 mm
C	11900 mm

#### **PRODUCT SPECIFICATIONS**

	COM XRT 1200 2.0	COM XRT 2400 2.0
Size Range	10 - 125 mm	10 - 125 mm
Feed Rate	up to 250 t/h	up to 500 t/h
Size Ratio	1:3	1:3
Operational width	1,200	2,400
Sensors	X-ray sensor, High Resolution (HR) or High Sensitivity (HS)	X-ray sensor, High Resolution (HR) or High Sensitivity (HS)
Number of Ejectors	192 / 152	384 / 300
Nozzle Pitch	6,25 mm / 8 mm	6,25 mm / 8 mm
Electric Power	3 phase, approx. 18 kVA	3 phase, approx. 22 kVA
Weight (Sorter)	13600 kg	21400 kg
Weight (Feeder)	1750 kg	3700 kg

The capacity, performance and dimension data are indicative and may change without prior notice. Exact numbers on request.

### **PRODUCT RANGE**

#### **PRO SERIES (Chute based)**

Size range from 2 mm to 250 mm is covered by three models which can be equipped with COLOR, Near-Infrared (NIR), LASER and Electromagnetic (EM) technology or a combination thereof.

#### **COM SERIES (Belt based)**

High capacity sorting on a belt feeding system is key for this product series. Different models and widths are available which can be equipped with X-Ray Transmission (XRT), Electromagnetic (EM), COLOR and/or Near-Infrared (NIR) technology.

### **APPLICATIONS**

#### **XRT**

Diamonds // Industrial Minerals, e.g. Phosphate, Limestone // Base metals, e.g. Tungsten, Tin, Lead, Zinc // Precious metals, e.g. Gold // Ferrous metals, e.g. Iron Ore

#### **COLOR**

Industrial Minerals, e.g. Magnesite, Calcite, Talc, Quartz, Feldspar, Burnt lime

#### **LASER**

Industrial Minerals, e.g. Quartz, Fluorspar, Spodumene, Rock salt // Precious metals, e.g. Gold

Industrial Minerals, e.g. Talc, Borate, Calcite, Lithium // Kimberlite

Slag, e.g. Stainless steel, Base metal, Ferro silica, Ferro chrome, Silica // Massive nickel sulphides // Manganese

## **₹TOMRA**

WWW.TOMRA.COM/MINING

Europe/Russia/China TOMRA Sorting GmbH\* Feldstrasse 128 22880 Wedel/Hamburg Germany Phone: +49 4103 1888 0 Fax: +49 4103 1888 188 mining-sorting@tomra.com

Australasia TOMRA Sorting Pty Ltd Unit 1, 20 Anella Avenue Castle Hill NSW 2154 Australia Phone: +61 2 8624 0100 Fax: +61 2 8624 0101 mining-sorting@tomra.com

#### Southern Africa

TOMRA Sorting (Pty) Ltd 37 Angus Crescent Longmeadow Business Estate Edenvale 1609 South Africa Phone: +27 11 010 0300 Fax: +27 86 602 4646 mining-sorting@tomra.com

#### **North America**

TOMRA Sorting, Inc. 1536 Cole Blvd, Suite 225 Golden, Colorado 80401 USA Phone: +1 720 870 2240 Fax: +1 720 870 2241

mining-sorting@tomra.com

#### South America

TOMRA Brasil Soluções em Segregação LTA Rua Fernandes Moreira. 883-Chácara Santo Antonio 04716-002 São Paulo Brazil Phone: +55 11 3294 3400 mining-sorting@tomra.com



2021/