

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF OCTANE FITNESS. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF OCTANE FITNESS IS PROHIBITED.

REV DESCRIPTION ECH # DATE ENG

See Sheet1

SECTION E-E
SCALE 1:1.3

ALIGN SET SCREWS ON BOTH PILLOW BLOCK BEARINGS WITH FLATS ON DRIVE AXLE

NOTES:
1. MATERIAL:
2. FINISH:
3. REMOVE ALL BURRS AND SHARP EDGES.
4. OCTANE FITNESS ENGINEERING APPROVAL ON FIRST SAMPLE AND VENDOR INSPECTION REPORT REQUIRED PRIOR TO PRODUCTION FROM NEW OR REVISED TOOLING.
5. CAD GENERATED MODEL. ANY DIMENSIONS NOT ON THIS PRINT SHOULD BE EXTRACTED FROM THE CAD MODEL.
6. SUPPLIER MUST SUPPLY A DECLARATION OF COMPLIANCE WITH EUROPEAN COUNCIL DIRECTIVE 2011/65/EU ON THE RESTRICTION OF USE OF CERTAIN HAZARDOUS SUBSTANCES (RoHS).

UP TO 40 DEGREES COLD FLEX
TENSILE STRENGTH
100% ELONGATION
TOLERANCES ARE:
DIMENSIONS ANGLES
X ±0.6
XX ±0.5
XXX -0.100

PART DESCRIPTION
L1/8000 BASE 201 6

DATE 8/30/2021

111200-001

OCTANE FITNESS
Fuel Your Life

REV	DESCRIPTION	ECN #	DATE	ENG
-	See Sheet1	-	-	-

SAMPLE AND VENDOR ON FROM NEW OR REVISED IN THIS PRINT SHOULD BE IN ACCORDANCE WITH EUROPEAN STANDARD OF USE OF CERTAIN	(A) 700 000 000 000 000 000 700 000 000 000 000 000 700 000 000 000 000 000 TOUS BANCS ARE: DECMAL ANGLES: X 10.6 0.5 X 10.6 0.5 X 10.6 0.5 X 10.6 0.5	OCTANE FITNESS <i>Fast Your Life</i> PART DESCRIPTION LX8000 BASE 2016	111200-001	111200-001
111200-001	111200-001	111200-001	111200-001	111200-001