




THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF OCTANE FITNESS. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF OCTANE FITNESS IS PROHIBITED.

REV	DESCRIPTION	ECN #	DWG	ENG
-	See Sheet 2	-	-	-



DETAIL G
SCALE 1:2

ITEM NO.	PART NUMBER	DESCRIPTION	QTY
1	109199-001	ASSEMBLY, Z88000 FRAME	1
11	103393-001	NUT, HEX, NYLON INSERT, M8 X 1.25, CZ CLASS 10	6
21	108087-001	ASSY, CRANK ARM, RH	1
25	108081-001	SLEEVE, HARDENED, 35 mm	2
26	108089-001	SPACER, HUB	2
27	108090-001	WASHER, HUB	2
28	108091-001	RETAINER, HUB	2
29	110450-001	WASHER, CRINKLE SS	2
31	111003-001	SCREW, M8 X 1.25 X 25.0L SHCS, CLEAR ZINC, 12.9 STL	4
41	110423-001	ASSY, CRANK ARM, LH	1
48	110431-001	ASSEMBLY, RETURN SPRING	2
49	108338-001	SPACER, SPRING PIVOT	2
50	105338-001	O-RINGS, 13.8 X 2.4	2
51	104301-001	WASHER, M8, 8.3 X 20 X 2, BLACK ZINC	2
52	101715-001	BOLT, M8 X 1.25 X 35 HCS, 8.8 ST, BZ	2
53	103743-001	SCREW, M8 X 1.25 X 40 HHCS, 8.8 ST, CZ	8
58	109454-001	SCREW, M10 X 1.5 X 30.0L SHCS, 12.9 STL, NICKEL PLATED	4
59	110994-001	ASSY, UPPER LEG, STL, RH	1
60	110995-001	ASSY, UPPER LEG, STL, LH	1
61	111080-001	ASSY, LOWER LEG, RH	1
62	111081-001	ASSY, LOWER LEG, LH	1
63	108410-001	BOLT, M10 X 1.5 X 145, HEX HEAD, CLASS 8.8	2
64	109553-001	SPACER, IN-SET	2
71	108238-001	WELDMENT, KNEE CRANK, RH	1
72	108239-001	WELDMENT, KNEE CRANK, LH	1
73	110084-001	NUT, HEX, M42 X 1.5, THIN JAM	2
74	110085-001	WASHER, 42.3 X 52 X 1.5, STL, CZ	2
75	112382-001	ASSEMBLY, BELT CRANK	2
76	112376-001	ASSY, LWR LEG ARTICULATOR LINK	2
77	112379-001	ASSY, BRAKE ROD	2
78	109453-001	CAP, LL, ARIC	2
79	109720-001	WASHER, 32 X 16 X 3, CZ	2
80	104156-001	NUT, HEX, M16 X 2.0 X 8 CZ	2
87	111802-001	MOUNT, STRIDE SENSOR BOARD, INGP	2
88	103237-001	SCREW, M3 X 0.5 X 6, FLAT SHCS, STAINLESS STEEL	4
91	111798-001	BOARD ASSY, MAG SENSOR, DUAL SENS, DIFF OUTPUT	2
94	109884-001	COVER, KNEE PIVOT	2
111	111799-001	SCREW, M2.9 X 6.5L SELF-TAPPING, STAINLESS STEEL, TYPE C	6

NOTES:

- TORQUE FASTENER TO 45 N·M (33 FT-LBS)
- TORQUE FASTENER TO 30 N·M (22 FT-LBS)
- TORQUE FASTENER TO 23 N·M (17 FT-LBS)
- TORQUE FASTENER TO 0.7 N·M (6 IN-LBS)

5. OCTANE FITNESS ENGINEERING APPROVAL ON FIRST SAMPLE AND VENDOR INSPECTION REPORT REQUIRED PRIOR TO PRODUCTION FROM NEW OR REVISED TOOLING. SUPPLIER MUST SUPPLY A DECLARATION OF COMPLIANCE WITH EUROPEAN COUNCIL DIRECTIVE 2002/95/EC, ON THE RESTRICTION OF USE OF CERTAIN HAZARDOUS SUBSTANCES (RoHS).

OCTANE FITNESS Fuel Your Life	
PART DESCRIPTION	
DECIMALS	ANGLES
15	15.0
20	20.0
25	25.0
30	30.0
35	35.0
40	40.0
45	45.0
50	50.0
55	55.0
60	60.0
65	65.0
70	70.0
75	75.0
80	80.0
85	85.0
90	90.0
95	95.0
100	100.0
105	105.0
110	110.0
115	115.0
120	120.0
125	125.0
130	130.0
135	135.0
140	140.0
145	145.0
150	150.0

APPROVAL	DATE	REV	QTY	109200-001	REV
DATE	DATE	DATE	DATE	DATE	DATE