



CITY OF
REXBURG
America's Family Community

ORDINANCE NO. 1272
FLOOD DAMAGE PREVENTION ORDINANCE

AN ORDINANCE REPEALING AND REPLACING ORDINANCE 1129 TO UPDATE THE CITY'S FLOOD DAMAGE PREVENTION ORDINANCE TO MEET CURRENT STATE OF IDAHO AND FEMA REGULATIONS.

BE IT ORDAINED BY THE MAYOR AND COUNCIL OF THE CITY OF REXBURG, IDAHO:

ARTICLE I. STATUTORY AUTHORIZATION, FINDINGS OF FACT, PURPOSE, AND OBJECTIVES.

SECTION I-A. STATUTORY AUTHORITY.

The Legislature of the State of Idaho, pursuant to Idaho Code §§ 46-1020, 46-1023, and 46-1024, authorizes local governments to adopt floodplain management ordinances that identify floodplains and minimum floodplain development standards to minimize flood hazards and protect human life, health, and property. Therefore, the City Council of the City of Rexburg, Idaho, does hereby ordain as follows:

SECTION I-B. FINDINGS OF FACT.

1. The flood hazard areas of the City of Rexburg are subject to periodic inundation that results in:
 - a. loss of life and property;
 - b. health and safety hazards;
 - c. disruption of commerce and governmental services;
 - d. extraordinary public expenditures for flood relief and protection; and
 - e. impairment of the tax base, all of which adversely affect the public health, safety and general welfare.
2. These flood losses may be caused by development in flood hazard areas, which are inadequately elevated, flood-proofed, or otherwise unprotected from flood damages, and by the cumulative effect of obstructions in floodplains causing increases in flood heights and velocities.
3. Local government units have the primary responsibility for planning, adopting, and enforcing land use regulations to accomplish proper floodplain management.

SECTION I-C. STATEMENT OF PURPOSE.

It is the purpose of this ordinance to promote the public health, safety, and general welfare, and to minimize public and private losses due to flood conditions in specific areas by provisions designed to:

1. Protect human life, health, and property;
2. Minimize damage to public facilities and utilities such as water purification and sewage treatment plants, water and gas mains, electric, telephone and sewer lines, streets, and bridges located in floodplains;
3. Help maintain a stable tax base by providing for the sound use and development of flood prone areas;
4. Minimize expenditure of public money for costly flood control projects;
5. Minimize the need for rescue and emergency services associated with flooding, generally undertaken at the expense of the general public;
6. Minimize prolonged business interruptions;

7. Ensure potential buyers are notified that property is in an area of special flood hazard; and
8. Ensure those who occupy the areas of special flood hazard assume responsibility for their actions.

SECTION I-D. OBJECTIVES AND METHODS OF REDUCING FLOOD LOSSES.

In order to accomplish its purposes, this ordinance includes methods and provisions to:

1. Require that development which is vulnerable to floods, including structures and facilities necessary for the general health, safety, and welfare of citizens, be protected against flood damage at the time of initial construction;
2. Restrict or prohibit development which are dangerous to health, safety, and property due to water or erosion hazards, or which increase flood heights, velocities, or erosion;
3. Control filling, grading, dredging, and other development which may increase flood damage or erosion;
4. Prevent or regulate the construction of flood barriers which will unnaturally divert flood waters or that may increase flood hazards to other lands;
5. Preserve and restore natural floodplains, stream channels, and natural protective barriers which carry and store flood waters.

ARTICLE II. DEFINITIONS.

Unless specifically defined below, words or phrases used in this ordinance shall be interpreted according to the meaning they have in common usage and to give this ordinance its most reasonable application.

1. **ACCESSORY STRUCTURES** (appurtenant structure): a structure on the same lot or parcel as a principal structure, the use of which is incidental and subordinate to the principal structure.
2. **ADDITION** (to an existing building): an extension or increase in the floor area or height of a building or structure.
3. **AGRICULTURAL STRUCTURES** (appurtenant structure): a structure which is used exclusively in connection with the production, harvesting, storage, raising, or drying of agricultural commodities and livestock; specifically excludes any structures used for human habitation.
4. **APPEAL**: a request for review of the Floodplain Administrator's interpretation of provisions of this ordinance or request for a variance.
5. **AREA OF SPECIAL FLOOD HAZARD**: see Special Flood Hazard Area (SFHA).
6. **BASE FLOOD**: the flood having a one percent (1%) chance of being equaled or exceeded in any given year.
7. **BASE FLOOD ELEVATION (BFE)**: a determination by the Federal Insurance Administrator of the water surface elevations of the base flood, that is, the flood level that has a one percent or greater chance of occurrence in any given year. When the BFE has not been provided in a Special Flood Hazard Area, it may be obtained from engineering studies available from a Federal, State, or other source using FEMA-approved engineering methodologies. This elevation, when combined with the Freeboard, establishes the Flood Protection Elevation.
8. **BASEMENT**: any area of the building having its floor sub grade (below ground level) on all sides.
9. **BUILDING**: see Structure.
10. **CRITICAL FACILITIES**: facilities that are vital to flood response activities or critical to the health and safety of the public before, during, and after a flood, such as a hospital, emergency operations center, electric substation, police station, fire station, nursing home, school, vehicle and equipment storage facility, or shelter; and facilities that, if flooded, would make the flood problem and its impacts much worse, such as a hazardous materials facility, power generation facility, water utility, or wastewater treatment plant.

11. **DATUM:** the vertical datum is a base measurement point (or set of points) from which all elevations are determined. Historically, that common set of points was the National Geodetic Vertical Datum of 1929 (NGVD29). The vertical datum currently adopted by the federal government as a basis for measuring heights is the North American Vertical Datum of 1988 (NAVD88).
12. **DEVELOPMENT:** any man-made change to improved or unimproved real estate, including but not limited to buildings or other structures, mining, dredging, filling, grading, paving, excavation or drilling operations, or storage of equipment and materials.
13. **DEVELOPMENT ACTIVITY:** any activity defined as Development which will necessitate a Floodplain Development Permit; such as: the construction of buildings, structures, or accessory structures; additions or substantial improvements to existing structures; bulkheads, retaining walls, piers, and pools; the placement of mobile homes; or the deposition or extraction of materials; the construction or elevation of dikes, berms and levees.
14. **ELEVATED BUILDING:** for insurance purposes, a non-basement building which has its lowest elevated floor raised above ground level by foundation walls, shear walls, posts, piers, pilings, or columns.
15. **ELEVATION CERTIFICATE:** The Elevation Certificate is an important administrative tool of the NFIP. It is used to determine the proper flood insurance premium rate; it is used to document elevation information; and it may be used to support a request for a Letter of Map Amendment (LOMA) or Letter of Map Revision based on fill (LOMR-F).
16. **ENCLOSURE:** an area enclosed by solid walls below the BFE/FPE or an area formed when any space below the BFE/FPE is enclosed on all sides by walls or partitions. Insect screening or open wood lattice used to surround space below the BFE/RFPE is not considered an enclosure.
17. **ENCROACHMENT:** the advance or infringement of uses, fill, excavation, buildings, structures, or development into a floodplain, which may impede or alter the flow capacity of a floodplain.
18. **EXISTING CONSTRUCTION:** for the purposes of determining rates, structures for which the "start of construction" commenced before the effective date of the FIRM. "Existing construction" may also be referred to as "existing structures."
19. **EXISTING MANUFACTURED HOME PARK OR MANUFACTURED HOME SUBDIVISION:** a manufactured home park or subdivision where the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including, at a minimum, the installation of utilities, the construction of streets, and final site grading or the pouring of concrete pads) is completed before the effective date of the original floodplain management regulations adopted by the community, Ordinance 717 adopted on April 17, 1991.
20. **EXISTING STRUCTURES:** see existing construction.
21. **EXPANSION TO AN EXISTING MANUFACTURED HOME PARK OR SUBDIVISION:** the preparation of additional sites by the construction of facilities for servicing the lots on which the manufactured homes are to be affixed (including the installation of utilities, the construction of streets, and either final site grading or the pouring of concrete pads).
22. **FLOOD or FLOODING:**
 - a. A general and temporary condition of partial or complete inundation of normally dry land areas from:
 - i. The overflow of inland or tidal waters.
 - ii. The unusual and rapid accumulation or runoff of surface waters from any source.
 - iii. Mudslides (i.e., mudflows) which are proximately caused by flooding as defined in paragraph a.ii of this definition and are akin to a river of liquid and flowing mud on the surfaces of normally dry land areas, as when earth is carried by a current of water and deposited along the path of the current.

- b. The collapse or subsidence of land along the shore of a lake or other body of water as a result of erosion or undermining caused by waves or currents of water exceeding anticipated cyclical levels or suddenly caused by an unusually high water level in a natural body of water, accompanied by a severe storm, or by an unanticipated force of nature, such as flash flood or an abnormal tidal surge, or by some similarly unusual and unforeseeable event which results in flooding as defined in paragraph a.i of this definition.
- 23. FLOOD ELEVATION DETERMINATION: See Base Flood Elevation (BFE).
 - 24. FLOOD ELEVATION STUDY: See Flood Insurance Study (FIS).
 - 25. FLOOD INSURANCE RATE MAP (FIRM): an official map of a community, on which the Federal Insurance Administrator has delineated both the special flood hazard areas and the risk premium zones applicable to the community.
 - 26. FLOOD INSURANCE STUDY (FIS): an examination, evaluation, and determination of flood hazards and, if appropriate, corresponding water surface elevations; or an examination, evaluation and determination of mudslide (i.e., mudflow) and/or flood-related erosion hazards.
 - 27. FLOOD ZONE: a geographical area shown on a Flood Hazard Boundary Map (FHBM) or Flood Insurance Rate Map (FIRM) that reflects the severity or type of flooding in the area, and applicable insurance rate.
 - 28. FLOODPLAIN OR FLOOD-PRONE AREA: any land area susceptible to being inundated by water from any source (see definition of "flooding").
 - 29. FLOODPLAIN ADMINISTRATOR: the individual appointed to administer and enforce the floodplain management regulations.
 - 30. FLOODPLAIN DEVELOPMENT PERMIT: any type of permit that is required in conformance with the provisions of this ordinance, prior to the commencement of any development activity.
 - 31. FLOODPLAIN MANAGEMENT: the operation of an overall program of corrective and preventive measures for reducing flood damage, including but not limited to emergency preparedness plans, flood control works, and flood plain management regulations.
 - 32. FLOODPLAIN MANAGEMENT REGULATIONS: zoning ordinances, subdivision regulations, building codes, health regulations, special purpose ordinances (such as a flood plain ordinance, grading ordinance, and erosion control ordinance), and other applications of police power. The term describes such state or local regulations, in any combination thereof, which provide standards for the purpose of flood damage prevention and reduction.
 - 33. FLOODPROOFING: any combination of structural and non-structural additions, changes, or adjustments to structures which reduce or eliminate flood damage to real estate or improved real property, water and sanitary facilities, structures and their contents.
 - 34. FLOOD PROTECTION ELEVATION (FPE): the Base Flood Elevation plus the Freeboard.
 - a. In "Special Flood Hazard Areas" where Base Flood Elevations (BFEs) have been determined, this elevation shall be the BFE plus 1 foot of freeboard for new structures; and
 - b. In "Special Flood Hazard Areas" where no BFE has been established, this elevation shall be at least 2 feet above the highest adjacent grade.
 - 35. FLOOD PROTECTION SYSTEM: those physical structural works for which funds have been authorized, appropriated, and expended and which have been constructed specifically to modify flooding in order to reduce the extent of the area within a community subject to a "special flood hazard" and the extent of the depths of associated flooding. Such a system typically includes dams, reservoirs, levees, or dikes. These specialized flood modifying works are those constructed in conformance with sound engineering standards.

36. **FLOODWAY:** the channel of a river or other watercourse and the adjacent land areas that must be reserved in order to discharge the base flood without cumulatively increasing the water surface elevation more than a designated height.
37. **FREEBOARD:** a factor of safety usually expressed in feet above a flood level for the purposes of floodplain management. Freeboard tends to compensate for the many unknown factors that could contribute to flood heights greater than the height calculated for a selected size flood and floodway conditions, such as wave action, obstructed bridge openings, debris and ice jams, and the hydrologic effects of urbanization in a watershed. The Base Flood Elevation (BFE) plus the freeboard establishes the Flood Protection Elevation (FPE). Freeboard shall be a minimum of one (1) foot for new structures. Modifications to existing structures that meet the definition of Substantial Improvements do not require freeboard if the Lowest Floor is already at or above the Base Flood Elevation.
38. **FUNCTIONALLY DEPENDENT USE:** a facility that cannot be used for its intended purpose unless it is located or carried out in close proximity to water, such as a docking or port facility necessary for the loading and unloading of cargo or passengers, shipbuilding, or ship repair facilities. The term does not include long-term storage, manufacture, sales, or service facilities.
39. **HIGHEST ADJACENT GRADE (HAG):** the highest natural elevation of the ground surface prior to construction, adjacent to the proposed walls of a structure. Refer to the FEMA Elevation Certificate for HAG related to building elevation information.
40. **HISTORIC STRUCTURE:** a structure that is:
- Listed individually in the National Register of Historic Places (a listing maintained by the U.S. Department of Interior) or preliminarily determined by the Secretary of the Interior as meeting the requirements for individual listing on the National Register;
 - Certified or preliminarily determined by the Secretary of the Interior as contributing to the historical significance of a registered historic district or to a district preliminarily determined by the Secretary to qualify as a registered historic district;
 - Individually listed on a state inventory of historic places and determined as eligible by states with historic preservation programs which have been approved by the Secretary of the Interior; or
 - Individually listed on a local inventory of historic places and determined as eligible by communities with historic preservation programs that have been certified either:
 - by an approved state program as determined by the Secretary of the Interior, or
 - directly by the Secretary of the Interior in states without approved programs.
41. **LETTER OF MAP CHANGE (LOMC):** a general term used to refer to the several types of revisions and amendments to FIRMs that can be accomplished by letter. They include Letter of Map Amendment (LOMA), Letter of Map Revision (LOMR), and Letter of Map Revision based on Fill (LOMR-F)
- LETTER OF MAP AMENDMENT (LOMA):** an official amendment, by letter, to an effective National Flood Insurance Program (NFIP) map. A LOMA establishes a property's or structure's location in relation to the Special Flood Hazard Area (SFHA). LOMAs are usually issued because a property or structure has been inadvertently mapped as being in the floodplain but is actually on natural high ground above the base flood elevation.
 - LETTER OF MAP REVISION (LOMR):** FEMA's modification to an effective Flood Insurance Rate Map (FIRM) or a Flood Boundary and Floodway Map (FBFM) or both. LOMRs are generally based on the implementation of physical measures that affect the hydrologic or hydraulic characteristics of a flooding source and thus result in the modification of the existing regulatory floodway, the effective Base Flood Elevations (BFEs), or the Special Flood Hazard Area (SFHA). The LOMR officially revises the Flood Insurance Rate Map (FIRM) or Flood Boundary and Floodway Map (FBFM), and sometimes the Flood Insurance Study (FIS) report, and when appropriate, includes a description of the modifications. The LOMR is generally accompanied by an annotated copy of the affected portions of the FIRM, FBFM, or FIS report.

- c. **LETTER OF MAP REVISION BASED ON FILL (LOMR-F):** FEMA's modification of the Special Flood Hazard Area (SFHA) shown on the Flood Insurance Rate Map (FIRM) based on the placement of fill outside the existing regulatory floodway. The LOMR-F does not change the FIRM, FBFM, or FIS report.
 - d. **CONDITIONAL LETTER OF MAP REVISION (CLOMR):** A formal review and comment as to whether a proposed flood protection project or other project complies with the minimum NFIP requirements for such projects with respect to delineation of special flood hazard areas. A CLOMR does not revise the effective Flood Insurance Rate Map (FIRM) or Flood Insurance Study (FIS). Upon submission and approval of certified as-built documentation, a Letter of Map Revision (LOMR) may be issued by FEMA to revise the effective FIRM. Building Permits and/or Flood Development Permits cannot be issued based on a CLOMR, because a CLOMR does not change the NFIP map.
- 42. **LEVEE:** a man-made structure, usually an earthen embankment, designed and constructed according to sound engineering practices, to contain, control, or divert the flow of water so as to provide protection from temporary flooding.
 - 43. **LEVEE SYSTEM:** a flood protection system that consists of a levee, or levees, and associated structures, such as closure and drainage devices, which are constructed and operated in accordance with sound engineering practices.
 - 44. **LOWEST ADJACENT GRADE (LAG):** the lowest point of the ground level next to the structure. Refer to the FEMA Elevation Certificate for LAG related to building elevation information.
 - 45. **LOWEST FLOOR:** the lowest floor of the lowest enclosed area (including basement). An unfinished or flood resistant enclosure, usable solely for parking of vehicles, building access or storage in an area other than a basement area is not considered a building's lowest floor; provided, that such enclosure is not built so as to render the structure in violation of the applicable non-elevation design requirements of 44 CFR § 60.3 and this ordinance.
 - 46. **MANUFACTURED HOME:** a structure, transportable in one or more sections, built on a permanent chassis and designed to be used with or without a permanent foundation when connected to the required utilities. The term "Manufactured Home" does not include a "Recreational Vehicle."
 - 47. **MANUFACTURED HOME PARK OR SUBDIVISION:** a parcel (or contiguous parcels) of land divided into two or more manufactured home lots for rent or sale.
 - 48. **MARKET VALUE:** the building value, not including the land value and that of any accessory structures or other improvements on the lot. Market value may be established by independent certified appraisal; replacement cost depreciated for age of building and quality of construction (Actual Cash Value); or adjusted tax assessed values.
 - 49. **MEAN SEA LEVEL:** for purposes of the National Flood Insurance Program (NFIP), the National Geodetic Vertical Datum (NGVD) of 1929 or other datum (such as North America Vertical Datum of 1988 - NAVD88) to which Base Flood Elevations (BFEs) shown on a community's FIRM are referenced.
 - 50. **NATIONAL FLOOD INSURANCE PROGRAM (NFIP):** The NFIP is a Federal program created by Congress to mitigate future flood losses nationwide through sound, community-enforced building and zoning ordinances and to provide access to affordable, federally backed flood insurance protection for property owners.
 - 51. **NEW CONSTRUCTION:** for floodplain management purposes, a structure for which the start of construction commenced on or after the effective date of a floodplain management regulation adopted by a community and includes any subsequent improvements to such structures. Any construction started after June 3, 1991 and before the effective start date of this floodplain management ordinance is subject to the ordinance in effect at the time the permit was issued, provided the start of construction was within 180 days of permit issuance.
 - 52. **NEW MANUFACTURED HOME PARK OR SUBDIVISION:** a place where the construction of facilities for servicing the lots on which the manufactured homes are to

- be affixed (including at a minimum the installation of utilities, the construction of streets, and final site grading or the pouring of concrete pads) is completed on or after June 3, 1991, the effective date of the initial Flood Insurance Rate Map (FIRM).
53. POST-FIRM: construction or other development for which the "start of construction" occurred on or after the effective date of the initial Flood Insurance Rate Map (FIRM).
54. PRE-FIRM: construction or other development for which the "start of construction" occurred before June 3, 1991, the effective date of the initial Flood Insurance Rate Map (FIRM).
55. RECREATIONAL VEHICLE: a vehicle that is:
- Built on a single chassis, and
 - 400 square feet or less when measured at the largest horizontal projection, and
 - Designed to be self-propelled or permanently towed by a light duty truck, and
 - Designed primarily not for use as a permanent dwelling but as temporary living quarters for recreational, camping, travel, or seasonal use.
56. REGULATORY FLOODWAY: See Floodway.
57. REMEDY A VIOLATION: to bring the structure or other development into compliance with State or local flood plain management regulations, or, if this is not possible, to reduce the impacts of its non-compliance. Ways that impacts may be reduced include protecting the structure or other affected development from flood damages, implementing the enforcement provisions of the ordinance or otherwise deterring future similar violations, or reducing Federal financial exposure with regard to the structure or other development.
58. REPETITIVE LOSS STRUCTURE: An NFIP-insured structure that has had at least two paid flood losses of more than \$1,000 each in any 10-year period since 1978.
59. RIVERINE: relating to, formed by, or resembling a river (including tributaries), stream, brook, etc.
60. SPECIAL FLOOD HAZARD AREA (SFHA): the land in the flood plain within a community subject to a one percent (1%) or greater chance of flooding in any given year. For purposes of these regulations, the term "special flood hazard area" is synonymous in meaning with the phrase "area of special flood hazard".
61. START OF CONSTRUCTION: includes substantial improvement, and means the date the building permit was issued, provided the actual start of construction, repair, reconstruction, rehabilitation, addition placement, or other improvement was within 180 days of the permit date. The actual start means either the first placement of permanent construction of a structure on a site, such as the pouring of slab or footings, the installation of piles, the construction of columns, or any work beyond the stage of excavation; or the placement of a manufactured home on a foundation. Permanent construction does not include land preparation, such as clearing, grading and filling; nor does it include the installation of streets and/or walkways; nor does it include excavation for a basement, footings, piers, or foundation or the erection of temporary forms; nor does it include the installation on the property of accessory buildings, such as garages or sheds not occupied as dwelling units or not part of the main structure. For a substantial improvement, the actual start of construction means the first alteration of any wall, ceiling, floor, or other structural part of a building, whether or not that alteration affects the external dimensions of the building.
62. STRUCTURE: a walled and roofed building, including a gas or liquid storage tank that is principally above ground, as well as a manufactured home.
63. SUBSTANTIAL DAMAGE: damage of any origin sustained by a structure whereby the cost of restoring the structure to its before-damaged condition would equal or exceed 50 percent (50%) of its market value before the damage occurred. See definition of "substantial improvement".
64. SUBSTANTIAL IMPROVEMENT: any reconstruction, rehabilitation, addition, or other improvement of a structure, the cost of which equals or exceeds 50 percent (50%) of the market value of the structure before the "start of construction" of the

improvement. This term includes structures which have incurred "substantial damage", regardless of the actual repair work performed. The term does not, however, include either:

- a. Any project for improvement of a structure to correct existing violations of state or local health, sanitary, or safety code specifications which have been identified by the local code enforcement official and which are the minimum necessary to assure safe living conditions, or
 - b. Any alteration of a "historic structure", provided that the alteration will not preclude the structure's continued designation as a "historic structure" and the alteration is approved by variance issued pursuant to this ordinance.
65. **TECHNICAL BULLETINS AND TECHNICAL FACT SHEETS:** FEMA publications that provide guidance concerning the building performance standards of the NFIP, which are contained in Title 44 of the U S Code of Federal Regulations § 60.3. The bulletins and fact sheets are intended for use primarily by State and local officials responsible for interpreting and enforcing NFIP regulations and by members of the development community, such as design professionals and builders. New bulletins, as well as updates of existing bulletins, are issued periodically as needed. The bulletins do not create regulations. Rather they provide specific guidance for complying with the minimum requirements of existing NFIP regulations.
66. **TEMPERATURE CONTROLLED:** having the temperature regulated by a heating and/or cooling system, built-in or appliance.
67. **VARIANCE:** a grant of relief from the governing body from a requirement of this ordinance.
68. **VIOLATION:** the failure of a structure or other development to be fully compliant with the community's flood plain management regulations. A structure or other development without the Finished Construction Elevation Certificate, other certifications, or other evidence of compliance required in 44 CFR § 60.3(b)(5), (c)(4), (c)(10), (d)(3), (e)(2), (e)(4), or (e)(5) is presumed to be in violation until such time as that documentation is provided.
69. **WATER SURFACE ELEVATION:** the height, in relation to the National Geodetic Vertical Datum (NGVD) of 1929 or the North American Vertical Datum (NAVD) of 1988 (or other specified datum), of floods of various magnitudes and frequencies in the flood plains of coastal or riverine areas.
70. **WATERCOURSE:** a lake, river, creek, stream, wash, channel, or other topographic feature on or over which waters flow at least periodically. Watercourse includes specifically designated areas in which substantial flood damage may occur.

ARTICLE III. GENERAL PROVISIONS.

SECTION III-A. LANDS TO WHICH THIS ORDINANCE APPLIES.

This ordinance shall apply to all Special Flood Hazard Areas within the jurisdiction of the City of Rexburg. Nothing in this ordinance is intended to allow uses or structures that are otherwise prohibited by the zoning ordinance.

SECTION III-B. BASIS FOR SPECIAL FLOOD HAZARD AREAS.

The Special Flood Hazard Areas identified by the Federal Insurance Administrator in a scientific and engineering report titled "Flood Insurance Study (FIS) for Madison County, Idaho and Incorporated Areas," dated June 3, 1991, with accompanying Flood Insurance Rate Maps (FIRM), and other supporting data, are adopted by reference and declared a part of this ordinance. The FIS and the FIRM are on file at the office of the City Clerk at 35 North 1st East, Rexburg, Idaho 83440.

SECTION III-C. ESTABLISHMENT OF FLOODPLAIN DEVELOPMENT PERMIT

A Floodplain Development Permit shall be required in conformance with the provisions of this ordinance prior to the commencement of any development activities within Special Flood Hazard Areas determined in accordance with the provisions of Section IV-B.

SECTION III-D. COMPLIANCE.

No structure or land shall hereafter be located, extended, converted, altered, or developed in any way without full compliance with the terms of this ordinance and other applicable regulations.

SECTION III-E. ABROGATION AND GREATER RESTRICTIONS.

This ordinance shall not in any way repeal, abrogate, impair, or remove the necessity of compliance with any other laws, ordinances, regulations, easements, covenants, or deed restrictions, etcetera. However, where this ordinance and another conflict or overlap, whichever imposes more stringent or greater restrictions shall control.

SECTION III-F. INTERPRETATION.

In the interpretation and application of this ordinance all provisions shall be:

1. Considered as minimum requirements;
2. Liberally construed in favor of the governing body; and
3. Deemed neither to limit nor repeal any other powers granted under State Statutes.

SECTION III-G. WARNING AND DISCLAIMER OF LIABILITY.

The degree of flood protection required by this ordinance is considered reasonable for regulatory purposes and is based on scientific and engineering considerations. Larger floods can and will occur. Flood heights may be increased by man-made or natural causes. This ordinance does not imply that land outside the Special Flood Hazards Areas or uses permitted within such areas will be free from flooding or flood damages. This ordinance shall not create liability on the part of the City of Rexburg or by any officer or employee thereof for flood damages that result from reliance on this ordinance or an administrative decision lawfully made hereunder.

SECTION III-H. PENALTIES FOR VIOLATION.

No structure or land shall hereafter be located, extended, converted, or altered unless in full compliance with the terms of this ordinance and other applicable regulations. Violation of the provisions of this ordinance or failure to comply with any of its requirements, including violation of conditions and safeguards established in connection with grants of variance or special exceptions, shall constitute a misdemeanor. Any person who violates this ordinance or fails to comply with any of its requirements shall, upon conviction thereof, be fined not more than \$300 or imprisoned for not more than 180 days, or both. Nothing herein contained shall prevent the City of Rexburg from taking such other lawful actions as is necessary to prevent or remedy any violation.

ARTICLE IV. ADMINISTRATION.

SECTION IV-A. DESIGNATION OF FLOODPLAIN ORDINANCE ADMINISTRATOR.

The Mayor will appoint a staff member to act as the "Floodplain Administrator", to administer and implement the provisions of this ordinance. If a Floodplain Administrator has not been appointed by the Mayor or if the appointed person is no longer able to perform these duties, the ordinance will be administered and implemented by the City Building Official, until a new Floodplain Administrator is appointed.

SECTION IV-B. DUTIES AND RESPONSIBILITIES OF THE FLOODPLAIN ADMINISTRATOR.

The Floodplain Administrator shall perform, but not be limited to, the following duties:

1. Review all floodplain development applications and issue permits for all proposed development within Special Flood Hazard Areas to assure that the requirements of this ordinance have been satisfied and all proposed development is reasonably safe from flooding.
2. Review all proposed development within Special Flood Hazard Areas to assure that all necessary Local, State, and Federal permits have been received, including Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 USC 1334.

3. Notify adjacent communities and the Idaho Department of Water Resources State Coordinator for the National Flood Insurance Program (NFIP) prior to any alteration or relocation of a watercourse and submit evidence of such notification to the Federal Insurance Administrator (FIA).
4. Assure that the flood carrying capacity within the altered or relocated portion of any watercourse is maintained;
5. Obtain and maintain actual elevation (in relation to mean sea level) of the lowest floor (including basement) and all attendant utilities of all new and substantially improved structures, in accordance with the provisions of Section IV-C.3.
6. Obtain and maintain actual elevation (in relation to mean sea level) to which all new and substantially improved structures and utilities have been floodproofed, in accordance with the provisions of Section IV-C.3.
7. Review plans to verify public utilities are constructed in accordance with the provisions of Sections V-A.5 to .7.
8. When floodproofing is utilized for a particular structure, obtain and maintain certifications from a registered professional engineer or architect in accordance with the provisions of Section IV-C.3 and Section V-B.2.
9. Where interpretation is needed as to the exact location of boundaries of the Special Flood Hazard Areas, and floodways (for example, where there appears to be a conflict between a mapped boundary and actual field conditions), make the necessary interpretation. The person contesting the location of the boundary shall be given a reasonable opportunity to appeal the interpretation as provided in this article.
10. Permanently maintain all records that pertain to the administration of this ordinance and make these records available for public inspection, recognizing that such information may be subject to the Privacy Act of 1974, as amended.
11. Make on-site inspections of work in progress. As the work pursuant to a floodplain development permit progresses, the Floodplain Administrator shall make as many inspections of the work as may be necessary to ensure that the work is being done according to the provisions of the local ordinance and the terms of the permit. In exercising this power, the Floodplain Administrator has a right, upon presentation of proper credentials, to enter on any premises within the jurisdiction of the community at any reasonable hour for the purposes of inspection or other enforcement action.
12. Issue stop-work orders as required. Whenever a building or part thereof is being constructed, reconstructed, altered, or repaired in violation of this ordinance, the Floodplain Administrator may order the work to be immediately stopped. The stop-work order shall be in writing and directed to the person doing or in charge of the work. The stop-work order shall state the specific work to be stopped, the specific reason(s) for the stoppage, and the condition(s) under which the work may be resumed. Violation of a stop-work order constitutes a misdemeanor.
13. Revoke floodplain development permits as required. The Floodplain Administrator may revoke and require the return of the floodplain development permit by notifying the permit holder in writing stating the reason(s) for the revocation. Permits shall be revoked for any substantial departure from the approved application, plans, and specifications; for refusal or failure to comply with the requirements of State or local laws; or for false statements or misrepresentations made in securing the permit. Any floodplain development permit mistakenly issued in violation of an applicable State or local law may also be revoked.
14. Make periodic inspections throughout the Special Flood Hazard Areas within the jurisdiction of the community. The Floodplain Administrator and each member of his or her inspections department shall have a right, upon presentation of proper credentials, to enter on any premises within the territorial jurisdiction of the department at any reasonable hour for the purposes of inspection or other enforcement action.
15. Follow through with corrective procedures of Section IV-D.
16. Review, provide input, and make recommendations for variance requests.

17. Maintain a current map repository to include, but not limited to, the FIS Report, FIRM and other official flood maps, and studies adopted in accordance with the provisions of Section III-B of this ordinance, including any revisions thereto including Letters of Map Change, issued by FEMA. Notify the NFIP State Coordinator and FEMA of your community's mapping needs.
18. Coordinate revisions to FIS reports and FIRMs, including Letters of Map Revision Based on Fill (LOMR-Fs) and Letters of Map Revision (LOMRs).
19. A community's base flood elevations may increase or decrease resulting from physical changes affecting flooding conditions. As soon as practicable, but not later than six months after the date such information becomes available, a community shall notify the Federal Insurance Administrator (FIA) of the changes by submitting technical or scientific data in accordance with this part. Such a submission is necessary so that upon confirmation of those physical changes affecting flooding conditions, risk premium rates and flood plain management requirements will be based upon current data.
20. Upon occurrence, notify the Federal Insurance Administrator (FIA) in writing whenever the boundaries of the community have been modified by annexation or the community has otherwise assumed or no longer has authority to adopt and enforce flood plain management regulations for a particular area. In order that all FHBMs and FIRM's accurately represent the community's boundaries, include within such notification a copy of a map of the community suitable for reproduction, clearly delineating the new corporate limits or new area for which the community has assumed or relinquished flood plain management regulatory authority.

SECTION IV-C. FLOODPLAIN DEVELOPMENT APPLICATION, PERMIT, AND CERTIFICATION REQUIREMENTS

1. Application Requirements. Application for a Floodplain Development Permit shall be made to the Floodplain Administrator prior to any development activities located within Special Flood Hazard Areas. The following items shall be presented to the Floodplain Administrator to apply for a floodplain development permit:
 - a. A plot plan drawn to scale which shall include, but shall not be limited to, the following specific details of the proposed floodplain development:
 - i. the nature, location, dimensions, and elevations of the area of development/disturbance; existing and proposed structures, utility systems, grading/pavement areas, fill materials, storage areas, drainage facilities, and other development;
 - ii. the boundary of the Special Flood Hazard Area as delineated on the FIRM or other flood map as determined in Section III-B, or a statement that the entire lot is within the Special Flood Hazard Area;
 - iii. the flood zone(s) designation of the proposed development area as determined on the FIRM or other flood map as determined in Section III-B;
 - iv. the boundary of the floodway(s) as determined in Section III-B;
 - v. the Base Flood Elevation (BFE) where provided as set forth in Section III-B; Section III-C; or Section V-C; and
 - vi. the old and new location of any watercourse that will be altered or relocated as a result of proposed development.
 - b. Proposed elevation, and method thereof, of all development within a Special Flood Hazard Area including but not limited to:
 - i. Elevation in a relation to mean sea level of the proposed lowest floor (including basement) of all structures;
 - ii. Elevation in relation to mean sea level to which any non-residential structure in Zone AE will be floodproofed; and
 - iii. Elevation in relation to mean sea level to which any proposed utility equipment and machinery will be elevated or floodproofed.

- c. If floodproofing, a Floodproofing Certificate (FEMA Form 086-0-33) with supporting data, an operational plan, and an inspection and maintenance plan that include, but are not limited to, installation, exercise, and maintenance of floodproofing measures will be required prior to Certificate of Occupancy/Completion.
 - d. A Foundation Plan, drawn to scale, which shall include details of the proposed foundation system to ensure all provisions of this ordinance are met. These details include but are not limited to:
 - i. The proposed method of elevation, if applicable (i.e., fill, solid foundation perimeter wall, solid backfilled foundation, open foundation, or on columns/posts/piers/piles/shear walls); and
 - ii. Openings to facilitate automatic equalization of hydrostatic flood forces on walls in accordance with Section V-A.8.b. when solid foundation perimeter walls are used in Zones AE.
 - e. Usage details of any enclosed areas below the lowest floor.
 - f. Plans and/or details for the protection of public utilities and facilities such as sewer, gas, electrical, and water systems to be located and constructed to minimize flood damage.
 - g. Certification that all other Local, State, and Federal permits required prior to floodplain development permit issuance have been received.
 - h. Documentation for placement of recreational vehicles and/or temporary structures, when applicable, to ensure that the provisions of Sections V-B.5 to .6 of this ordinance are met.
 - i. A description of proposed watercourse alteration or relocation, when applicable, including an engineering report on the effects of the proposed project on the flood-carrying capacity of the watercourse and the effects to properties located both upstream and downstream; and
 - j. A map (if not shown on plot plan) showing the location of the proposed watercourse alteration or relocation.
2. Permit Requirements. The Floodplain Development Permit shall include, but not be limited to:
- a. A complete description of all the development to be permitted under the floodplain development permit (i.e. house, garage, pool, septic, bulkhead, cabana, pole barn, chicken coop, pier, bridge, mining, dredging, filling, rip-rap, docks, grading, paving, excavation or drilling operations, or storage of equipment or materials, etcetera).
 - b. The Special Flood Hazard Area determination for the proposed development in accordance with available data specified in Section III-B.
 - c. The Flood Protection Elevation required for the lowest floor and all attendant utilities.
 - d. The Flood Protection Elevation required for the protection of all utility equipment and machinery.
 - e. All certification submittal requirements with timelines.
 - f. The flood openings requirements, if in Zones AE.
 - g. All floodplain development permits shall be conditional upon the start of construction of work within 180 days. A floodplain development permit shall expire 180 days after issuance unless the permitted activity has commenced as per the Start of Construction definition.
 - h. Fully enclosed areas below the lowest floor are usable solely for parking of vehicles, building access, or storage.
 - i. All materials below BFE/FPE must be flood resistant materials.
3. Certification Requirements.

- a. Elevation Certificates
 - i. A Construction Drawings Elevation Certificate (FEMA Form 86-0-33) is RECOMMENDED prior to the actual start of any new construction.
 - ii. A Building Under Construction Elevation Certificate (FEMA Form 86-0-33) is RECOMMENDED after the lowest floor is established.
 - iii. A final as-built Finished Construction Elevation Certificate (FEMA Form 86-0-33) is REQUIRED after construction is completed and prior to Certificate of Compliance/Occupancy issuance. It shall be the duty of the permit holder to submit to the Floodplain Administrator a certification of final as-built construction of the elevation of the lowest floor and all attendant utilities. The Floodplain Administrator shall review the certificate data submitted. Deficiencies detected by such review shall be corrected by the permit holder immediately and prior to Certificate of Compliance/Occupancy issuance. In some instances, another certification may be required to certify corrected as-built construction. Failure to submit the certification or failure to make required corrections shall be cause to withhold the issuance of a Certificate of Compliance/Occupancy.
 - b. Floodproofing Certificate. If non-residential floodproofing is used to meet the Flood Protection Elevation requirements, design plans, with supporting data, an operational plan, and an inspection and maintenance plan are required prior to the actual start of any new construction. It shall be the duty of the permit holder to submit to the Floodplain Administrator a certification of the floodproofed design elevation of the lowest floor and all attendant utilities, in relation to mean sea level. Floodproofing certification shall be prepared by or under the direct supervision of a professional engineer or architect and certified by same. The Floodplain Administrator shall review the certificate data, the operational plan, and the inspection and maintenance plan. Deficiencies detected by such review shall be corrected by the applicant prior to permit approval. Failure to submit the certification or failure to make required corrections shall be cause to deny a Floodplain Development Permit. Prior to request for a Certificate of Compliance/Occupancy a Floodproofing Certificate (FEMA Form 086-0-34) shall be provided to the Floodplain Administrator for review and approval.
 - c. If a manufactured home is placed within Zone AE and the elevation of the chassis is more than 36 inches in height above grade, an engineered foundation certification is required in accordance with the provisions of Section V-B.3.b.
 - d. If a watercourse is to be altered or relocated, the following shall all be submitted by the permit applicant prior to issuance of a floodplain development permit:
 - i. a description of the extent of watercourse alteration or relocation; and
 - ii. a professional engineer's certified report on the effects of the proposed project on the flood-carrying capacity of the watercourse and the effects to properties located both upstream and downstream; and
 - iii. a map showing the location of the proposed watercourse alteration or relocation; and
 - iv. an Idaho Stream Channel Alteration Permit approval shall be provided by the applicant to the Floodplain Administrator.
 - e. Certification Exemptions. The following structures, are exempt from the elevation/floodproofing certification requirements specified in items a. and b. of this subsection:
 - i. Recreational Vehicles meeting requirements of Section V-B.5.a;
 - ii. Temporary Structures meeting requirements of Section V-B.6; and
 - iii. Accessory Structures less than 200 square feet meeting requirements of Section V-B.7.
4. Determinations for Existing Buildings and Structures. For applications for building permits to improve buildings and structures, including alterations, movement, enlargement, replacement, repair, change of occupancy, additions, rehabilitations,

renovations, improvements, repairs of damage, and any other improvement of or work on such buildings and structures, the Floodplain Administrator, in coordination with the Building Official, shall:

- a. Estimate the market value, or require the applicant to obtain an appraisal of the market value prepared by a qualified independent appraiser, of the building or structure before the start of construction of the proposed work. In the case of repair, the market value of the building or structure shall be the market value before the damage occurred and before any repairs are made;
 - b. Compare the cost to perform the improvement, the cost to repair a damaged building to its pre-damaged condition, or the combined costs of improvements and repairs, if applicable, to the market value of the building or structure;
 - c. Determine and document whether the proposed work constitutes substantial improvement or repair of substantial damage; and
 - d. Notify the applicant if it is determined that the work constitutes substantial improvement or repair of substantial damage and that compliance with the flood resistant construction requirements of the adopted Idaho Building Code and this ordinance is required.
5. Any other information deemed necessary for review of public safety and floodplain management requirements by the floodplain administrator.

SECTION IV-D. CORRECTIVE PROCEDURES

1. Violations to be Corrected. When the Floodplain Administrator finds violations of applicable State and local laws, it shall be his or her duty to notify the owner or occupant of the building of the violation. The owner or occupant shall immediately remedy each of the violations of law cited in such notification.
2. Actions in Event of Failure to Take Corrective Action. If the owner of a building or property shall fail to take prompt corrective action, the Floodplain Administrator shall give the owner written notice, by certified or registered mail to the owner's last known address or by personal service, stating:
 - a. that the building or property is in violation of the floodplain management regulations;
 - b. that a hearing will be held before the Floodplain Administrator at a designated place and time, not later than ten (10) days after the date of the notice, at which time the owner shall be entitled to be heard in person or by counsel and to present arguments and evidence pertaining to the matter; and
 - c. that following the hearing, the Floodplain Administrator may issue an order to alter, vacate, or demolish the building; or to remove fill as applicable.
3. Order to Take Corrective Action. If, upon a hearing held pursuant to the notice prescribed above, the Floodplain Administrator shall find that the building or development is in violation of the Flood Damage Prevention Ordinance, he or she shall issue an order in writing to the owner, requiring the owner to remedy the violation within a specified time period, not less than sixty (60) calendar days, nor more than one-hundred-eighty (180) calendar days. Where the Floodplain Administrator finds that there is imminent danger to life or other property, he or she may order that corrective action be taken in such lesser period as may be feasible.
4. Appeal. Any owner who has received an order to take corrective action may appeal the order to the local elected governing body by giving notice of appeal in writing to the Floodplain Administrator and the clerk within ten (10) days following issuance of the final order. In the absence of an appeal, the order of the Floodplain Administrator shall be final. The local governing body shall hear an appeal within a reasonable time and may affirm, modify and affirm, or revoke the order.
5. Failure to Comply with Order. If the owner of a building or property fails to comply with an order to take corrective action for which no appeal has been made or fails to comply with an order of the governing body following an appeal, the owner shall be guilty of a misdemeanor and shall be punished at the discretion of the court.

SECTION IV-E. VARIANCE PROCEDURES.

1. The City Council as established by the City of Rexburg, hereinafter referred to as the "appeal board", shall hear and decide requests for variances from the requirements of this ordinance.
2. Variances may be issued for:
 - a. the repair or rehabilitation of historic structures upon the determination that the proposed repair or rehabilitation will not preclude the structure's continued designation as a historic structure and that the variance is the minimum necessary to preserve the historic character and design of the structure;
 - b. functionally dependent facilities, if determined to meet the definition as stated in Article II of this ordinance, provided provisions of Sections IV-E.8.b, c, and d, have been satisfied, and such facilities are protected by methods that minimize flood damages during the base flood and create no additional threats to public safety; or
 - c. any other type of development, provided it meets the requirements of this Section.
3. In passing upon variances, the appeal board shall consider all technical evaluations, all relevant factors, all standards specified in other sections of this ordinance, and:
 - a. the danger that materials may be swept onto other lands to the injury of others;
 - b. the danger to life and property due to flooding or erosion damage;
 - c. the susceptibility of the proposed facility and its contents to flood damage and the effect of such damage on the individual owner;
 - d. the importance of the services provided by the proposed facility to the community;
 - e. the necessity to the facility of a waterfront location as defined under Article II of this ordinance as a functionally dependent facility, where applicable;
 - f. the availability of alternative locations, not subject to flooding or erosion damage, for the proposed use;
 - g. the compatibility of the proposed use with existing and anticipated development;
 - h. the relationship of the proposed use to the comprehensive plan and floodplain management program for that area;
 - i. the safety of access to the property in times of flood for ordinary and emergency vehicles;
 - j. the expected heights, velocity, duration, rate of rise, and sediment transport of the flood waters and the effects of wave action, if applicable, expected at the site; and
 - k. the costs of providing governmental services during and after flood conditions including maintenance and repair of public utilities and facilities such as sewer, gas, electrical and water systems, and streets and bridges.
4. The applicant shall include a written report addressing each of the above factors in Sections IV-E.3.a to .k with their application for a variance.
5. Upon consideration of the factors listed above and the purposes of this ordinance, the appeal board may attach such conditions to the granting of variances as it deems necessary to further the purposes and objectives of this ordinance.
6. Any applicant to whom a variance is granted shall be given written notice over the signature of a community official specifying the difference between the Base Flood Elevation (BFE) and the elevation to which the structure is to be built and that such construction below the BFE increases risks to life and property, and that the issuance of a variance to construct a structure below the BFE will result in increased premium rates for flood insurance up to \$25 per \$100 of insurance coverage. Such notification shall be maintained with a record of all variance actions, including justification for their issuance.

7. The Floodplain Administrator shall maintain the records of all appeal actions and report any variances to the Federal Insurance Administrator and the State of Idaho upon request.
8. Conditions for Variances:
 - a. Variances shall not be issued when the variance will make the structure in violation of other Federal, State, or local laws, regulations, or ordinances.
 - b. Variances shall not be issued within any designated floodway if the variance would result in any increase in flood levels during the base flood discharge.
 - c. Variances shall only be issued upon a determination that the variance is the minimum necessary, considering the flood hazard, to afford relief.
 - d. Variances shall only be issued prior to development permit approval.
 - e. Variances shall only be issued upon:
 - i. a showing of good and sufficient cause;
 - ii. a determination that failure to grant the variance would result in exceptional hardship; and
 - iii. a determination that the granting of a variance will not result in increased flood heights, additional threats to public safety, of extraordinary public expense, create nuisance, cause fraud on or victimization of the public, or conflict with existing local laws or ordinances.
9. A variance may be issued for solid waste disposal facilities or sites, hazardous waste management facilities, salvage yards, and chemical storage facilities that are located in Special Flood Hazard Areas provided that all of the following conditions are met.
 - a. The use serves a critical need in the community.
 - b. No feasible location exists for the use outside the Special Flood Hazard Area.
 - c. The lowest floor of any structure is elevated or floodproofed to at least the Flood Protection Elevation.
 - d. The use complies with all other applicable Federal, State and local laws.
10. The City of Rexburg will notify the State NFIP Coordinator of the Idaho Department of Water Resources of its intention to grant a variance at least thirty (30) calendar days prior to granting the variance.
11. Any person aggrieved by the decision of the appeal board may appeal such decision to the Court, as provided in Idaho Code 67-6535.

ARTICLE V. PROVISIONS FOR FLOOD HAZARD REDUCTION.

SECTION V-A. GENERAL STANDARDS

In all Special Flood Hazard Areas the following provisions are required:

1. All new construction, substantial improvements, and development shall be designed (or modified) and adequately anchored to prevent flotation, collapse, and lateral movement of the structure resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy.
2. All new construction, substantial improvements, and development shall be constructed with materials and utility equipment resistant to flood damage in accordance with the Technical Bulletin 2, Flood Damage-Resistant Materials Requirements, and available from the Federal Emergency Management Agency.
3. All new construction, substantial improvements, and development shall be constructed by methods and practices that minimize flood damages.
4. All new and replacement electrical, heating, ventilation, plumbing, and air conditioning equipment, and other service facilities shall be designed and/or located so as to prevent water from entering or accumulating within the components during conditions of flooding to the Flood Protection Elevation. These include, but are not limited to, HVAC equipment, water softener units, bath/kitchen fixtures, ductwork, electric/gas meter panels/boxes, utility/cable boxes, hot water heaters, and electric

outlets/switches.

5. All new and replacement water supply systems shall be designed to minimize or eliminate infiltration of floodwaters into the system.
6. All new and replacement sanitary sewage systems shall be designed to minimize or eliminate infiltration of floodwaters into the systems and discharges from the systems into flood waters.
7. On-site waste disposal systems shall be located and constructed to avoid impairment to them or contamination from them during flooding.
8. A fully enclosed area, of new construction and substantially improved structures, which is below the lowest floor used solely for parking, access, and storage shall:
 - a. be constructed entirely of flood resistant materials at least to the Flood Protection Elevation; and
 - b. include, in Zones AE flood openings to automatically equalize hydrostatic flood forces on walls by allowing for the entry and exit of floodwaters. To meet this requirement, the openings must either be certified by a professional engineer or architect or meet or exceed the following minimum design criteria:
 - i. A minimum of two flood openings on different sides of each enclosed area subject to flooding;
 - ii. The total net area of all flood openings must be at least one (1) square inch for each square foot of enclosed area subject to flooding;
 - iii. If a building has more than one enclosed area, each enclosed area must have flood openings to allow floodwaters to automatically enter and exit;
 - iv. The bottom of all required flood openings shall be no higher than one (1) foot above the interior or exterior adjacent grade;
 - v. Flood openings may be equipped with screens, louvers, or other coverings or devices, provided they permit the automatic flow of floodwaters in both directions; and
 - vi. Enclosures made of flexible skirting are not considered enclosures for regulatory purposes, and, therefore, do not require flood openings. Masonry or flood resistant wood underpinning, regardless of structural status, is considered an enclosure and requires flood openings as outlined above.
9. Any alteration, repair, reconstruction, or improvements to a structure, which is in compliance with the provisions of this ordinance, shall meet the requirements of "new construction" as contained in this ordinance.
10. Nothing in this ordinance shall prevent the repair, reconstruction, or replacement of a building or structure existing on the effective date of this ordinance and located totally or partially within the floodway, or stream setback, provided there is no additional encroachment below the Flood Protection Elevation in the floodway, or stream setback, and provided that such repair, reconstruction, or replacement meets all of the other requirements of this ordinance.
11. New solid waste disposal facilities and sites, hazardous waste management facilities, salvage yards, and chemical storage facilities shall not be permitted, except by variance as specified in Section IV-E.9. A structure or tank for chemical or fuel storage incidental to an allowed use or to the operation of a water treatment plant or wastewater treatment facility may be located in a Special Flood Hazard Area only if the structure or tank is either elevated or floodproofed to at least the Flood Protection Elevation and certified in accordance with the provisions of Section IV-C.3.
12. All subdivision proposals and other development proposals shall be consistent with the need to minimize flood damage and determined to be reasonably safe from flooding.
13. All subdivision proposals and other development proposals shall have public utilities and facilities such as sewer, gas, electrical, and water systems located and constructed

to minimize flood damage.

14. All subdivision proposals and other development proposals shall have adequate drainage provided to reduce exposure to flood hazards.
15. All subdivision proposals and other development proposals shall have received all necessary permits from those governmental agencies for which approval is required by Federal or State law, including Section 404 of the Federal Water Pollution Control Act Amendments of 1972, 33 USC 1334.
16. All subdivision proposals and other development proposals greater than 50 lots or 5 acres, whichever is the lesser, shall include within such proposals base flood elevation data.
17. When a structure is partially located in a Special Flood Hazard Area, the entire structure shall meet the requirements for new construction and substantial improvements.
18. When a structure is located in multiple flood hazard zones or in a flood hazard risk zone with multiple base flood elevations, the provisions for the more restrictive flood hazard risk zone and the highest Base Flood Elevation (BFE) shall apply.

SECTION V-B. SPECIFIC STANDARDS

In all Special Flood Hazard Areas where Base Flood Elevation (BFE) data has been provided, as set forth in Section III-B, the following provisions, in addition to the provisions of Section V-A, are required:

1. Residential Construction. New construction, substantial improvements, and development of any residential structure (including manufactured homes) shall have the lowest floor, including basement, and utilities including ductwork, elevated no lower than the Flood Protection Elevation, as defined in Article II of this ordinance.
2. Non-Residential Construction. New construction, substantial improvements, and development of any commercial, industrial or other non-residential structure shall have the lowest floor, including basement, and utilities including ductwork, elevated no lower than the Flood Protection Elevation, as defined in Article II of this ordinance. Structures located in Zone AE may be floodproofed to the Flood Protection Elevation in lieu of elevation provided that all areas of the structure, together with attendant utility and sanitary facilities, below the Flood Protection Elevation are watertight with walls substantially impermeable to the passage of water, using structural components having the capability of resisting hydrostatic and hydrodynamic loads and the effect of buoyancy. A registered professional engineer or architect shall certify that the floodproofing standards of this subsection are satisfied. Such certification shall be provided to the Floodplain Administrator as set forth in Section IV-C.3, along with the operational plan and the inspection and maintenance plan.
3. Manufactured Homes.
 - a. New and replacement manufactured homes shall be elevated so that the lowest floor of the manufactured home is no lower than the Flood Protection Elevation, as defined in Article II of this ordinance.
 - b. Manufactured homes shall be securely anchored to an adequately anchored foundation to resist flotation, collapse, and lateral movement, either by certified engineered foundation system, or in accordance with the most current edition of the Idaho Division of Building Safety's "Idaho Manufactured Home Installation Standard" in accordance with Idaho Code § 44-2201(2). Additionally, when the elevation would be met by an elevation of the chassis thirty-six (36) inches or less above the grade at the site, the chassis shall be supported by reinforced piers or engineered foundation. When the elevation of the chassis is above thirty-six (36) inches in height, an engineering certification is required.
 - c. All enclosures or skirting below the lowest floor shall meet the requirements of Sections V-A.8.a and b.
 - d. An evacuation plan must be developed for evacuation of all residents of all new, substantially improved, or substantially damaged manufactured home parks or

subdivisions located within flood prone areas. This plan shall be filed with and approved by the Floodplain Administrator and the local Emergency Management Coordinator.

4. Additions/Improvements.

- a. Additions and/or improvements to pre-FIRM structures when the addition and/or improvements in combination with any interior modifications to the existing structure are
 - i. not a substantial improvement, the addition and/or improvements must be designed to minimize flood damages and must not be any more non-conforming than the existing structure; or
 - ii. a substantial improvement, both the existing structure and the addition and/or improvements must comply with the standards for new construction.
- b. Additions to non-compliant post-FIRM structures that are a substantial improvement with no modifications to the existing structure other than a standard door in the common wall shall require only the addition to comply with the standards for new construction.
- c. Additions and/or improvements to non-compliant post-FIRM structures when the addition and/or improvements in combination with any interior modifications to the existing structure are
 - i. not a substantial improvement, the addition and/or improvements only must comply with the standards for new construction; or
 - ii. a substantial improvement, both the existing structure and the addition and/or improvements must comply with the standards for new construction.
- d. Any combination of repair, reconstruction, rehabilitation, addition, or improvement of a building or structure taking place during a 2 year period, the cumulative cost of which equals or exceeds 50 percent (50%) of the market value of the structure before the improvement or repair is started, must comply with the standards for new construction. For each building or structure, the 2 year period begins on the date of the first improvement or repair of that building or structure subsequent to the effective date of this ordinance. If the structure has sustained substantial damage, any repairs are considered substantial improvement regardless of the actual repair work performed. The requirement does not, however, include either:
 - i. any project for improvement of a building required to correct existing health, sanitary, or safety code violations identified by the building official and that are the minimum necessary to assume safe living conditions; or
 - ii. any alteration of a historic structure provided that the alteration will not preclude the structure's continued designation as a historic structure.

5. Recreational Vehicles. Recreational vehicles shall be either:

- a. Temporary Placement
 - i. be on site for fewer than 180 consecutive days and be fully licensed and ready for highway use (a recreational vehicle is ready for highway use if it is on its wheels or jacking system, is attached to the site only by quick disconnect type utilities, and has no permanently attached additions); or
- b. Permanent Placement.
 - i. Recreational vehicles that do not meet the limitations of Temporary Placement shall meet all the requirements for new construction, as set forth in Sections V-A, V-B.1, and V-B.3.

6. Temporary Non-Residential Structures. Prior to the issuance of a floodplain development permit for a temporary structure, the applicant must submit to the Floodplain Administrator a plan for the removal of such structure(s) in the event of a flash flood or other type of flood warning notification. The following information

shall be submitted in writing to the Floodplain Administrator for review and written approval:

- a. a specified time period for which the temporary use will be permitted. Time specified may not exceed six (6) months, renewable up to one (1) year;
 - b. the name, address, and phone number of the individual responsible for the removal of the temporary structure;
 - c. the time frame prior to the event at which a structure will be removed (i.e., immediately upon flood warning notification);
 - d. a copy of the contract or other suitable instrument with the entity responsible for physical removal of the structure; and
 - e. designation, accompanied by documentation, of a location outside the Special Flood Hazard Area, to which the temporary structure will be moved.
 - f. Temporary structures in the floodway must provide a Hydraulic and Hydrology Analysis along with a No-Rise Certification.
7. Accessory and Agricultural Structures (Appurtenant structures). When accessory structures (sheds, detached garages, etc.) used solely for parking, and storage are to be placed within a Special Flood Hazard Area, elevation or floodproofing certifications are required for all accessory structures in accordance with Section IV-C.3, and the following criteria shall be met:
- a. Accessory structures shall not be used for human habitation (including working, sleeping, living, cooking, or restroom areas);
 - b. Accessory structures shall not be temperature-controlled;
 - c. Accessory structures shall be designed to have low flood damage potential;
 - d. Accessory structures shall be constructed and placed on the building site so as to offer the minimum resistance to the flow of floodwaters;
 - e. Accessory structures shall be firmly anchored in accordance with the provisions of Section V-A.1;
 - f. All utility equipment and machinery, such as electrical, shall be installed in accordance with the provisions of Section V-A.4; and
 - g. Flood openings to facilitate automatic equalization of hydrostatic flood forces shall be provided below Flood Protection Elevation in conformance with the provisions of Section V-A.8.
 - h. Accessory structures not used solely for parking, access, and storage must be elevated per Sections V-B.1 and 2.
 - i. An accessory structure with a footprint less than 200 square feet and is a minimal investment of \$7,500 or less and satisfies the criteria outlined in paragraphs a - g above is not required to provide the elevation certificate per Section V-B.2.
8. Tanks. When gas and liquid storage tanks are to be placed within a Special Flood Hazard Area, the following criteria shall be met:
- a. Underground tanks in flood hazard areas shall be anchored to prevent flotation, collapse, or lateral movement resulting from hydrodynamic and hydrostatic loads during conditions of the base flood, including the effects of buoyancy (assuming the tank is empty);
 - b. Elevated above-ground tanks, in flood hazard areas shall be attached to and elevated to or above the design flood elevation on a supporting structure that is designed to prevent flotation, collapse, or lateral movement during conditions of the base flood. Tank-supporting structures shall meet the foundation requirements of the applicable flood hazard area;
 - c. Not elevated above-ground tanks may be permitted in flood hazard areas provided the tanks are anchored or otherwise designed and constructed to prevent flotation, collapse or lateral movement resulting from hydrodynamic and hydrostatic loads during conditions of the design flood, including the effects of buoyancy assuming the tank is empty and the effects of flood-borne debris.

- d. Tank inlets, fill openings, outlets and vents shall be:
 - i. at or above the flood protection elevation or fitted with covers designed to prevent the inflow of floodwater or outflow of the contents of the tanks during conditions of the base flood; and
 - ii. anchored to prevent lateral movement resulting from hydrodynamic and hydrostatic loads, including the effects of buoyancy, during conditions of the base flood.

9. Construction of Below-Grade Crawlspace.

- a. The interior grade of a crawlspace must not be below the BFE and must not be more than two (2) feet below the exterior lowest adjacent grade (LAG).
- b. The height of the below-grade crawlspace, measured from the interior grade of the crawlspace to the top of the crawlspace foundation wall, must not exceed four (4) feet at any point.
- c. There must be an adequate drainage system that removes floodwaters from the interior area of the crawlspace. The enclosed area should be drained within a reasonable time after a flood event.
- d. The velocity of floodwaters at the site should not exceed five (5) feet per second for any crawlspace.

10. Subdivision plats. Flood zones.

- a. A note must be provided on the final plat documenting the current flood zone in which the property or properties are located. The boundary line must be drawn on the plat in situations where two or more flood zones intersect over the property or properties being surveyed. An example note is as follows:

FEMA FIRM panel(s): #16065C0020D

FIRM effective date(s): 6/3/1991

Flood Zone(s): Zone X, Zone AE

Base Flood Elevation(s): AE _____.0 ft., etc.

Flood Zones are subject to change by FEMA & all land within a floodway or floodplain is regulated by Ordinance 1272 of the City Code.

- 11. Critical Facilities: Construction of new critical facilities shall be, to the extent possible, located outside the limits of the special flood hazard area (SFHA) (100-year floodplain). Construction of new critical facilities shall be permissible within the SFHA if no feasible alternative site is available. Critical facilities constructed within the SFHA shall have the lowest floor elevated three feet (3') above BFE or to the height of the 500-year flood, whichever is higher. Access to and from the critical facility should also be protected to the height utilized above. Floodproofing and sealing measures must be taken to ensure that toxic substances will not be displaced by or released into floodwaters. Access routes elevated to or above the level of the base flood elevation shall be provided to all critical facilities to the extent possible.

SECTION V-C. STANDARDS FOR RIVERINE FLOODPLAINS WITH BASE FLOOD ELEVATIONS BUT WITHOUT ESTABLISHED FLOODWAYS.

Along rivers and streams where Base Flood Elevation (BFE) data is provided by FEMA or is available from another source but floodways are not identified for a Special Flood Hazard Area on the FIRM or in the FIS report, the following requirements shall apply to all development within such areas:

- 1. Standards of Sections V-A and V-B; and
- 2. Until a regulatory floodway is designated, no encroachments, including fill, new construction, substantial improvements, or other development shall be permitted unless certification with supporting technical data by a registered professional engineer is provided demonstrating that the cumulative effect of the proposed development, when combined with all other existing and anticipated development, will not increase the water surface elevation of the base flood more than one foot at any point within the community.

ARTICLE VI. LEGAL STATUS PROVISIONS

SECTION VI-A. EFFECT ON RIGHTS AND LIABILITIES UNDER THE EXISTING FLOOD DAMAGE PREVENTION ORDINANCE

This ordinance, in part, comes forward by re-enactment of some of the provisions of Ordinance 717 adopted on April 17, 1991 and replaced by Ordinance 1129 adopted on April 15, 2015, and it is not the intention to repeal but rather to re-enact and continue to enforce without interruption of such existing provisions, so that all rights and liabilities that have accrued thereunder are reserved and may be enforced. The enactment of this ordinance shall not affect any action, suit, or proceeding instituted or pending. All provisions of Ordinance 717 adopted on April 17, 1991 and replaced by Ordinance 1129 adopted on April 15, 2015, which are not reenacted herein are repealed.

SECTION VI-B. EFFECT UPON OUTSTANDING FLOODPLAIN DEVELOPMENT PERMITS

Nothing herein contained shall require any change in the plans, construction, size, or designated use of any development or any part thereof for which a Floodplain Development Permit has been granted by the Floodplain Administrator or his or her authorized agents before the time of passage of this ordinance. Provided, however, that when construction is not begun under such outstanding permit within a period of 180 days subsequent to the date of issuance of the outstanding permit, construction or use shall be in conformity with the provisions of this ordinance.

SECTION VI-C. SEVERABILITY

The ordinance is hereby declared to be severable. Should any portion of this ordinance be declared invalid by a court of competent jurisdiction, the remaining provisions shall continue in full force and effect and shall be read to carry out the purpose(s) of the ordinance before the declaration of partial invalidity.

SECTION VI-D. EFFECTIVE DATE

This ordinance shall take effect and be in full force and effect from and after its passage, approval and due publication as provided by law.

ARTICLE VII. SUMMARY OF ORDINANCE:

AN ORDINANCE REPEALING AND REPLACING ORDINANCE 1129 TO UPDATE THE CITY'S FLOOD DAMAGE PREVENTION ORDINANCE TO MEET CURRENT STATE OF IDAHO AND FEMA REGULATIONS.

I, Stephen Zollinger, City Attorney for the city of Rexburg, Idaho, hereby declare and certify that in my capacity as City Attorney of the city of Rexburg, pursuant to Idaho Code section 50-901A (3) of the Idaho Code as amended, I have reviewed a copy of the above Summary of Ordinance, have found the same to be true and complete, and said Summary of Ordinance provides adequate notice to the public of the contents, including the exhibits, of Ordinance No. 1272.

DATED this 15th day of December, 2021.



Stephen Zollinger, City Attorney
Rexburg, Idaho

(SEAL)


Jerry Merrill, Mayor


Deborah Lovejoy, City Clerk

Deborah Lovejoy
Deborah Lovejoy, City Clerk

