

PERRIN

SUBARU Coolant Overflow Tank for 2015+ STI

2018-04-10

Thank you for purchasing this PERRIN product for your car! Installation of this product should only be performed by persons experienced with installation of aftermarket performance parts and proper operation of high performance vehicles. If vehicle needs to be raised off the ground for installation, the installer must use proper jacks, jack-stands and/or a professional vehicle hoist for safety of the installer and to protect property. If the vehicle is lifted improperly, serious injury or death may occur! Please read through all instructions before performing any portion of installation. If you have any questions, please contact our tech department prior to starting installation. We can be reached in any of the following methods:

Email Tech@PERRINperformance.com
Instant Chat off the main page of www.PERRINperformance.com
Or simply call our tech team at 503-693-1702

GENERAL MODIFICATION NOTE

Modifications to any vehicle can change the handling and performance. As with any vehicle extreme care must be used to prevent loss of control or roll-over during sharp turns or abrupt maneuvers. Always wear seat belts, and drive safely, recognizing that reduced speeds and specialized driving techniques may be required. Failure to drive a vehicle safely may result in serious injury or death. Do not drive a vehicle unless you are familiar with its unique handling characteristics and are confident of your ability to maintain control under all driving conditions. Some modifications (and combinations of modifications) are not recommended and may not be permitted in your state or country. Consult the owner's manual, service manual, instructions accompanying these products, and local laws before purchasing and installing these modifications. You are responsible for the legality and safety of the vehicle you modify using these components.

IMPORTANT NOTICES!

- There are many ways to install this part into the car. Please use the suggestions we have provided for your particular car. Almost every method of installation can be used in your application, but our suggestions are based on the future purchase of a PERRIN Front Mounted Intercooler.
- After installation, make sure to fill the coolant tank with roughly halfway with water or coolant.

Parts Included with the PERRIN Coolant Overflow Tank:

- (1) PERRIN Coolant Overflow Tank
- (1) 90 degree SS bracket
- (1) 5/16" Tee
- (1) M8x10mm hex head bolt
- (1) M8 Flat washer
- (1) M6x20mm Hex head bolt
- (1) M6 Flat Washer
- (14") 5/16" Silicone hose
- (1) 5/16" Vacuum cap
- (5) 8" Zipties

Installation for 2015-17 STI

1. Remove OEM coolant overflow tank from car by unsnapping small tab on left side of OEM Coolant overflow tank. NOTE: Take care in not spilling any coolant as this will be reused after PERRIN Coolant Overflow Tank is installed.
2. Remove rubber coolant pickup hose from small coolant pipes on back of radiator. Install supplied 5/16" cap over end of pipe.
3. The recommended location for the PERRIN Coolant Overflow tank is behind passenger side headlight. Locate 10mm bolt securing a ground wire on side of frame rail.



Using "L" Bracket

4. Using Supplied M8 Bolt and washer, bolt short leg of "L" bracket to one of (2) holes on bottom of coolant tank. We recommend the offset hole as this will provide the best fit on most cars. The other hole can be used in cases where different intercoolers are used or other aftermarket parts are installed.
5. Remove 10mm grounding bolt on side of frame rail. Secure tank to frame rail using OEM bolt through middle hole on bracket. NOTE: Make sure to put ground wire under head of bolt before tightening down. Once installed twisting or bending of bracket can be done to move tank to desired position.



6. Push supplied 5/16" silicone hose into medium size hole on top of tank. Push hose through hole until it hits the bottom of tank. Pull hose out roughly .5" so hose doesn't touch bottom of tank.
7. Locate OEM coolant overflow hose on right side of radiator. This is the thinner hose that connects to the pipe capped off with the 5/16" cap. Roughly halfway between radiator and engine cut hose and join both ends to supplied 5/16" tee.
8. Connect silicone hose to open leg of tee and cut hose to length.
9. Remove yellow cap from OEM coolant overflow tank by pinching small tabs together and pushing barb through hole. NOTE: If this breaks, you will need to purchase this part from Subaru.
10. Snap cap onto PERRIN Coolant Overflow Tank and push barbed end into remaining small hole on top of can.
11. Open cap and fill can roughly halfway with coolant (or water if no coolant) from OEM overflow tank. Snap cap back onto tank and take car for test drive. It is normal after the first test drive to see a little coolant come out of the top of the can. This is the system balancing the amount of coolant needed for the engine.
12. After a couple hours of operation it's a good idea to check tightness of bolts.

**Questions, Comments and Suggestions Contact: Tech@PERRINperformance.com
Visit Our Website for Instant Chat Options at www.PERRINperformance.com
Call Our Tech Team at 503-693-1702**