

## 20119-E | Emergency Slide Switch Fixed Wall Mount

The 60019 HID Badge Holder Tag is designed for operation within the ATLAS system architecture. This dual function transmitter is designed to provide staff, patients and vendors an alternative to a hand-held or belt clipped device.

Like the standard Heavy Duty Tag, the 60019 HID Badge Holder Tag utilizes a 2.4 GHz radio to accurately determine its location. This transmitter also uses the same channel to transmit data. The device design includes a secure housing for a standard ID badge as well as pull-cord notification. Ships with a nylon lanyard (device and lanyard are shown in picture).



### Features & Benefits

-  Compatible with the PALS® 9000 systems and Crisis Controller® Software
-  Able to transmit in the harshest RF environments
-  Single Push latching and unlatching with LED backlight
-  Long range transmission
-  Constructed using heavy duty ABS plastic
-  Extended battery life (*up to 12 months depending on features and usage*)
-  Full transmitter supervision includes alarms for low battery and inactivity
-  Returns accurate RF location and tracking information
-  Easy Installation
-  Available in flush or surface mount
-  Also available in flush or wall mount boxes

### Specifications

<b>DIMENSIONS</b>
1.6875" diameter, .625" width
<b>CASE</b>
Polycarbonate/ABS plastic/Lexan®
<b>WEIGHT</b>
Approximately .4 oz.
<b>OPERATING TEMPERATURE</b>
0° to 50° Centigrade
<b>BATTERY TYPE</b>
Standard CR 2032 coin cell battery or approved equal
<b>DATA TRANSMISSION SETTINGS</b>
PAN ID, Ch 1-10, power +1dBm to -25dBm

\*Battery Life when deployed will vary as a function of duty time used, frequency of alarm transmissions sent, LED brightness/frequency, location broadcast interval settings and environmental conditions at your site. Based upon 240mAh CR 2032 (Energizer). Ask your Actall Sales Representative for more details.

