









20134-E | Wireless Ceiling Mount Motion Detector

The 20134 Wireless 360° Ceiling mount motion detector transmitter effectively monitors indoor areas for human signature movements, which reduce false alarms.

The device is fully supervised, includes a lithium battery, and case tamper protection. When activated the transmitter sends an alarm to the Crisis Controller® software showing the location of the alarm.



Features & Benefits

-  Compatible with the PALS® 9000 systems and Crisis Controller® Software
-  Wireless four-element passive infrared intrusion detector for use in ceiling mount applications
-  Full transmitter supervision includes alarms for low battery, tamper, and inactivity
-  Returns accurate RF location
-  Equipped with a special lens that offers wide coverage patterns, even at low mounting heights
-  Highly sensitive to moving heat infrared radiation
-  Intelligent sleep timer extends battery life in high traffic environments and other causes of false alarms
-  Detection range of 65 feet (20m)

Specifications

DIMENSIONS
.6" x 2.7" x 2.2"
FREQUENCY
900 Mhz
BATTERY
Included
BATTERY LIFE
2 Years
SLEEP TIME
Variable

*Battery Life when deployed will vary as a function of duty time used, frequency of alarm transmissions sent, LED brightness/frequency, location broadcast interval settings and environmental conditions at your site. Based upon 240mAh CR 2032 (Energizer). Ask your Actall Sales Representative for more details.

