











## 60017 | Low Security Patient Tag

The 60017 Low Security Patient Tag is designed for operation within the ATLAS system architecture. This simple, reduced sized tag is designed to provide ATLAS installation the capability of tracking assets, personnel or patients in real time (RTLS).

Like all ATLAS devices, the 60017 utilizes a 2.4 GHz radio to accurately determine its location. The device can be carried on its own, affixed to the asset to be tracked or worn in a variety of positions utilizing the rubberized case (shown in picture).



### Features & Benefits

-  Communicates with ATLAS® LDN field devices via 2.4GHz spectrum transmission
-  Provides Low cost "tracking-only" capabilities for ATLAS® users
-  Reliable data transmission between the 60017 and LDN at a minimum of 50 feet
-  Extended battery life  
*(Up to 1.5 years, depending on user preferences and deployment profile \*)*
-  Low battery notification both on device and via transmission to ATLAS® system head end
-  Unique device ID within installation environment
-  Water resistant housing
-  On/Off feature available
-  No on-site device programming required
-  Device ships pre-programmed to user parameters

### Specifications

<b>DIMENSIONS</b>
1.6875" diameter, .625" width
<b>CASE</b>
Polycarbonate/ABS plastic/Lexan®
<b>WEIGHT</b>
Approximately .4 oz.
<b>OPERATING TEMPERATURE</b>
0° to 50° Centigrade
<b>BATTERY TYPE</b>
Standard CR 2032 coin cell battery or approved equal
<b>DATA TRANSMISSION SETTINGS</b>
PAN ID, Ch 1-10, power +1dBm to -25dBm

\*Battery Life when deployed will vary as a function of duty time used, frequency of alarm transmissions sent, LED brightness/frequency, location broadcast interval settings and environmental conditions at your site. Based upon 240mAh CR 2032 (Energizer). Ask your Actall Sales Representative for more details.

