

60019 | Badge Holder Tag

The 60019 Badge Holder Tag is designed for operation within the ATLAS system architecture. This dual function transmitter is designed to provide staff, patients and vendors an alternative to a hand-held or belt clipped duress device.

Like the standard Heavy Duty Tag, the Badge Holder Tag utilizes a 2.4 GHz radio to accurately determine its location. This transmitter also uses the same channel to transmit alarm data. The device design includes a secure housing for a standard ID badge as well as button and pull-cord duress notification. Ships with a nylon lanyard (device and lanyard are shown in picture).



Features & Benefits

-  Lower cost, feature rich and smaller form factor than part 60001
-  Communicates with ATLAS® LDN field devices via 2.4GHz spectrum transmission
-  Reliable data transmission between 60019 and LDN at a minimum of 50 feet
-  Extended battery life
*(Up to 1.5 years, depending on user preferences and deployment profile *)*
-  Low battery notification both on device and via transmission to ATLAS® system head end
-  Unique device ID within installation environment
-  Water resistant housing
-  On/Off feature available
-  No on-site device programming required
-  Device ships pre-programmed to user parameters
-  Two LED indicators for on-device user notifications
-  Button and pull-cord activation

Specifications

DIMENSIONS
1.6875" diameter, .625" width
CASE
Polycarbonate/ABS plastic/Lexan®
WEIGHT
Approximately .4 oz.
OPERATING TEMPERATURE
0° to 50° Centigrade
BATTERY TYPE
Standard CR 2032 coin cell battery or approved equal
DATA TRANSMISSION SETTINGS
PAN ID, Ch 1-10, power +1dBm to -25dBm

*Battery Life when deployed will vary as a function of duty time used, frequency of alarm transmissions sent, LED brightness/frequency, location broadcast interval settings and environmental conditions at your site. Ask your Actall Sales Representative for more details.

