

• TRUSTED QUALITY SINCE 1921 •

RUST-OLEUM®
SPECIALTY

**SPECIALTY
FLUORESCENT SPRAYS**

DESCRIPTION AND USES

Rust-Oleum® Fluorescent Sprays provide bright, highly visible colors on a variety of surfaces. They are ideal for indoor and outdoor projects such as crafts, hobbies, stenciling, marking, and color coding. These paints also glow under ultraviolet (black) light. For best results, apply over a white base coat.

PRODUCTS

SKU (11 ounces)	Description
272128	Rojo Naranja Fluorescente
272130	Verde Fluorescente
272131	Naranja Fluorescente
272132	Rosa Fluorescente
272133	Amarillo Fluorescente

PAINTING CONDITIONS

Use outdoors or in a well ventilated area. Use when temperature is between 10-32°C and humidity is below 85% to ensure proper drying. Do not apply to surfaces, when heated, exceed 93°C. Do not apply to galvanized steel. Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PRODUCT APPLICATION

SURFACE PREPARATION

Remove all dirt, grease, oil, salt and chemical contaminants by washing the surface with a commercial detergent, or other suitable cleaning method. Rinse with fresh water and allow to thoroughly dry. Remove loose paint and rust with a wire brush or sandpaper. Previously coated surfaces must be sound and in good condition. Smooth, hard, or glossy finishes should be scarified by sanding to create a surface profile.

Removal of old paint by sanding, scraping or other means may generate dust or fumes that contain lead. LEAD IS TOXIC.

PRODUCT APPLICATION (cont.)

PRIMING

Use of a Rust-Oleum primer provides superior adhesion and hiding and is especially recommended for bare wood and metal. Apply an undercoat of primer on darker surfaces for maximum brilliance.

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Hold can upright 25-35 cm from surface and spray in a steady back and forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface. Keep the can in motion while spraying. Apply two or more light coats a few minutes apart to avoid drips and runs. **Do not use near open flame.**

DRY & RECOAT

Dry and recoat times are based on 21°C (70°F) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 15 minutes and is fully dry in 24 hours. Recoat at any time.

CLEAN-UP

Clean valve immediately after use by turning can upside down and depressing spray button for 3-5 seconds. Clean up wet paint with xylene or mineral spirits. Throw away empty can in trash pick-up. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as mineral spirits. Do not insert any object into can valve opening.

TECHNICAL DATA

FLUORESCENT SPRAYS

PHYSICAL PROPERTIES

Physical Properties		FLOURESCENT SPRAYS
Resin Type		Modified Acrylic Lacquer
Pigment Type		Varies with color
Solvents		Acetone, Hexane, Toluene, Xylene
MIR		1.30 Max
Fill Weight		11 ounces
Practical Coverage at Recommended DFT (assumes 15% material loss)		Approximately 0.9-1.09 m ² /can
Dry Times at 21-27°C and 50% Relative Humidity	Touch	15 minutes
	Fully Dry	24 hours
	Recoat	Anytime
Dry Heat Resistance		93°C
Shelf Life		5 years
Flash Point		-104°C
Safety Information		For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.